IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Reissue Application of:	Bill L. Davis and Jesse S. Williamson
Entitled:	COMBINED LITHOGRAPHIC/FLEXOGRAPHIC PRINTING APPARATUS AND PROCESS
For:	Reissue of U.S. Patent 5,630,363
Filed:	May 20, 1999
Serial No.:	09/315,796
Examiner:	Not Yet Assigned
Group Art Unit:	2854

SUPPLEMENTAL STATEMENT OF PRIOR ART AND OTHER INFORMATION

APPENDIX 6

VI. File History Pertinent to Series Commencing with United States Serial No. 08/538,274 filed October 2, 1995 issued as U.S. Patent No. 5,598,777 on February 4, 1997

Index No.	Description
66	File History of European Patent Application No. EP 0 767 057 A3 entitled: A Rotary Offset Printing Press, Applicant: Howard W. DeMoore, Inventors: Howard W. DeMoore and Ronald M. Rendleman, Filed October 2, 1996, Date of Publication A3: June 10, 1998, Date of Publication A2: April 9, 1997

EPA/EPO/OEB
D-80298 München
089/2399-0
TX 523 656 epmu d
FAX 089/2399-4465

Europäisches Patentamt | European Patent Office | Office européen des brevets

Generaldirektion 2 | Directorate General 2 | Direction Générale 2

Rechnung / Invoice / Facture

BIRD & BIRD
ATTN: MS. CECILIA CHEUNG
90 FETTER LANE
LONDON EC4A 1JP
GREAT BRITAIN

Kundennummer
Customer number 01500251
Numéro du client

Datum/Date
20/07/99

Zeichen/Ref./Réf.	Anmeldung Nr./Application No./Demande n°/Patent Nr /Patent No./Brevet n°.
LIBRY.0666	96250220.9 2304 0767057

Anmelder/Applicant/Demandeur/Patentinhaber/Proprietor/Titulaire
DeMoore, Howard W.

Übersendung von/Transmission of/Envoi de

Antrag vom/Request dated/Requête du 18/06/99

- [X] Kopien bei Akteneinsicht nach Regel 94(3) EPÜ / Copies in the case of inspection of files pursuant to Rule 94(3) EPC / Copies en cas d'inspection publique selon la règle 94(3) CBE
- [ ] Beglaubigung / Certification / Certification
- [ ] ___ Prioritätsbeleg(e)/priority document(s)/document(s) de priorité R. 94(4)
- [ ] ___ Ausfertigung(en) der Patenturkunde nach Regel 54(2) EPÜ / Duplicate of the patent certificate pursuant to Rule 54(2) EPC / Duplicata du certificat de brevet, selon la Règle 54(2) CBE
- [ ] Auszug aus dem Register nach Regel 92(3) EPÜ / Extract from the register pursuant to Rule 92(3) EPC / Extrait du registre selon la Règle 92(3) CBE
- [ ] Auskunft aus den Akten nach Regel 95 EPÜ / Communication of information contained in the files pursuant to Rule 95 EPC / Communication d'informations contenues dans la dossier selon la Règle 95 CBE
- [ ] Akteneinsicht nach Regel 94(2) EPÜ / Inspection of files pursuant to Rule 94(2) EPC / Inspection publique selon la Règle 94(2) CBE

Rechnung Nr./Invoice No./Facture N° 20189457

Bitte bei Zahlung unbedingt angeben. / Indicate number without fail when paying. / Ce n° doit absolument être indiqué lors du paiement.

		EUR	Gegenwert / Equivalent / Contre-valeur GBP
Verwaltungsgebühr/Administration fee/Taxe d'administration		20,00	13,50
Kosten für Kopien/Cost of copies/Frais pour copies	204 Blätter) pages) feuilles)	122,40	81,60
Telefax		0,00	0,00
Summe/Total/Montant total		142,40	95,10
gezahlt sind/already paid/montant versé		0,00	0,00
noch zu zahlen/outstanding/reste à payer		142,40	95,10

- [ ] Der obengenannte Betrag wird abgebucht vom laufenden Konto Nr. / The above sum will be debited from deposit account No. / Le montant susmentionné sera débité du compte courant n° ___

- [X] Der obengenannte Betrag ist nach den auf der Anlage angegebenen Zahlungsmöglichkeiten zu entrichten (f. 2566.1 + 2). / The above sum is payable as detailed on the annex (f. 2566.1 + 2). / Le montant indiqué ci-dessus doit être acquitté suivant les modalités figurant sur l'annexe (f. 2566.1 + 2).

GARRY A G (TEL:2375)

EPA/EPO/OEB Form 2516 - 08.94

Formalprüfungsstelle/Formalities section/Section des formalités

EPA/EPO/OEB
D-80298 München
089/2399-0
TX 523 656 epmu d
FAX 089/2399-4465

Zahlungsmöglichkeiten

Nach Art. 5 der Gebührenordnung können die Gebühren wie folgt entrichtet werden:

a) durch Einzahlung oder Überweisung auf ein Bankkonto des Amts,

b) durch Einzahlung oder Überweisung auf ein Postscheckkonto des Amts,

c) durch Übergabe oder Übersendung von Schecks, die an die Order des Amts lauten,

d) durch Abbuchung von einem laufenden Konto beim Amt.

Die Zahlungswährung richtet sich nach der Währung des Staats, in dem das Konto geführt wird.

Der Betrag ist "ohne Kosten für den Empfänger" zu überweisen.

Das Verzeichnis der für die Europäische Patentorganisation eröffneten Bank- und Postscheckkonten, sowie der entsprechenden Zahlungswährungen ist auf Form 2566.2 abgedruckt.

Methods of payment

Under Art. 5 of the rules relating to Fees the fees may be paid as follows:

a) by payment or transfer to a bank account held by the Office,

b) by payment or transfer to a giro account held by the Office,

c) by delivery or remittance of cheques which are made payable to the Office,

d) by debiting a deposit account held with the Office.

The currency for payment is determined by the currency of the State in which the account is held.

The fee is to be transferred "at no costs to the payee".

The list of bank and giro accounts opened in the name of the European Patent Organisation and corresponding currencies for payment is reproduced on Form 2566.2.

Modalités de paiement

Aux termes de l'article 5 du Règlement relatif aux taxes, les taxes peuvent être acquittées comme suit:

a) par versement ou virement à un compte bancaire de l'Office,

b) par versement ou virement à un compte chèques postal de l'Office,

c) par remise ou envoi de chèques établis à l'ordre de l'Office,

d) par prélèvement sur un compte courant ouvert auprès de l'Office.

Le paiment doit être effectué dans la monnaie de l'Etat où le compte est ouvert.

Le virement doit se faire "sans frais pour le destinataire".

La liste des comptes bancaires et de chèques postaux ouverts au nom de l'Organisation européenne des brevets et des monnaies de paiement correspondantes est reprise sur le formulaire Form 2566.2.

Verzeichnis der für die Europäische Patentorganisation eröffneten Bank- und Postscheckkonten sowie der entsprechenden Zahlungswährungen

List of bank and giro accounts opened in the name of the European Patent Organisation and corresponding currencies for payment

Liste des comptes bancaires et de chèques postaux ouverts au nom de l'Organisation européenne des brevets et des monnaies de paiement correspondantes

	Bankkonten Bank accounts Comptes bancaires	Postscheckkonten Giro accounts Comptes de chèques postaux	Zahlungswährung Currency for payment Monnaies de paiement
AT	N° 102-133-851/00 (BLZ 12000) Bank Austria AG Am Hof 2 A-1010 Wien	N° 7451 030 Österreichische Postsparkasse Georg-Coch-Platz 2 A-1018 Wien	Österr. Schilling (ATS/EUR)
BE	N° 310-0443878-78 Banque Bruxelles Lambert BP 948 B-1000 Bruxelles	N° 000-1154425-29 Banque de la Poste B-1100 Bruxelles	Franc belge (BEF/EUR)
CH	N° 322 005 01'B UBS CH-8021 Zürich	N° 30-20788-1 Zahlungsverkehr PTT Verarbeitungszentrum CH-4040 Basel	Franc suisse (CHF)
CY	N° 0155-08-000-650 Bank of Cyprus 21, Evagoras Av. P. O. Box 1472 CY - 1509 Nicosia		Cyprus Pound (CYP)
DE	N° 3 338 800 00 (BLZ 700 800 00) Dresdner Bank Promenadeplatz 7 D-80273 München	N° 300-800 (BLZ 700 100 80) Postbank München D-80310 München	Deutsche Mark (DEM/EUR)
DK	N° 3015133759 Den Danske Bank Holmens Kanal Dept Holmens Kanal 2 DK-1020 København K.	N° 833-5893 GIROBANK A/S Girostrøget 1 DK-0300 Hoje Taastrup	Danske kroner (DKK)
ES	N° 0104/0328/85/0300400024 Banco Exterior de España Carrera de San Jeronimo 35 E-28014 Madrid	N° 00-18718728 Caja Postal Cuentas Extranjeras Pº de Recoletos, 5 E-28070 Madrid	Pesata española (ESP/EUR)
FI	N° 200110-102078 Merita Bank Senaatintori FIN-00020 Merita	N° 800013-00405 Leonia Fabianinkatu 23 FIN-00007 Helsinki	Suomen Markka (FIM/EUR)
FR	N° 200 20453, Code banque 30 004, Code guichet 00 567, Clé Rib 29 Banque Nationale de Paris Agence Franco-Etranger 2 Place de l'Opéra F-75002 Paris		Franc français (FRF/EUR)
GB	N° 60 271 489 (sorting-code 20-00-00) Barclays Bank PLC 54 Lombard Street P.O. Box 544 GB-London EC3V 9EX		Pound Sterling (GBP)
GR	N° 112002002007048 Credit Bank AE Athens Tower Branch 2, Messoghion Avenue GR-115 27 Athens		Greek Drachma (GRD)
IE	N° 30932201 (Bank Code 93-14-90) Bank of Ireland Lower Baggot Street Branch P.O. Box 3131 IRL-Dublin 2		Irish pound (IEP/EUR)
IT	N° 935932.01.84, ABI 02002 / CAB 03200 Banca Commerciale Italiana Via del Plebiscito 112 I-00186 Roma	N° 10568277 Posto Italiano C.U.A.S. Piazza Vesuvio 6 I-20144 Milano	Lira italiana (ITL/EUR)
LU	N° 7-109/9134/200 Banque Internationale à Luxembourg 69, route d'Esch L-2953 Luxembourg	N° 25421-37 Administration des P. & T. Chèques postaux BP 2500 L-1050 Luxembourg	Franc belge (BEF/EUR)
MC	N° 254 22754, Code Banque 30 004, Code Guichet 09 178, Clé Rib 91 Banque Nationale de Paris Succursale de Monte-Carlo Galerie Charles III Avenue des Spélugues Boite Postale 129 MC-98007 Monaco Cedex		Franc français (FRF/EUR)
NL	N° 51.38.38.547 ABN-AMRO Bank NV Knautordijk 1, Postbus 165 NL-2501 AP Den Haag	N° 4012627 Postbank NV NL-6800 MA Arnhem	Nederlandse Gulden (NLG/EUR)
PT	N° 0015/020 0309391145 / 05 Banco Pinto et Sotto Mayor Av. Fontes Pereira de Melo 7 P-1000 Lisboa		Escudo português (PTE/EUR)
SE	N° 122 697 100 Bankgiro N° 5843-6153 Svenska Handelsbanken S-10570 Stockholm	N° 7 41 53-8 Postgirot S-10508 Stockholm	Svenska kronor (SEK)

Antrag auf Erteilung eines europäischen Patents / Request for grant of a European patent / Requête en délivrance d'un brevet européen

1

Bestätigung einer bereits durch Telefax eingereichten Anmeldung / Confirmation of an application previously filed by facsimile / Confirmation d'une demande déjà déposée par télécopie
Nummer, Datum der Übermittlung der Telefax und Name der Empfangsbehörde / Number, date and name of receiving office / N° de télécopie, date de réception et nom de l'office récepteur

EPA EPO OEB Reçu / Received 07-10-1996 / Datum / Date / Behörde / Authority / Autorité

25

Nur für amtlichen Gebrauch / For official use only / Cadre réservé à l'administration

Anmeldenummer / Application No. / N° de la demande	RAKEY	1	96250231.7
Tag des Eingangs (Regel 24(2)) / Date of receipt (Rule 24(2)) / Date de réception (règle 24(2))	DREC	2	02 10. 1996
Tag des Eingangs beim EPA (Regel 24(4)) / Date of receipt at EPO (Rule 24(4)) / Date de réception à l'OEB (règle 24(4))	RENA	3	
Anmeldetag / Date of filing / Date de dépôt		4	

Tabulatoren-Positionen / Tabulation marks / Arrêts de tabulation

Es wird die Erteilung eines europäischen Patents und gemäß Artikel 94 die Prüfung der Anmeldung beantragt / Grant of a European patent, and examination of the application under Article 94, are hereby requested / Il est demandé la délivrance d'un brevet européen et, conformément à l'article 94, l'examen de la demande — EXAM 4 — 5 — X

Prüfungsantrag in einer zugelassenen Nichtamtssprache (siehe Merkblatt II, 5) / Request for examination in an admissible non-EPO language (see Notes II, 5) / Requête en examen dans une langue non officielle autorisée (voir notice II 5)

Zeichen des Anmelders oder Vertreters (max. 15 Positionen) / Applicant's or representative's reference (maximum 15 spaces) / Référence du demandeur ou du mandataire (max. 15 caractères ou espaces) — AREF — 6

P 44214

ANMELDER / APPLICANT / DEMANDEUR
Name / Nom — 7

Howard DeMoore

Anschrift / Address / Adresse — 8

10954 Shady Trail
Dallas, Texas 75220
U.S.A.

APPR 01 # 5921919
DEST

Zustellanschrift / Address for correspondence / Adresse pour la correspondance — 9

PADR

Staat des Wohnsitzes oder Sitzes / State of residence or of principal place of business / Etat du domicile ou du siège — 10

Staatsangehörigkeit / Nationality / Nationalité — 11

Telefon / Telephone / Téléphone — 12

Telex / Télex — Telefax / Fax / Téléfax — 13

Weitere(r) Anmelder auf Zusatzblatt / Additional applicant(s) on additional sheet / Autre(s) demandeur(s) sur feuille additionnelle — 14 ☐

VERTRETER / REPRESENTATIVE / MANDATAIRE: — 15
Name / Nom

(Nur einen Vertreter angeben, der in das europäische Patentregister eingetragen und an den zugestellt wird / Name only one representative, who is to be listed in the Register of European Patents and to whom notification is to be made / N'indiquer qu'un seul mandataire, qui sera inscrit au Registre européen des brevets et auquel signification sera faite)

FREP 01 121000111 # # #

UEXKÜLL & STOLBERG
Patentanwälte
Beselerstr. 4

D-22607 Hamburg

Zusammenschluß/Association Nr.1

Geschäftsanschrift / Address of place of business / Adresse professionnelle — 16

Telefon / Telephone / Téléphone — 17 (040) 899 6540

Telex / Télex — Telefax / Fax / Téléfax — 18 (040) 899 654 88

Weitere(r) Vertreter auf Zusatzblatt / Additional representative(s) on additional sheet / Autre(s) mandataire(s) sur feuille additionnelle — 19 ☐

EPA/EPO/OEB Form 1001.1 10.95 — TRAN — FILL

P 44214

Raum für Zeichen des Anmelders / Space for applicant's reference / Espace réservé à la référence du demandeur

Vollmacht / Authorisation / Pouvoir:

ist beigefügt / is enclosed / ci-joint 20

ist registriert unter Nummer / has been registered under No. / a été enregistré sous le n° GENA 21 Nummer / Number / Numéro

ERFINDER / INVENTOR / INVENTEUR: INVT 20 # # 22

Anmelder ist (sind) alleinige(r) Erfinder / The applicant(s) is (are) the sole inventor(s) / Le(s) demandeur(s) est (sont) le (les) seul(s) inventeur(s)

Erfindernennung auf gesondertem Schriftstück / Designation of inventor attached / Voir la désignation de l'inventeur ci-jointe 23 X

BEZEICHNUNG DER ERFINDUNG / TITLE OF INVENTION / TITRE DE L'INVENTION: 24

A Rotary Offset Printing Press

TIDE | TIEN | TIFR

0695796A1

PRIORITÄTSERKLÄRUNG / DECLARATION OF PRIORITY / DECLARATION DE PRIORITE PRIO 25

	Staat / State / Etat	Anmeldetag / Filing date / Date de dépôt	Aktenzeichen / Application No. / N° de la demande
1	US	02.10.1995	08/538,274
2			
3			
4			

01 # # #

02 # # #

03 # # #

04 # # #

Weitere Prioritätserklärung(en) auf Zusatzblatt / Additional declaration(s) of priority on additional sheet / Autre(s) déclaration(s) de priorité sur feuille additionnelle

MIKROORGANISMEN

Die Erfindung betrifft einen Mikroorganismus (mehrere Mikroorganismen) oder seine (ihre) Verwendung, der (die) auf Grund des Budapester Vertrages oder eines bilateralen Abkommens zwischen der Hinterlegungsstelle und dem EPA nach Regel 28(1) a) bei einer anerkannten Hinterlegungsstelle hinterlegt worden ist (sind), um die Bedingungen für die Offenbarung der Erfindung gemäß Artikel 83 in Verbindung mit Regel 28 zu erfüllen.

MICRO-ORGANISMS

The invention relates to and/or uses (a) micro-organism(s) deposited for the purposes of disclosure pursuant to Article 83 in conjunction with Rule 28 with a depositary institution recognised within the meaning of Rule 28(1) (a) under either the Budapest Treaty or a bilateral agreement between the institution and the EPO.

MICO 1 # | | | | | | #

26

MICRO-ORGANISMES

L'invention concerne un (plusieurs) micro-organisme(s) et/ou utilise un (plusieurs) micro-organisme(s), déposé(s) afin de satisfaire aux conditions d'exposé de l'invention prévues à l'article 83 ensemble la règle 28; à cet effet, le dépôt a été effectué auprès d'une autorité habilitée au sens de la règle 28(1) a), en vertu soit du Traité de Budapest, soit d'un accord bilatéral entre l'autorité et l'OEB.

Die Angaben nach Regel 28(1) c) sind in den technischen Anmeldungsunterlagen enthalten auf / The particulars referred to in Rule 28(1) (c) are given in the technical documents in the application on / Les indications visées à la règle 28(1) c) figurent dans les pièces techniques de la demande à la /aux 27

Seite(n) / page(s)	Zeile(n) / line(s) / ligne(s)

werden später mitgeteilt / will be submitted at a later date / seront communiquées ultérieurement 28

Die Empfangsbescheinigung(en) der Hinterlegungsstelle ist (sind) beigefügt / The receipt(s) of deposit issued by the depositary institution is (are) enclosed / Le(s) récépissé(s) de dépôt délivré(s) par l'autorité de dépôt est (sont) ci-joint(s) 29

wird (werden) nachgereicht / will be filed at a later date / sera (seront) produit(s) ultérieurement 30

P 44214

Raum für Zeichen des Anmelders / Space for applicant's reference / Espace réservé à la référence du demandeur

NUCLEOTID-UND AMINOSÄURESEQUENZEN / NUCLEOTIDE AND AMINO ACID SEQUENCES / SEQUENCES DE NUCLEOTIDES ET D'ACIDES AMINES SEQL (1) 31

Die Beschreibung enthält ein Sequenzprotokoll nach Regel 27a(1) / The description contains a sequence listing in accordance with Rule 27a(1) / La description contient une liste de séquences selon la règle 27bis(1)

Der vorgeschriebene maschinenlesbare Datenträger ist beigefügt / The prescribed machine readable data carrier is enclosed / Le support de données prescrit déchiffrable par machine est annexé

Es wird hiermit erklärt, daß die auf dem Datenträger gespeicherte Information mit dem schriftlichen Sequenzprotokoll übereinstimmt (Regel 27a(2)) / It is hereby stated that the information recorded on the data carrier is identical to the written sequence listing (Rule 27a(2)) /Il est déclaré par la présente que l'information figurant sur le support de données est identique à celle que contient la liste de séquences écrite (règle 27bis (2))

Verschiedene Anmelder für verschiedene Vertragsstaaten / Different applicants for different Contracting States / Différents demandeurs pour différents Etats contractants 32

Name(n) des (der) Anmelder(s) und benannte Vertragsstaaten / Name(s) of applicant(s) and designated Contracting States / Nom(s) du (des) demandeur(s) et des Etats contractants désignés

APPR 02 # #

BENENNUNG VON VERTRAGSSTAATEN / DESIGNATION OF CONTRACTING STATES / DESIGNATION D'ETATS CONTRACTANTS DEST 33

Österreich / Austria / Autriche	AT
Belgien / Belgium / Belgique	BE
Schweiz und Liechtenstein / Switzerland and Liechtenstein / Suisse et Liechtenstein	CH / LI
Deutschland / Germany / Allemagne	DE
Dänemark / Denmark / Danemark	DK
Spanien / Spain / Espagne	ES
Frankreich / France / France	FR
Vereinigtes Königreich / United Kingdom / Royaume-Uni	GB
Griechenland / Greece / Grèce	GR
Irland / Ireland / Irlande	IE
Italien / Italy / Italie	IT
Luxemburg / Luxembourg / Luxembourg	LU
Monaco / Monaco / Monaco	MC
Niederlande / Netherlands / Pays-Bas	NL
Portugal / Portugal / Portugal	PT
Schweden / Sweden / Suède	SE
Finland	FI

(Platz für Vertragsstaaten, für die das EPÜ nach Drucklegung dieses Formblatts in Kraft tritt)

(Space for Contracting States for which the EPC enters into force after this form has been printed)

(Prévu pour des Etats contractants à l'égard desquels la CBE entrera en vigueur après l'impression du présent formulaire)

VORSORGLICHE BENENNUNG SÄMTLICHER VERTRAGSSTAATEN
Die in Feld 33 angegebenen Staaten sind jene, für die die Zahlung der Benennungsgebühren vorgenommen wurde oder derzeit beabsichtigt ist. Vorsorglich werden jedoch sämtliche Staaten benannt, die zum Zeitpunkt der Einreichung dieser Anmeldung Vertragsstaaten des EPÜ sind (1.10.1995: AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LI, LU, MC, NL, PT, SE). Es wird ersucht, die Benennung der hier zusätzlich benannten Vertragsstaaten als vom Anmelder zurückgenommen zu betrachten, wenn für diese Staaten die Benennungsgebühren nicht bis zum Ablauf der in Regel 85a(2) vorgesehenen Nachfrist entrichtet werden. Es wird beantragt, von der Zustellung einer Mitteilung nach Regel 85a(1) und einer Mitteilung nach Regel 69(1) betreffend die hier zusätzlich benannten Vertragsstaaten abzusehen

PRECAUTIONARY DESIGNATION OF ALL CONTRACTING STATES
The States indicated in Section 33 are those for which it is at present intended to pay designation fees if these have not already been paid. As a precautionary measure, however, all those States which are Contracting States to the EPC at the time of filing this application are designated (1.10.1995: AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LI, LU, MC, NL, PT, SE). It is hereby requested that the designation of any additional States thereby included be regarded as withdrawn by the applicant if the designation fees have not been paid by the time the period of grace allowed in Rule 85a(2) expires. It is requested that no communication under Rule 85a(1) nor any communication under Rule 69(1) concerning the additional Contracting States designated above be notified.

33a ☒ **DESIGNATION A TOUTES FINS UTILES DE TOUS LES ETATS CONTRACTANTS**
Les Etats indiqués à la rubrique 33 sont ceux pour lesquels le paiement des taxes de désignation a été effectué ou pour lesquels l'on se propose actuellement de payer les taxes de désignation. Toutefois, à toutes fins utiles, sont désignés tous les Etats qui sont des Etats contractants de la CBE à la date du dépôt de la demande (1.10.1995: AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LI, LU, MC, NL, PT, SE). Il est demandé, au cas où les taxes de désignation pour les Etats contractants désignés à titre complémentaire ne seraient pas acquitées dans le délai supplémentaire prévu à la règle 85bis(2), que la désignation desdits Etats soit considérée comme retirée par le demandeur. Prière de ne pas procéder pour lesdits Etats contractants désignés à titre complémentaire à la signification d'une notification établie conformément à la règle 85bis(1) ou à la règle 69(1).

P 44214

Raum für Zeichen des Anmelders / Space for applicant's reference / Espace réservé à la référence du demandeur

ERSTRECKUNG DES EUROPÄISCHEN PATENTS

Diese Anmeldung gilt als Antrag, die europäische Patentanmeldung und das darauf erteilte europäische Patent auf alle Nicht-Vertragsstaaten des EPÜ zu erstrecken, mit denen am Tag ihrer Einreichung „Erstreckungsabkommen" bestehen (Derzeit: Litauen, Lettland, Slowenien)
Die Erstreckung wird jedoch nur wirksam, wenn die vorgeschriebene Erstreckungsgebühr entrichtet wird

EXTENSION OF THE EUROPEAN PATENT

This application is deemed to be a request to extend the European patent application and the European patent granted in respect of it to all non-Contracting States to the EPC with which "extension agreements" exist on the date on which the application is filed (Present situation: Lithuania, Latvia, Slovenia)
However, the extension only takes effect if the prescribed extension fee is paid

34

EXTENSION DES EFFETS DU BREVET EUROPEEN

La présente demande est reputée constituer une requête en extension des effets de la demande de brevet européen et du brevet européen délivré sur la base de cette demande à tous les États non parties à la CBE avec lesquels il existe un «accord d'extension» à la date du dépôt de la demande (Situation actuelle : Lituanie, Lettonie, Slovénie)
Toutefois l'extension ne produit ses effets que s'il est acquitté la taxe d'extension prescrite.

EXPT

Der Anmelder beabsichtigt derzeit, die Erstreckungsgebühr für die nachfolgend angekreuzten Staaten zu entrichten: /
The applicant currently intends to pay the extension fee for the States marked below with a cross: /
Le demandeur se propose actuellement d'acquitter la taxe d'extension pour les Etats dont le nom est coché ci-après :

Litauen / Lithuania / Lituanie	LT
Lettland / Latvia / Lettonie	LV
Slowenien / Slovenia / Slovénie	SI

Bereits Staaten, in denen nach Entrichtung dieser Gebühr ein Erstreckungsabkommen in Kraft treten soll / States for which extension agreements are due to enter into force after payment of this fee / Etats pour lesquels un accord d'extension doit entrer en vigueur après acquittement de cette taxe

Die Anmeldung ist eine Teilanmeldung / The application is a divisional application / La présente demande constitue une demande divisionnaire

DFIL 9 # PANR #

35 Nummer der früheren Anmeldung / No. of earlier application / Numéro de la demande initiale

Es handelt sich um eine Anmeldung nach Art. 61(1)b) / The application is an Art. 61(1)(b) application / La présente demande constitue une demande selon l'article 61(1)b)

DFIL 9 # EANR #

36 Nummer der früheren Anmeldung / No. of earlier application / Numéro de la demande initiale

Patentansprüche / Claims / Revendications CLMS

37 24 Zahl der Patentansprüche / Number of claims / Nombre de revendications

Weiterer Satz von Patentansprüchen (Art. 167(2)a))/ Additional set of claims (Art. 167(2)(a))/ Série supplémentaire de revendications (art. 167(2)a))

AUCL (1) — AT
AUCL (3) — ES
AUCL (4) — GR

38 Zahl der Patentansprüche / Number of claims / Nombre de revendications

Zur Veröffentlichung mit der Zusammenfassung wird vorgeschlagen Abbildung Nr. / With the abstract it is proposed to publish figure No. / Il est proposé de publier avec l'abrégé la figure n° DRAW (2)

39 1 Nummer / Number / Numéro

Zusätzliche Abschrift(en) der im europäischen Recherchenbericht angeführten Schriftstücke wird (werden) beantragt / Additional copy(ies) of the documents cited in the European search report is (are) requested / Prière de fournir une (des) copie(s) supplémentaire(s) des documents cités dans le rapport de recherche européenne ASOC

40 1 Anzahl der **zusätzlichen** Sätze von Abschriften / Number of **additional** sets of copies / Nombre de jeux **supplémentaires** de copies

P 44214
Raum für Zeichen des Anmelders / Space for applicant's reference / Espace réservé à la référence du demandeur

Es wird die Rückerstattung der Recherchengebühr gemäß Art. 10 GebO beantragt / Refund of the search fee is requested pursuant to Article 10 of the Rules relating to Fees / Le remboursement de la taxe de recherche est demandé en vertu de l'article 10 du règlement relatif aux taxes 41 ☐

Eine Kopie des Recherchenberichts ist beigefügt / A copy of the search report is attached / Une copie du rapport de recherche est jointe 42 ☐

AUTOMATISCHER ABBUCHUNGSAUFTRAG *(nur möglich für Inhaber von bei m EPA geführten laufenden Konten)*
AUTOMATIC DEBIT ORDER *(for EPO deposit account holders only)*
ORDRE DE PRELEVEMENT AUTOMATIQUE *(uniquement possible pour les titulaires de comptes courants ouverts auprès de l'OEB)*

Das Europäische Patentamt wird hiermit beauftragt, fällig werdende Gebühren und Auslagen nach Maßgabe der Vorschriften über das automatische Abbuchungsverfahren vom nebenstehenden laufenden Konto abzubuchen / The European Patent Office is hereby authorised, under the Arrangements for the automatic debiting procedure, to debit from the deposit account opposite any fees and costs falling due / Par la présente, il est demandé à l'Office européen des brevets de prélever du compte courant ci-contre les taxes et frais venant à échéance, conformément à la réglementation relative au prélèvement automatique

DECA

Nummer des laufenden Kontos / Deposit account number / Numero du compte courant | Name des Kontoinhabers / Account holder's name / Nom du titulaire du compte

43

Eventuelle Rückzahlungen auf das nebenstehende beim EPA geführte laufende Konto / Reimbursement, if any, to EPO deposit account opposite / Remboursements éventuels à effectuer sur le compte courant ci-contre ouvert auprès de l'OEB

DEPA

Nummer des laufenden Kontos / Deposit account number / Numero du compte courant | Name des Kontoinhabers / Account holder's name / Nom du titulaire du compte

44 2800 0327 UEXKÜLL & STOLBERG

Die vorgeschriebene Liste über die diesem Antrag beigefügten Unterlagen ergibt sich aus der vorbereiteten Empfangsbescheinigung (Seite 6 dieses Antrages) / The prescribed list of documents enclosed with this request is shown on the prepared receipt (page 6 of this request) / La liste prescrite des documents joints à cette requête figure sur le récépissé préétabli (page 6 de la présente requête) 45

Unterschrift(en) des (der) Anmelder(s) oder Vertreter(s) / Signature(s) of applicant(s) or representative(s) / Signature(s) du (des) demandeur(s) ou du (des) mandataire(s)

Ort / Place / Lieu Hamburg

Datum / Date 1. 10. 1996

UEXKÜLL & STOLBERG
(Association No. 1)

Arnulf Huber

46 Für Angestellte nach Artikel 133 (3) Satz 1 mit allgemeiner Vollmacht / For employees under Article 133 (3), 1st sentence, having a general authorisation / Pour les employés mentionnés à l'article 133, paragraphe 3, 1re phrase, munis d'un pouvoir général Nr. / No. / n° :

Name des oben Unterzeichneten bitte mit Schreibmaschine wiederholen. Bei juristischen Personen bitte die Stellung des (der) Unterzeichneten innerhalb der Gesellschaft mit Schreibmaschine angeben / Please type name under signature. In case of legal persons, the position of the signatory within the company should also be typed / Le ou les noms du ou des signataires doivent être également dactylographiés. S'il s'agit d'une personne morale, la position occupée au sein de celle-ci par le ou les signataires sera indiquée à la machine à écrire

P 44214
Raum für Zeichen des Anmelders / Space for applicant's reference / Espace réservé à la référence du demandeur

Empfangsbescheinigung / Receipt for documents / Récépissé de documents

(Liste der diesem Antrag beigefügten Unterlagen) (Checklist of enclosed documents) (Liste des documents annexés à la présente requête)

Es wird hiermit der Empfang der unten bezeichneten Dokumente bescheinigt / Receipt of the documents indicated below is hereby acknowledged / Nous attestons le dépôt des documents désignés ci-dessous

Wird im Falle der Einreichung der europäischen Patentanmeldung bei einer nationalen Behörde diese Empfangsbescheinigung vom Europäischen Patentamt übersandt, so ist sie als Mitteilung gemäß Regel 24(4) anzusehen (siehe Feld RENA). **Nach Erhalt der Mitteilung nach Regel 24(4) sind alle weiteren Unterlagen, die die Anmeldung betreffen, nur noch unmittelbar beim EPA einzureichen.** / If this receipt is issued by the European Patent Office and the European patent application was filed with a national authority it serves as a communication under Rule 24(4) (see Section RENA). **Once the communication under Rule 24(4) has been received, all further documents relating to the application must be sent directly to the European Patent Office.** / Si, en cas de dépôt de la demande de brevet européen auprès d'un service national, l'Office européen des brevets délivre le présent récépissé de documents, ce récépissé est réputé être la notification visée à la règle 24(4). **Dès que la notification visée à la règle 24(4) a été reçue, tous les autres documents relatifs à la demande doivent être adressés directement à l'OEB.**

UEXKÜLL & STOLBERG
Patentanwälte
Beselerstr. 4

D-22607 Hamburg

Nur für amtlichen Gebrauch / For official use only / Cadre réservé à l'administration

Datum / Date: 4.10.96

Europäisches Patentamt
European Patent Office
Office Européen des Brevets
DG 1 - Agence de Berlin
Gitschiner Str. 103, D-10969 Berlin
D-10958 Berlin

Howard Demoore

Unterschrift / Amtsstempel / Signature / Official stamp / Signature / Cachet officiel

Anmeldenummer / Application No. / N° de la demande		96 ...
Tag des Eingangs (Regel 24(2)) / Date of receipt (Rule 24(2)) / Date de réception (règle 24(2))	DREC	02 10. 1996
Zeichen des Anmelders/Vertreters / Applicant's/ Representative's ref. / Référence du demandeur ou du mandataire	AREF	P 44214
Nur nach Einreichung der Anmeldung bei einer nationalen Behörde: / Only after filing of the application with a national authority: / Seulement après le dépôt de la demande auprès d'un service national:		
Tag des Eingangs beim EPA (Regel 24(4)) / Date of receipt at EPO (Rule 24(4)) / Date de réception à l'OEB (règle 24(4))	RENA	

			Stückzahl / Number of copies / Nombre d'exemplaire	Blattzahl* eines Stücks / Number of sheets* in each copy / Nombre de feuilles* par exemplaire	Gesamtzahl der Abbildungen / Total number of figures / Nombre total de figures
A.	**Anmeldungsunterlagen und Prioritätsbeleg(e) / Application documents and priority document(s) / Pièces de la demande et document(s) de priorité**	47			
1	Beschreibung / Description		3 1	35	
2.	Patentansprüche / Claim(s) / Revendication(s)		3 1	12	
3.	Ggf. unterschiedliche Patentansprüche (Art. 167(2) a)) / Any different claims (Art. 167(2)(a)) / Le cas échéant, revendications différentes (art. 167(2) a))				
4	Zeichnung(en) / Drawing(s) / Dessin(s)	DRAW 1 #	3 1	10	18
5	Zusammenfassung / Abstract / Abrégé		3 1	1	
6	Übersetzung der Anmeldungsunterlagen / Translation of the application documents / Traduction des pièces de la demande				
7	Prioritätsbeleg(e) / Priority document(s) / Document(s) de priorité				

B.	**Der Anmeldung in der eingereichten Fassung liegen folgende Unterlagen bei: / This application as filed is accompanied by the items below: / A la présente demande sont annexées les pièces suivantes:**	48	
1	Einzelvollmacht / Specific authorisation / Pouvoir particulier		☐
2.	Allgemeine Vollmacht / General authorisation / Pouvoir général		☐
3.	Erfindernennung / Designation of inventor / Désignation de l'inventeur		☒
4	Früherer Recherchenbericht / Earlier search report / Rapport de recherche antérieure		☐
5.	Gebührenzahlungsvordruck (EPA Form 1010) / Voucher for the settlement of fees (EPO Form 1010) / Bordereau de règlement de taxes (OEB Form 1010)		☐
6.	Scheck (ausgeschlossen bei Einreichung bei den nationalen Behörden) / Cheque (not when filing with national authorities) / Chèque (pas de chèque en cas de dépôt auprès des services nationaux)		☐ Währung Betrag / Currency Amount / Monnaie Montant (Ausfüllung freigestellt / optional / facultatif)
7	Datenträger für Sequenzprotokoll / Data carrier for sequence listing / Support de données pour liste de séquences	SEQL (4)	☐
8	Zusatzblatt / Additional sheet / Feuille additionnelle		☐
9	Sonstige Unterlagen (bitte hier spezifizieren) / Other (please specify here) / Autres documents (veuillez préciser ici)		☐
C.	**Kopien dieser Empfangsbescheinigung / Copies of this receipt for documents / Copies du présent récépissé de documents**	49	2 Anzahl der Kopien / Number of copies / Nombre de copies

* Die Richtigkeit der Angabe der Blattzahl wurde bei Eingang nicht geprüft / No check was made on receipt that the number of sheets indicated was correct / L'exactitude du nombre de feuilles n'a pas été contrôlée lors du dépôt

P 44214

Raum für Zeichen des Anmelders / Space for applicant's reference / Espace réservé à la référence du demandeur

EPA/EPO/OEB Form 1001.6 10.95

ERFINDERNENNUNG / DESIGNATION OF INVENTOR / DESIGNATION DE L'INVENTEUR

Nr. der Anmeldung / Application N° / N° de la demande

Zeichen des Vertreters
Representative's Reference
Référence du mandataire
P 44214

In Sachen der Europäischen Patentanmeldung *(Bezeichnung der Erfindung)*
In respect of the European patent application *(title of the invention)*
En ce qui concerne la demande de brevet européen (Titre de l'invention)

A Rotary Offset Printing Press

nennen die Unterzeichneten
We, the undersigned
les soussignés

UEXKÜLL & STOLBERG
Patentanwälte
Beselerstr. 4
D-22607 HAMBURG
Zusammenschluß Nr. 1 / Association No. 1 / Groupement No. 1

als Erfinder:
do hereby designate as inventor(s):
désigne(nt) en tant qu'inventeur(s):

1. DeMoore, Howard
   10954 Shady Trail
   Dallas, Texas 75220
   U.S.A.

2. Rendleman, Ronald M.
   4331 Royal Ridge
   Dallas, Texas 75229
   U.S.A.

3. Bird, John W.
   1514 Iroquois Circle
   Carollton, Texas 75007
   U.S.A.

(Weitere Erfinder sind auf einem gesonderten Blatt angegeben)
☐ (Additional inventors indicated on supplementary sheet)
(les autres inventeurs sont mentionnés sur une feuille supplémentaire)

Erklärung darüber, wie der (die) Anmelder das Recht auf das Europäische Patent erlangt hat (haben):
Statement indicating the origin of right to the European patent:
Déclaration indiquant l'origine de l'acquisition du droit au brevet:

Assignment dated March 4, 1995

Ort / Place / Lieu HAMBURG

Datum / Date 28. 9. 1996

Unterschrift des Vertreters
Signature of Representative
Signature du mandataire

UEXKÜLL & STOLBERG

Arnulf Huber

Zusammenschluß Nr. 1 / Association No. 1 / Groupement N° 1

Field of the Invention

This invention relates generally to sheet-fed or web-fed, rotary offset lithographic printing presses, and more particularly, to a new and improved inking/coating apparatus for the in-line application of aqueous or flexographic printing inks, primer or protective/decorative coatings applied simultaneously to the plate and blanket of the first or any consecutive printing unit of any lithographic printing press.

Background of the Invention

Conventional sheet-fed, rotary offset printing presses typically include one or more printing units through which individual sheets are fed and printed. After the last printing unit, freshly printed sheets are transferred by a delivery conveyor to the delivery end of the press where the freshly printed and/or coated sheets are collected and stacked uniformly. In a typical sheet-fed, rotary offset printing press such as the Heidelberg Speedmaster line of presses, the delivery conveyor includes a pair of endless chains carrying gripper bars with

gripper fingers which grip and pull freshly printed sheets from the last impression cylinder and convey the sheets to the sheet delivery stacker.

Since the inks used with sheet fed rotary offset printing presses are typically wet and tacky, special precautions must be taken to prevent marking and smearing of the freshly printed or coated sheets as the sheets are transferred from one printing unit to another. The printed ink on the surface of the sheet dries relatively slowly and is easily smeared during subsequent transfer between printing units. Marking, smearing and smudging can be prevented by a vacuum assisted sheet transfer apparatus as described in the following U.S. Patents: 5,113,255; 5,127,329; 5,205,217; 5,228,391; 5,243,909; and 5,419,254, all to Howard W. DeMoore, co-inventor, and manufactured and sold by Printing Research, Inc. of Dallas, Texas, U.S.A. under its trademark BACVAC™.

In some printing jobs, offsetting is prevented by applying a protective and/or decorative coating material over all or a portion of the freshly printed sheets. Some coatings are formed of a UV-curable or water-dispersed resin applied as a liquid solution over the freshly printed sheets to protect the ink from offsetting or set-off and improve the appearance of the freshly printed sheets. Such coatings are particularly desirable when decorative or protective finishes are applied in the printing of posters, record jackets, brochures, magazines, folding cartons and the like.

<u>Description of the Prior Art</u>

Various arrangements have been made for applying the coating as an in-line printing operation by using the last printing unit of the press as the coating application unit. For example, U.S. Patents 4,270,483; 4,685,414; and 4,779,557 disclose coating apparatus which can be moved into position to permit the blanket cylinder of the last printing unit of a printing press to be used to apply a coating material over the freshly printed

sheets. In U.S. Patent 4,841,903 (Bird) there are disclosed coating apparatus which can be selectively moved between the plate cylinder or the blanket cylinder of the last printing unit of the press so the last printing unit can only be used for coating purposes. However, when coating apparatus of these types are being used, the last printing unit cannot be used to print ink to the sheets, but rather can only be used for the coating operation. Thus, while coating with this type of in-line coating apparatus, the printing press loses the capability of printing on the last printing unit as it is converted to a coating unit.

The coater of U.S. Patent 5,107,790 (Sliker et al) is retractable along an inclined rail for extending and retracting a coater head into engagement with a blanket on the blanket cylinder. Because of its size, the rail-retractable coater can only be installed between the last printing unit of the press and the delivery sheet stacker, and cannot be used for interunit coating. The coater of U.S. Patent 4,615,293 (Jahn) provides two separate, independent coaters located on the dampener side of a converted printing unit for applying lacquer to a plate and to a rubber blanket. Consequently, although a plate and blanket are provided, the coating unit of Jahn's press is restricted to a dedicated coating operation only.

Proposals have been made for overcoming the loss of a printing unit when in-line coating is used, for example as set forth in U.S. Patent 5,176,077 to Howard W. DeMoore (co-inventor and assignee), which discloses a coating apparatus having an applicator roller positioned to apply the coating material to the freshly printed sheet while the sheet is still on the last impression cylinder of the press. This allows the last printing unit to print and coat simultaneously, so that no loss of printing unit capability results.

Some conventional coaters are rail-mounted and occupy a large amount of press space and reduce access to the press. Elaborate equipment is needed for retracting such coaters from the

operative coating position to the inoperative position, which reduces access to the printing unit.

Accordingly, there is a need for an in-line inking/coating apparatus which does not result in the loss of a printing unit, does not extend the length of the press, and which can print and coat aqueous and flexographic inks and coating materials simultaneously onto the plate and blanket on any lithographic printing unit of any lithographic printing press, including the first printing unit.

Objects of the Invention

Accordingly, a general object of the present invention is to provide improved inking/coating apparatus which is capable of selectively applying ink or coating material to a plate on a plate cylinder or ink or coating material to a plate or blanket on a blanket cylinder.

A specific object of the present invention is to provide improved inking/coating apparatus of the character described which is extendable into inking/coating engagement with either a plate on a plate cylinder or to a plate or blanket on a blanket cylinder.

A related object of the present invention is to provide improved inking/coating apparatus of the character described which is capable of being mounted on any lithographic printing unit of the press and does not interfere with operator access to the plate cylinder, blanket cylinder, or adjacent printing units.

Another object of the present invention is to provide improved inking/coating apparatus of the character described, which can be moved from an operative inking/coating engagement position adjacent to a plate cylinder or a blanket cylinder to a non-operative, retracted position.

Still another object of the present invention is to provide improved inking/coating apparatus of the character described, which can be used for applying aqueous, flexographic and ultra-violet curable inks and/or coatings in combination with

lithographic, flexographic and waterless printing processes on any rotary offset printing press.

A related object of the present invention is to provide improved inking/coating apparatus of the character described, which is capable of applying aqueous or flexographic ink or coating material on one printing unit, for example the first printing unit, and drying the ink or coating material before it is printed or coated on the next printing unit so that it can be overprinted or overcoated immediately on the next printing unit with waterless, aqueous, flexographic or lithographic inks or coating materials.

Yet another object of the present invention is to provide improved inking/coating apparatus for use on a multiple color rotary offset printing press that can apply ink or coating material separately and/or simultaneously to the plate and/or blanket of a printing unit of the press from a single operative position, and from a single inking/coating apparatus.

A related object of the present invention is to provide improved inking/coating apparatus of the character described, in which virtually no printing unit adjustment or alteration is required when the inking/coating apparatus is converted from plate to blanket printing or coating and vice versa.

Another object of the present invention is to provide improved inking/coating apparatus that can be operably mounted in the dampener space of any lithographic printing unit for inking/coating engagement with either a plate on a plate cylinder or a plate or blanket on a blanket cylinder, and which does not interfere with operator movement or activities in the interunit space between printing units.

Summary of the Invention

The foregoing objects are achieved by a retractable, in-line inking/coating apparatus which is mounted on the dampener side of any printing unit of a rotary offset press for movement between an operative (on-impression) inking/coating position and

a retracted, disengaged (off-impression) position. The inking/coating apparatus includes an applicator roller which is movable into and out of engagement with a plate on a plate cylinder or a blanket on a blanket cylinder. The inking/coating applicator head is pivotally coupled to a printing unit by pivot pins which are mounted on the press side frames in the traditional dampener space of the printing unit in parallel alignment with the plate cylinder and the blanket cylinder. This dampener space mounting arrangement allows the inking/coating unit to be installed between any adjacent printing units on the press.

In the preferred embodiment, the applicator head includes vertically spaced pairs of cradle members with one cradle pair being adapted for supporting an inking/coating applicator roller in alignment with a plate cylinder, and the other cradle pair supporting an inking/coating applicator roller in alignment with the blanket cylinder, respectively, when the applicator head is in the operative position. Because of the pivotal support provided by the pivot pins, the applicator head can be extended and retracted within the limited space available in the traditional dampener space, without restricting operator access to the printing unit cylinders and without causing a printing unit to lose its printing capability.

When the inking/coating apparatus is used in combination with a flexographic printing plate and aqueous or flexographic ink or coating material, the water component of the aqueous or flexographic ink or coating material on the freshly printed or coated sheet is evaporated and dried by a high velocity, hot air interunit dryer and a high volume heat and moisture extractor assembly so that the freshly printed ink or coating material is dry before the sheet is printed or coated on the next printing unit. This quick drying process permits a base layer or film of ink, for example opaque white or metallic (gold, silver or other metallics) ink to be printed on the first printing unit, and then overprinted on the next printing unit without back-trapping or dot gain.

The construction and operation of the present invention will be understood from the following detailed description taken in conjunction with the accompanying drawings which disclose, by way of example, the principles and advantages of the present invention.

Brief Description of the Drawings

FIGURE 1 is a perspective view of a sheet fed, rotary offset printing press having inking/coating apparatus embodying the present invention;

FIGURE 2 is a simplified perspective view of the single head, dual cradle inking/coating apparatus of the present invention;

FIGURE 3 is a schematic side elevational view of the printing press of Figure 1 having single head, dual cradle inking/coating apparatus installed in the traditional dampener position of the first, second and last printing units;

FIGURE 4 is a simplified side elevational view showing the single head, dual cradle inking/coating apparatus in the operative inking/coating position for simultaneously printing on the printing plate and blanket on the fourth printing unit;

FIGURE 5 is a simplified side elevational view showing the single head, dual cradle inking/coating apparatus in the operative position for spot or overall inking or coating on the blanket of the first printing unit, and showing the dual cradle inking/coating apparatus in the operative position for spot or overall inking or coating on the printing plate of the second printing unit;

FIGURE 6 is a simplified side elevational view of the single head, dual cradle inking/coating apparatus of FIGURE 4 and FIGURE 5, partially broken away, showing the single head, dual cradle inking/coating apparatus in the operative coating position and having a sealed doctor blade reservoir assembly for spot or overall coating on the blanket;

FIGURE 7 is a schematic view showing a heat exchanger and pump assembly connected to the single head, dual cradle inking/coating apparatus for circulating temperature controlled ink or coating material to the inking/coating apparatus;

FIGURE 8 is a side elevational view, partially broken away, and similar to FIGURE 6 which illustrates an alternative coating head arrangement;

FIGURE 9 is a simplified elevational view of a printing unit which illustrates pivotal coupling of the inking/coating apparatus on the printing unit side frame members;

FIGURE 10 is a view similar to FIGURE 2 in which a pair of split applicator rollers are mounted in the upper cradle and lower cradle, respectively;

FIGURE 11 is a side elevational view of a split applicator roller;

FIGURE 12 is a perspective view of a doctor blade reservoir which is centrally partitioned by a seal element;

FIGURE 13 is a sectional view showing sealing engagement of the split applicator roller against the partition seal element of FIGURE 12;

FIGURE 14 is a view similar to FIGURE 8 which illustrates an alternative inking/coating embodiment;

FIGURE 15 is a simplified side elevational view of a substrate which has a bronzed-like finish which is applied by simultaneous operation of the dual applicator roller embodiment of FIGURE 14;

FIGURE 16 is a side elevational view, partly in section, of a pan roller having separate transfer surfaces mounted on a split fountain pan;

FIGURE 17 is a simplified side elevational view of the dual cradle inking/coating apparatus, partially broken away, which illustrates an alternative inking/coating head apparatus featuring a single doctor blade assembly, anilox applicator roller mounted on the lower cradle; and

FIGURE 18 is a side elevational view, partly in section, of a single doctor blade anilox applicator roller assembly having separate transfer surfaces, and a split fountain pan having separate fountain compartments, with the separate fountain compartments being supplied with different inks or coating materials from separate off-press sources.

Detailed Description of the Preferred Embodiments

As used herein, the term "processed" refers to printing and coating methods which can be applied to either side of a substrate, including the application of lithographic, waterless, UV-curable, aqueous and flexographic inks and/or coatings. The term "substrate" refers to sheet and web material. Also, as used herein, the term "waterless printing plate" refers to a printing plate having image areas and non-image areas which are oleophilic and oleophobic, respectively. "Waterless printing ink" refers to an oil-based ink which does not contain a significant aqueous component. "Flexographic plate" refers to a flexible printing plate having a relief surface which is wettable by flexographic ink or coating material. "Flexographic printing ink or coating material" refers to an ink or coating material having a base constituent of either water, solvent or UV-curable liquid. "UV-curable lithographic printing ink and coating material" refers to oil-based printing inks and coating materials that can be cured (dried) photomechanically by exposure to ultraviolet radiation, and that have a semi-paste or gel-like consistency. "Aqueous printing ink or coating material" refers to an ink or coating material that predominantly contains water as a solvent, diluent or vehicle. A "relief plate" refers to a printing plate having image areas which are raised relative to non-image areas which are recessed.

As shown in the exemplary drawings, the present invention is embodied in a new and improved in-line inking/coating apparatus, herein generally designated 10, for applying aqueous, flexographic or UV-curable inks or protective and/or decorative

coat[illegible]s to sheets or webs printe[illegible]in a sheet-fed or web-fed, rotary offset printing press, herein generally designated 12. In this instance, as shown in FIGURE 1, the inking/coating apparatus 10 is installed in a four unit rotary offset printing press 12, such as that manufactured by Heidelberger Druckmaschinen AG of Germany under its designation Heidelberg Speedmaster SM102 (40", 102cm).

The press 12 includes a press frame 14 coupled at one end, herein the right end, to a sheet feeder 16 from which sheets, herein designated S, are individually and sequentially fed into the press, and at the opposite end, with a sheet delivery stacker 20 in which the freshly printed sheets are collected and stacked. Interposed between the sheet feeder 16 and the sheet delivery stacker 20 are four substantially identical sheet printing units 22, 24, 26 and 28 which can print four different colors onto the sheets as they are transferred through the press 12. The printing units are housed within printing towers T1, T2, T3 and T4 formed by side frame members 14, 15. Each printing tower has a delivery side 25 and a dampener side 27. A dampener space 29 is partially enclosed by the side frames on the dampener side of the printing unit.

As illustrated, the printing units 22, 24, 26 and 28 are substantially identical and of conventional design. The first printing unit 22 includes an in-feed transfer cylinder 30, a plate cylinder 32, a blanket cylinder 34 and an impression cylinder 36, all supported for rotation in parallel alignment between the press side frames 14, 15 which define printing unit towers T1, T2, T3 and T4. Each of the first three printing units 22, 24 and 26 have a transfer cylinder 38 disposed to transfer the freshly printed sheets from the adjacent impression cylinder and transfer the freshly printed sheets to the next printing unit via an intermediate transfer drum 40.

The last printing unit 28 includes a delivery cylinder 42 mounted on a delivery shaft 43. The delivery cylinder 42 supports the freshly printed sheet 18 as it is transferred from

the last impression cylinder 36 to the delivery conveyor system, generally designated 44, which transfers the freshly printed sheet to the sheet delivery stacker 20. To prevent smearing during transfer, a flexible covering is mounted on the delivery cylinder 42, as described and claimed in U.S. Patent 4,402,267 to Howard W. DeMoore, which is incorporated herein by reference. The flexible covering is manufactured and sold by Printing Research, Inc. of Dallas, Texas, U.S.A., under its trademark SUPER BLUE®. Optionally, a vacuum-assisted sheet transfer assembly manufactured and sold by Printing Research, Inc. of Dallas, Texas, U.S.A., under its trademark BACVAC® can be substituted for the delivery transfer cylinder 42 and flexible covering.

The delivery conveyor system 44 as shown in FIGURE 2 is of conventional design and includes a pair of endless delivery gripper chains 46, only one of which is shown carrying at regular spaced locations along the chains, laterally disposed gripper bars having gripper fingers used to grip the leading edge of a freshly printed or coated sheet 18 after it leaves the nip between the impression cylinder 36 and delivery cylinder 42 of the last printing unit 28. As the leading edge is gripped by the gripper fingers, the delivery chains 46 pull the sheet away from the last impression cylinder 36 and convey the freshly printed or coated sheet to the sheet delivery stacker 20.

Prior to reaching the delivery sheet stacker, the freshly printed and/or coated sheets S pass under a delivery dryer 48 which includes a combination of infra-red thermal radiation, high velocity hot air flow and a high performance heat and moisture extractor for drying the ink and/or the protective/decorative coating. Preferably, the delivery dryer 48, including the high performance heat and moisture extractor is constructed as described in U.S. Application Serial Number 08/116,711, filed September 3, 1993, entitled "Infra-Red Forced Air Dryer and Extractor" by Howard C. Secor, Ronald M. Rendleman and Paul D. Copenhaver, commonly assigned to the assignee of the present invention, Howard W. DeMoore, and licensed to Printing

Research, Inc. of Dallas, Texas, U.S.A., which manufactures and markets the delivery dryer 48 under its trademark AIR BLANKET™.

In the exemplary embodiment shown in FIGURE 3, the first printing unit 22 has a flexographic printing plate PF mounted on the plate cylinder, and therefore neither an inking roller train nor a dampening system is required. A flexographic printing plate PF is also mounted on the plate cylinder of the second printing unit 24. The form rollers of the inking roller train 52 shown mounted on the second printing unit 24 are retracted and locked off to prevent plate contact. Flexographic ink is supplied to the flexographic plate PF of the second printing unit 24 by the inking/coating apparatus 10.

A suitable flexographic printing plate PF is offered by E.I. du Pont de Nemours of Wilmington, Delaware, U.S.A., under its trademark CYREL®. Another source is BASF Aktiengesellschaft of Ludwigshafen, Germany, which offers a suitable flexographic printing plate under its trademark NYLOFLEX®.

The third printing unit 26 as illustrated in FIGURE 3 and FIGURE 4 is equipped for lithographic printing and includes an inking apparatus 50 having an inking roller train 52 arranged to transfer ink Q from an ink fountain 54 to a lithographic plate P mounted on the plate cylinder 32. This is accomplished by a fountain roller 56 and a ductor roller 57. The fountain roller 56 projects into the ink fountain 54, whereupon its surface picks up ink. The lithographic printing ink Q is transferred from the fountain roller 56 to the inking roller train 52 by the ductor roller 57. The inking roller train 52 supplies ink Q to the image areas of the lithographic printing plate P.

The lithographic printing ink Q is transferred from the lithographic printing plate P to an ink receptive blanket B which is mounted on the blanket cylinder 34. The inked image carried on the blanket B is transferred to a substrate S as the substrate is transferred through the nip between the blanket cylinder 34 and the impression cylinder 36.

The inking roller arrangement 52 illustrated in FIGURE 3 and FIGURE 4 is exemplary for use in combination with lithographic ink printing plates P. It is understood that a dampening system 58 having a dampening fluid reservoir DF is coupled to the inking roller train 52 (FIGURE 4), but is not required for waterless or flexographic printing.

The plate cylinder 32 of printing unit 28 is equipped with a waterless printing plate PW. Waterless printing plates are also referred to as dry planographic printing plates and are disclosed in the following U.S. patents: 3,910,187; Re. 30,670; 4,086,093; and 4,853,313. Suitable waterless printing plates can be obtained from Toray Industries, Inc. of Tokyo, Japan. A dampening system is not used for waterless printing, and waterless (oil-based) printing ink is used. The waterless printing plate PW has image areas and non-image areas which are oleophilic/hydrophilic and oleophobic/hydrophobic, respectively. The waterless printing plate PW is engraved or etched, with the image areas being recessed with respect to the non-image areas. The image area of the waterless printing plate PW is rolled-up with the flexographic or aqueous printing ink which is transferred by the applicator roller 66. Both aqueous and oil-based inks and coatings are repelled from the non-image areas, and are retained in the image areas. The printing ink or coating is then transferred from the image areas to an ink or coating receptive blanket B and is printed or coated onto a substrate S.

For some printing jobs, a flexographic plate PF or a waterless printing plate PW is mounted over a resilient packing such as the blanket B on the blanket cylinder 34, for example as indicated by phantom lines in printing unit 22 of FIGURE 5. An advantage of this alternative embodiment is that the waterless plate PW or the flexographic plate PF are resiliently supported over the blanket cylinder by the underlying blanket B or other resilient packing. The radial deflection and give of the resilient blanket B provides uniform, positive engagement between

the applicator roller 66 and a flexographic plate or waterless plate.

In that arrangement, a plate is not mounted on the plate cylinder 32; instead, a waterless plate PW is mounted on the blanket cylinder, and the inked image on the waterless printing plate is not offset but is instead transferred directly from the waterless printing plate PW to the substrate S. The water component of flexographic ink on the freshly printed sheet is evaporated by high velocity, hot air dryers and high volume heat and moisture extractors so that the freshly printed aqueous or flexographic ink is dried before the substrate is printed on the next printing unit.

Referring now to FIGURE 2, FIGURE 3 and FIGURE 9, the inking/coating apparatus 10 is pivotally mounted on the side frames 14, 15 for rotation about an axis X. The inking/coating apparatus 10 includes a frame 60, a hydraulic motor 62, a lower gear train 64, an upper gear train 65, an applicator roller 66, a sealed doctor blade assembly 68 (FIGURE 6), and a drip pan DP, all mounted on the frame 60. The external peripheral surface of the applicator roller 66 is wetted by contact with liquid coating material or ink contained in a reservoir 70.

The hydraulic motor 62 drives the applicator roller 66 synchronously with the plate cylinder 32 and the blanket cylinder 34 in response to an RPM control signal from the press drive (not illustrated) and a feedback signal developed by a tachometer 72. While a hydraulic drive motor is preferred, other drive means such as an electric drive motor or an equivalent can be used.

When using waterless printing plate systems, the temperature of the waterless printing ink and of the waterless printing plate must be closely controlled for good image reproduction. For example, for waterless offset printing with TORAY waterless printing plates PW, it is absolutely necessary to control the waterless printing plate surface and waterless ink temperature to a very narrow range, for example 24°C (75°F) to 27°C (80°F).

Referring to FIGURE 7, the reservoir 70 is supplied with ink or coating which is temperature controlled by a heat exchanger 71. The temperature controlled ink or coating material is circulated by a positive displacement pump, for example a peristaltic pump, through the reservoir 70 and heat exchanger 71 from a source 73 through a supply conduit 75 and a return conduit 77. The heat exchanger 71 cools or heats the ink or coating material and maintains the ink or coating and the printing plate within the desired narrow temperature range.

According to one aspect of the present invention, aqueous/flexographic ink or coating material is supplied to the applicator roller 66, which transfers the aqueous/flexographic ink or coating material to the printing plate (FIGURE 7), which may be a waterless printing plate or a flexographic printing plate. When the inking/coating apparatus is used for applying aqueous/flexographic ink or coating material to a waterless printing plate PW, the inking roller train 52 is not required, and is retracted away from the printing plate. Because the viscosity of aqueous/flexographic printing ink or coating material varies with temperature, it is necessary to heat or cool the aqueous/flexographic printing ink or coating material to compensate for ambient temperature variations to maintain the ink viscosity in a preferred operating range.

For example, the temperature of the printing press can vary from around 60°F (15°C) in the morning, to around 85°F (29°C) or more in the afternoon. The viscosity of aqueous/flexographic printing ink or coating material can be marginally high when the ambient temperature of the press is near 60°F (15°C), and the viscosity can be marginally low when the ambient temperature of the press exceeds 85°F (29°C). Consequently, it is desirable to control the temperature of the aqueous/flexographic printing ink or coating material so that it will maintain the surface temperature of waterless printing plates within the specified temperature range. Moreover, the ink/coating material temperature should be controlled to maintain the tack of the aqueous/flexographic

printing ink or coating material within a desired range when the ink or coating material is being used in connection with flexographic printing processes.

The applicator roller 66 is preferably an anilox fluid metering roller which transfers measured amounts of printing ink or coating material to a plate or blanket. The surface of an anilox roller is engraved with an array of closely spaced, shallow depressions referred as "cells". Ink or coating from the reservoir 70 flows into the cells as the anilox roller turns through the reservoir. The transfer surface of the anilox roller is "doctored" (wiped or scraped) by dual doctor blades 68A, 68B to remove excess ink or coating material. The ink or coating metered by the anilox roller is that contained within the cells. The dual doctor blades 68A, 68B also seal the supply reservoir 70.

The anilox applicator roller 66 is cylindrical and may be constructed in various diameters and lengths, containing cells of various sizes and shapes. The volumetric capacity of an anilox roller is determined by cell size, shape and number of cells per unit area. Depending upon the intended application, the cell pattern may be fine (many small cells per unit area) or coarse (fewer large cells per unit area).

By supplying the ink or coating material through the inking/coating apparatus 10, more ink or coating material can be applied to the sheet S as compared with the inking roller train of a lithographic printing unit. Moreover, color intensity is stronger and more brilliant because the aqueous or flexographic ink or coating material is applied at a much heavier film thickness or weight than can be applied by the lithographic process, and the aqueous or flexographic colors are not diluted by dampening solution.

Preferably, the sealed doctor blade assembly 68 is constructed as described in U.S. Patent 5,176,077 to Howard W. DeMoore, co-inventor and assignee, which is incorporated herein by reference. An advantage of using a sealed reservoir is that fast drying ink or coating material can be used. Fast drying ink or

coating material can be used in an open fountain 53 (see FIGURE 8); however, open air exposure causes the water and solvents in the fast-drying ink or coating material to evaporate faster, thus causing the ink or coating material to dry prematurely and change viscosity. Moreover, an open fountain emits unwanted odors into the press room. When the sealed doctor blade assembly is utilized, the pump (FIGURE 7) which circulates ink or coating material to the doctor blade head is preferably a peristaltic pump, which does not inject air into the feeder lines which supply the ink or coating reservoir 70 and helps to prevent the formation of air bubbles and foam within the ink or coating material.

An inking/coating apparatus 10 having an alternative applicator roller arrangement is illustrated in FIGURES 10-13. In this arrangement, the engraved metering surface of the anilox applicator rollers 66, 67 are partitioned by smooth seal surfaces 66C which separates a first engraved peripheral surface portion 66A from a second engraved peripheral surface portion 66B. Likewise, smooth seal surfaces 66D, 66E are formed on the opposite end portions of the applicator roller 66 for engaging end seals 134, 136 (FIGURE 12) of the doctor blade reservoir. The upper applicator roller 67 has engraved anilox metering surfaces 67A and 67B which are separated by a smooth seal band 67C.

Referring now to FIGURE 12 and FIGURE 13, the reservoir 70 of the doctor blade head 68 is partitioned by a curved seal element 130 to form two separate chambers 70A, 70B. The seal element 130 is secured to the doctor blade head within an annular groove 132. The seal element 130 is preferably made of polyurethane foam or other durable, resilient foam material. The seal element 130 is engaged by the seal band 66, thus forming a rotary seal which blocks the leakage of ink or coating material from one reservoir chamber into the other reservoir chamber. Moreover, the seal band provides an unprinted or uncoated area which separates the printed or coated areas from each other, which is needed for work and turn printing jobs or other printing jobs which print two or more separate images onto the same substrate.

Another advantage of the split applicator roller embodiment is that it enables two or more flexographic inks or coating materials to be printed simultaneously within the same lithographic printing unit. That is, the reservoir chambers 70A, 70B of the upper doctor blade assembly can be supplied with gold ink and silver ink, for example, while the reservoir chambers 70A, 70B of the lower doctor blade assembly can be supplied with inks of two additional colors, for example opaque white ink and blue ink. This permits the opaque white ink to be overprinted with the gold ink, and the blue ink to be overprinted with the silver ink on the same printing unit on any lithographic press.

Moreover, a catalyst can be used in the upper doctor blade reservoir and a reactive ink or coating material can be used in the lower doctor blade reservoir. This can provide various effects, for example improved chemical resistance and higher gloss levels.

The split applicator roller sections 67A, 67B in the upper cradle position can be used for applying two separate inks or coating materials simultaneously, for example flexographic, aqueous and ultra-violet curable inks or coating materials, to separate surface areas of the plate, while the lower applicator roller sections 66A, 66B can apply an initiator layer and a micro-encapsulated layer simultaneously to separate blanket surface areas. Optionally, the metering surface portions 66A, 66B can be provided with different cell metering capacities for providing different printing effects which are being printed simultaneously. For example, the screen line count on one half-section of an anilox applicator roller is preferably in the range of 200-600 lines per inch (79-236 lines per cm) for half-tone images, and the screen line count of the other half-section is preferably in the range of 100-300 lines per inch (39-118 lines per cm) for overall coverage, high weight applications such as opaque white. This split arrangement in combination with dual applicator rollers is particularly advantageous when used in connection with "work and turn" printing jobs.

Referring again to FIGURE 7, instead of using the sealed doctor blade reservoir assembly 68 as shown in FIGURE 6, an open fountain assembly 69 is provided by the fountain pan 53 which contains a volume of liquid ink Q or coating material. The liquid ink or coating material is transferred to the applicator roller 66 by a pan roller 55 which turns in contact with ink Q or coating material in the fountain pan. If a split applicator roller is used, the pan roller 55 is also split, and the pan is divided into two pan sections 53A, 53B by a separator plate 53P, as shown in FIGURE 16.

In the alternative embodiment of FIGURE 16, the pan roller 55 is divided into two pan roller sections 55A, 55B by a centrally located, annular groove 59. The separator plate 53P is received within and centrally aligned with the groove 59, but does not touch the adjoining roller faces. By this arrangement, two or more inks or coating materials Q1, Q2 are contained within the open pan sections 55A, 55B for transfer by the split pan roller sections 53A, 53B, respectively. This permits two or more flexographic inks or coating materials to be transferred to two separate image areas on the plate or on the blanket of the same printing unit. This arrangement is particularly advantageous for work and turn printing jobs or other printing jobs which print two or more separate images onto the same substrate.

The frame 60 of the inking/coating apparatus 10 includes side support members 74, 76 which support the applicator roller 66, gear train 64, gear train 65, doctor blade assembly 68 and the drive motor 62. The applicator roller 66 is mounted on stub shafts 63A, 63B which are supported at opposite ends on a lower cradle assembly 100 formed by a pair of side support members 78, 80 which have sockets 79, 81 and retainer caps 101, 103. The stub shafts are received in roller bearings 105, 107 which permit free rotation of the applicator roller 66 about its longitudinal axis A1 (axis A2 in the upper cradle). The retainer caps 101, 103 hold the stub shafts 63A, 63B and bearings 105, 107 in the sockets 79,

81 to hold the applicator roller in parallel alignment with the pivot axis X.

The side support members 74, 76 also have an upper cradle assembly 102 formed by a pair of side support members 82, 84 which are vertically spaced with respect to the lower side plates 78, 80. Each cradle 100, 102 has a pair of sockets 79, 81 and 83, 85, respectively, for holding an applicator roller 66, 67 for spot coating or inking engagement with the printing plate P on the plate cylinder 32 (FIGURE 4) or with a printing plate P or a blanket B on the blanket cylinder 34.

Preferably, the applicator roller 67 (FIGURE 8, FIGURE 9) the upper cradle (plate) position is an anilox roller having a resilient transfer surface. In the dual cradle arrangement as shown in FIGURE 2, the press operator can quickly change from blanket inking/coating to plate inking/coating within minutes, since it is only necessary to release, remove and reposition or replace the applicator roller 66.

The capability to simultaneously print in the flexographic mode, the aqueous mode, the waterless mode, or the lithographic mode on different printing units of the same lithographic press and to print or coat from either the plate position or the blanket position on any one of the printing units is referred to herein as the LITHOFLEX™ printing process or system. LITHOFLEX™ is a trademark of Printing Research, Inc. of Dallas, Texas, U.S.A., exclusive licensee of the present invention.

Referring now to FIGURE 14, an inking/coating apparatus 10 having an inking/coating assembly 109 of an alternative design is installed in the upper cradle position for applying ink and/or coating material to a plate P on the plate cylinder 32. According to this alternative embodiment, an applicator roller 67R having a resilient transfer surface is coupled to an anilox fluid metering roller which transfers measured amounts of printing ink or coating material to the plate P. The anilox roller 111 has a transfer surface constructed of metal, ceramic or composite material which is engraved with cells. The resilient applicator roller 67R is

interposed in transfer engagement with the plate P and the metering surface of the anilox roller 111. The resilient transfer surface of the applicator roller 67R provides uniform, positive engagement with the plate.

Referring now to FIGURE 17, an inking/coating apparatus 10 having an alternative inking/coating assembly 113 is installed in the lower cradle assembly 100 for applying flexographic or aqueous ink and/or coating material Q to a plate or blanket mounted on the blanket cylinder 34. Instead of using the sealed, dual doctor blade reservoir assembly 68 as shown in FIGURE 6, an open, single doctor blade anilox roller assembly 113 is supplied with liquid ink Q or coating material contained in an open fountain pan 117. The liquid ink or coating material Q is transferred to the engraved transfer surface of the anilox roller 66 as it turns in the fountain pan 117. Excess ink or coating material Q is removed from the engraved transfer surface by a single doctor blade 68B. The liquid ink or coating material Q is pumped from an off-press source, for example the drum 73 shown in FIGURE 17, through a supply conduit 119 into the fountain pan 117 by a pump 120.

For overall inking or coating jobs, the metering transfer surface of the anilox roller 66 extends over its entire peripheral surface. However, for certain printing jobs which print two or more separate images onto the same substrate, for example work and turn printing jobs, the metering transfer surface of the anilox applicator roller 66 is partitioned by a centrally located, annular undercut groove 66C which separates first and second metering transfer surfaces 66A, 66B as shown in FIGURE 11 and FIGURE 18.

The single doctor blade 68B has an edge 68E which wipes simultaneously against the split metering transfer surfaces 66A, 66B. In this single blade, split anilox roller embodiment 113, it is necessary to provide dual supply sources, for example drums 73A, 73B, dual supply lines 119A, 119B, and dual pumps 120A, 120B. Moreover, the fountain pan 117 is also split, and the pan 117 is

divided into two pan sections 117A, 117B by a separator plate 121, as shown in FIGURE 18. The separator plate 121 is centrally aligned with the undercut groove 66C, but does not touch the adjoining roller faces.

Although the single blade, split anilox applicator roller assembly 113 is shown mounted in the lower cradle position (FIGURE 17), it should be understood that the single blade, split anilox applicator roller assembly 113 can be mounted and used in the upper cradle position, as well.

According to another aspect of the present invention, the inking/coating apparatus 10 is pivotally coupled on horizontal pivot pins 88P, 90P which allows the single head, dual cradle inking/coating apparatus 10 to be mounted on any lithographic printing unit. Referring to FIGURE 9, the horizontal pivot pins 88P, 90P are mounted within the traditional dampener space 29 of the printing unit and are secured to the press side frames 14, 15, respectively. Preferably, the pivot support pins 88P, 90P are secured to the press side frames by a threaded fastener. The pivot support pins are received within circular openings 88, 90 which intersect the side support members 74, 76 of the inking/coating apparatus 10. The horizontal support pins 88P, 90P are disposed in parallel alignment with rotational axis X and with the plate cylinder and blanket cylinder, and are in longitudinal alignment with each other.

Preferably, the pivot pins 88P, 90P are located in the dampener space 29 so that the rotational axes A1, A2 of the applicator rollers 66, 67 are elevated with respect to the nip contact points N1, N2. By that arrangement, the transfer point between the applicator roller 66 and a blanket on the blanket cylinder 34 (as shown in FIGURE 8) and the transfer point between the applicator roller 66 and a plate on the plate cylinder 32 (as shown in FIGURE 5) are above the radius lines R1, R2 of the plate cylinder and the blanket cylinder, respectively. This permits the inking/coating apparatus 10 to move clockwise to retract the applicator roller 66 to an off-impression position relative to the

blan[illegible] cylinder in response to a [illegible]gle extension stroke of the power actuator arms 104A, 106A. Similarly, the applicator roller 66 is moved counterclockwise to the on-impression operative position as shown in FIGURES 4, 5, 6 and 8 by a single retraction stroke of the actuator arms 104A, 106A, respectively.

Preferably, the pivot pins are made of steel and the side support members are made of aluminum, with the steel pivot pins and the aluminum collar portion bordering the circular openings 88, 90 forming a low friction journal. By this arrangement, the inking/coating apparatus 10 is freely rotatable clockwise and counterclockwise with respect to the pivot pins 88P, 90P. Typically, the arc length of rotation is approximately 60 mils (about 1.5 mm). Consequently, the inking/coating apparatus 10 is almost totally enclosed within the dampener space 29 of the printing unit in the on-impression position and in the off-impression position.

The cradle assemblies 100 and 102 position the applicator roller 66 in inking/coating alignment with the plate cylinder or blanket cylinder, respectively, when the inking/coating apparatus 10 is extended to the operative (on-impression) position. Moreover, because the inking/coating apparatus 10 is installed within the dampener space 29, it is capable of freely rotating through a small arc while extending and retracting without being obstructed by the press side frames or other parts of the printing press. This makes it possible to install the inking/coating apparatus 10 on any lithographic printing unit. Moreover, because of its internal mounting position within the dampener space 29, the projection of the inking/coating apparatus 10 into the space between printing units is minimal. This assures unrestricted operator access to the printing unit when the applicator head is in the operative (on-impression) and retracted (off-impression) positions.

As shown in FIGURE 4 and FIGURE 5, movement of the inking/coating apparatus 10 is counterclockwise from the retracted

(off-impression) position to the operative (on-impression) position.

Although the dampener side installation is preferred, the inking/coating apparatus 10 can be adapted for operation on the delivery side of the printing unit, with the inking/coating apparatus being movable from a retracted (off-impression) position to an on-impression position for engagement of the applicator roller with either a plate on the plate cylinder or a blanket on the blanket cylinder on the delivery side 25 of the printing unit.

Movement of the inking/coating apparatus 10 to the operative (on-impression) position is produced by power actuators, preferably double acting pneumatic cylinders 104, 106 which have extendable/retractable power transfer arms 104A, 106A, respectively. The first pneumatic cylinder 104 is pivotally coupled to the press frame 14 by a pivot pin 108, and the second pneumatic cylinder 106 is pivotally coupled to the press frame 15 by a pivot pin 110. In response to selective actuation of the pneumatic cylinders 104, 106, the power transfer arms 104A, 106A are extended or retracted. The power transfer arm 104A is pivotally coupled to the side support member 74 by a pivot pin 112. Likewise, the power transfer arm 106A is pivotally coupled to the side support member 76 by a pivot pin 114.

As the power arms extend, the inking/coating apparatus 10 is rotated clockwise on the pivot pins 88P, 90P, thus moving the applicator roller 66 to the off-impression position. As the power arms retract, the inking/coater apparatus 60 is rotated counterclockwise on the pivot pins 88P, 90P, thus moving the applicator roller 66 to the on-impression position. The torque applied by the pneumatic actuators is transmitted to the inking/coating apparatus 10 through the pivot pin 112 and pivot pin 114.

Fine adjustment of the on-impression position of the applicator roller relative to the plate cylinder or the blanket cylinder, and of the pressure of roller engagement, is provided by an adjustable stop assembly 115. The adjustable stop assembly 115

has a threaded bolt 116 which is engagable with a bell crank 118. The bell crank 118 is pivotally coupled to the side support member 74 on a pin 120. One end of the bell crank 118 is engagable by the threaded bolt 116, and a cam roller 122 is mounted for rotation on its opposite end. The striking point of engagement is adjusted by rotation of the bolt 116 so that the applicator roller 66 is properly positioned for inking/coating engagement with the plate P or blanket B and provides the desired amount of inking/coating pressure when the inking/coating assembly 60 is moved to the operative position.

This arrangement permits the in-line inking/coating apparatus to operate effectively without encroaching in the interunit space between any adjacent printing units, and without blocking or obstructing access to the cylinders of the printing units when the inking/coating apparatus is in the extended (off-impression) position or retracted (on-impression) position. Moreover, when the in-line inking/coating apparatus is in the retracted position, the doctor blade reservoir and coating circulation lines can be drained and flushed automatically while the printing press is running as well as when the press has been stopped for change-over from one job to another or from one type of ink or coating to another.

Substrates which are printed or coated with aqueous flexographic printing inks require high velocity hot air for drying. When printing a flexographic ink such as opaque white or metallic gold, it is always necessary to dry the printed substrates between printing units before overprinting them. According to the present invention, the water component on the surface of the freshly printed or coated substrate S is evaporated and dried by high velocity, hot air interunit dryer and high volume heat and moisture extractor units 124, 126 and 128, as shown in FIGURE 2, FIGURE 4 and FIGURE 5. The dryer/extractor units 124, 126 and 128 are oriented to direct high velocity heated air onto the freshly printed/coated substrates as they are transferred by the impression cylinder 36 and the intermediate

transfer drum 40 of one printing unit and to another transfer cylinder 30 and to the impression cylinder 36 of the next printing unit. By that arrangement, the freshly printed flexographic ink or coating material is dried before the substrate S is overprinted by the next printing unit.

The high velocity, hot air dryer and high performance heat and moisture extractor units 124, 126 and 128 utilize high velocity air jets which scrub and break-up the moist air layer which clings to the surface of each freshly printed or coated sheet or web. Within each dryer, high velocity air is heated as it flows across a resistance heating element within an air delivery baffle tube. High velocity jets of hot air are discharged through multiple airflow apertures into an exposure zone Z (FIGURE 4 and FIGURE 5) and onto the freshly printed/coated sheet S as it is transferred by the impression cylinder 36 and transfer drum 40, respectively.

Each dryer assembly includes a pair of air delivery dryer heads 124D, 126D and 128D which are arranged in spaced, side-by-side relationship. The high velocity, hot air dryer and high performance heat and moisture extractor units 124, 126 and 128 are preferably constructed as disclosed in co-pending U.S. Patent Application Serial No. 08/132,584, filed October 6, 1993, entitled "High Velocity Hot Air Dryer", to Howard W. DeMoore, co-inventor and assignee of the present invention, and which is incorporated herein by reference, and which is marketed by Printing Research, Inc. of Dallas, Texas, U.S.A., under its trademark SUPER BLUE HV™.

The hot moisture-laden air displaced from the surface of each printed or coated sheet is extracted from the dryer exposure zone Z and exhausted from the printing unit by the high volume extractors 124, 126 and 128. Each extractor head includes an extractor manifold 124E, 126E and 128E coupled to the dryer heads 124D, 126D and 128D and draws the moisture, volatiles, odors and hot air through a longitudinal air gap G between the dryer heads. Best results are obtained when extraction is performed simulta-

neou[illegible] with drying. Preferably, a [illegible]xtractor is closely coupled to the exposure zone Z at each dryer location as shown in FIGURE 4. Extractor heads 124E, 126E and 128E are mounted on the dryer heads 124D, 126D and 128D, respectively, with the longitudinal extractor air gap G facing directly into the exposure zone Z. According to this arrangement, each printed or coated sheet is dried before it is printed on the next printing unit.

The aqueous water-based inks used in flexographic printing evaporate at a relatively moderate temperature provided by the interunit high velocity hot air dryers/extractors 124, 126 and 128. Sharpness and print quality are substantially improved since the flexographic ink or coating material is dried before it is overprinted on the next printing unit. Since the freshly printed flexographic ink is dry, dot gain is substantially reduced and back-trapping on the blanket of the next printing unit is virtually eliminated. This interunit drying/extracting arrangement makes it possible to print flexographic inks such as metallic ink and opaque white ink on the first printing unit, and then dry-trap and overprint on the second and subsequent printing units.

Moreover, this arrangement permits the first printing unit 22 to be used as a coater in which a flexographic, aqueous or UV-curable coating material is applied to the lowest grade substrate such as recycled paper, cardboard, plastic and the like, to trap and seal-in lint, dust, spray powder and other debris and provide a smoother, more durable printing surface which can be overprinted on the next printing unit.

A first down (primer) aqueous coating layer seals-in the surface of a low grade, rough substrate, for example, re-cycled paper or plastic, and improves overprinted dot definition and provides better ink lay-down while preventing strike-through and show-through. A flexographic UV-curable coating material can then be applied downstream over the primer coating, thus producing higher coating gloss.

Preferably, the applicator roller 66 is constructed of composite carbon fiber material, metal or ceramic coated metal

when is used for applying ink or coating material to the blanket B or other resilient material on the blanket cylinder 34. When the applicator roller 66 is applied to the plate, it is preferably constructed as an anilox roller having a resilient, compressible transfer surface. Suitable resilient roller surface materials include Buna N synthetic rubber and EPDM (terpolymer elastomer).

It has been demonstrated in prototype testing that the inking/coating apparatus 10 can apply a wide range of ink and coating types, including fluorescent (Day Glo), pearlescent, metallics (gold, silver and other metals), glitter, scratch and sniff (micro-encapsulated fragrance), scratch and reveal, luminous, pressure-sensitive adhesives and the like, as well as UV-curable and aqueous coatings.

With the dampener assembly removed from the printing unit, the inking/coating apparatus 10 can easily be installed in the dampener space for selectively applying flexographic inks and/or coatings to a flexographic or waterless printing plate or to the blanket. Moreover, overprinting of the flexographic inks and coatings can be performed on the next printing unit since the flexographic inks and/or coatings are dried by the high velocity, hot air interunit dryer and high volume heat and moisture extractor assembly of the present invention.

The flexographic inks and coatings as used in the present invention contain colored pigments and/or soluble dyes, binders which fix the pigments onto the surface of the substrate, waxes, defoamers, thickeners and solvents. Aqueous printing inks predominantly contain water as a diluent and/or vehicle. The thickeners which are preferred include algonates, starch, cellulose and its derivatives, for example cellulose esters or cellulose ethers and the like. Coloring agents including organic as well as inorganic pigments may be derived from dyes which are insoluble in water and solvents. Suitable binders include acrylates and/or polyvinylchloride.

When metallic inks are printed, the cells of the anilox roller must be appropriately sized to prevent the metal particles from getting stuck within the cells. For example, for metallic gold ink, the anilox roller should have a screen line count in the range of 175-300 lines per inch (68-118 lines per cm). Preferably, in order to keep the anilox roller cells clear, the doctor blade assembly 68 is equipped with a bristle brush BR (FIGURE 14) as set forth in U.S. Patent 5,425,809 to Steven M. Person, assigned to Howard W. DeMoore, and licensed to Printing Research, Inc. of Dallas, Texas, U.S.A., which is incorporated herein by reference.

The inking/coating apparatus 10 can also apply UV-curable inks and coatings. If UV-curable inks and coatings are utilized, ultra-violet dryers/extractors are installed adjacent to the high velocity hot air dryer/extractor units 124, 126 and 128, respectively.

It will be appreciated that the LITHOFLEX™ printing process described herein makes it possible to selectively operate a printing unit of a press in the lithographic printing mode while simultaneously operating another printing unit of the same press in either the flexographic printing mode or in the waterless printing mode, while also providing the capability to print or coat, separately or simultaneously, from either the plate position or the blanket position. The dual cradle support arrangement of the present invention makes it possible to quickly change over from inking/coating on the blanket cylinder position to inking/coating on the plate cylinder position with minimum press down-time, since it is only necessary to remove and reposition or replace the applicator roller 66 while the inking/coating apparatus 10 is in the retracted position. It is only necessary to remove four cap screws, lift the applicator roller 66 from the cradle, and reposition it in the other cradle. All of this can be accomplished in a few minutes, without removing the inking/coating apparatus 10 from the press.

It is possible to spot coat or overall coat from the plate position or from the blanket position with flexographic inks or coatings on one printing unit and then spot coat or overall coat with UV-curable inks or coatings from the plate position or from the blanket position on another printing unit during the same press run. Moreover, the press operator can spot or overall coat from the plate for one job, and then spot and/or overall coat from the blanket on the next job.

The positioning of the applicator roller relative to the plate or blanket is repeatable to a predetermined preset operative position. Consequently, only minor printing unit modifications or alterations may be required for the LITHOFLEX™ process. Although automatic extension and retraction have been described in connection with the exemplary embodiment, extension to the operative (on-impression) position and retraction to a non-operative (off-impression) position can be carried out manually, if desired. In the manual embodiment, it is necessary to latch the inking/coating apparatus 10 to the press side frames 14, 15 in the operative (on-impression) position, and to mechanically prop the inking/coating apparatus in the off-impression (retracted) position.

Referring again to FIGURE 8, an applicator roller 66 is mounted on the lower cradle assembly 100 by side support members 78, 80, and a second applicator roller 66 is mounted on the upper cradle assembly 102 by side support members 82, 84. According to this arrangement, the inking/coating apparatus 10 can apply printing ink and/or coating material to a plate on the plate cylinder, while simultaneously applying printing ink and/or coating material to a plate or a blanket on the blanket cylinder of the same printing unit. When the same color ink is used by the upper and lower applicator rollers from the plate position and from the blanket position simultaneously on the same printing unit, a "double bump" or double inking films or coating layers are applied to the substrate S during a single pass of the substrate through the printing unit. The tack of the two inks or coating

materials must be compatible for good transfer during the double bump. Moreover, the inking/coating apparatus 10 can be used for supplying ink or coating material to the blanket cylinder of a rotary offset web press, or to the blanket of a dedicated coating unit.

According to conventional bronzing techniques, a metallic (bronze) powder is applied off-line to previously printed substrate which produces a grainy, textured finish or appearance. The on-line application of bronze material by conventional flexographic or lithographic printing will only produce a smooth, continuous appearance. However, a grainy, textured finish is preferred for highest quality printing which, prior to the present invention, could only be produced by off-line methods.

Referring now to FIGURE 14 and FIGURE 15, metallic ink or coating material is applied on-line to the substrate S by simultaneous operation of the upper and lower applicator rollers 67R, 66 to produce an uneven surface finish having a bronze-like textured or grainy appearance. According to the simulated bronzing method of the present invention, the flexographic bronze ink is applied simultaneously to the plate and to the blanket by the dual cradle inking/coating apparatus 10 as shown in FIGURE 14. A resilient applicator roller 67R is mounted in the upper cradle 102, and an anilox applicator roller 66 is mounted on the lower cradle 100. The rollers are supplied from separate doctor blade reservoirs 70. The doctor blade reservoir 70 in the upper cradle position supplies bronze ink or coating material having relatively coarse, metallic particles 140 dispersed in aqueous or flexographic ink. The coarse particle ink or coating material is applied to the plate P by the resilient applicator roller 67R in the upper cradle position 102. At the same time, flexographic and/or bronze ink or coating material having relatively fine, metallic particles 142 is transferred to the blanket B by the anilox roller 66 which is mounted on the lower cradle 100.

The metering surfaces of the upper and lower applicator rollers have different cell sizes and volumetric capacities which

accommodate the coarse and fine metallic particles. For example, the anilox roller 111 mounted in the upper cradle position 102 which transfers the coarse metallic particles 140 preferably has a screen line count in the range of 100-300 lines per inch (39-118 lines per cm), and the metering surface of the anilox roller 66 mounted on the lower cradle 100 which transfers the relatively fine metallic particles 142 preferably has a screen line count in the range of 200-600 lines per inch (79-236 lines per cm).

After transfer from the plate to the blanket, the fine metallic particles 142 form a layer over the coarse metallic particles 140. As both bronze layers are offset onto the substrate S, the layer of fine metallic particles 142 is printed onto the substrate S with the top layer of coarse metallic particles 140 providing a textured, grainy appearance. The fine metallic particles 142 cover the substrate which would otherwise be visible in the gaps between the coarse metallic particles 140. The combination of the coarse particle layer over the fine particle layer thus provides a textured, bronzed-like finish and appearance.

Particulate materials other than metal can be used for producing a textured finish. For example, coarse and fine particles of metallized plastic (glitter), mica particles (pearlescent) and the like, can be substituted for the metallic particles for producing unlimited surface variations, appearances and effects. All of the particulate material, including the metallic particles, are preferably in solid, flat platelet form, and have a size dimension suitable for application by an anilox applicator roller. Other particulate or granular material, for example stone grit having irregular form and size, can be used to good advantage.

Solid metal particles in platelet form, which are good reflectors of light, are preferred for producing the bronzed-like appearance and effect. However, various textured finishes, which could have light-reflective properties, can be produced by using granular materials such as stone grit. Most commonly used metals

including copper, zinc and aluminum. Other ductile metals can be used, if desired. Moreover, the coarse and fine particles need not be made of the same particulate material. Various effects and textured appearances can be produced by utilizing diverse particulate materials for the coarse particles and the fine particles, respectively. Further, either fine or coarse particle ink or coating material can be printed from the upper cradle position, and either fine or coarse particle ink or coating material can be printed from the lower cradle position, depending on the special or surface finish that is desired.

It will be appreciated that the last printing unit 28 can be configured for additional inking/coating capabilities which include lithographic, waterless, aqueous and flexographic processes. Various substrate surface effects (for example double bump or triple bump inking/coating or bronzing) can be performed on the last printing unit. For triple bump inking/coating, the last printing unit 28 is equipped with an auxiliary in-line inking or coating apparatus 97 as shown in FIGURE 3 and FIGURE 4. The in-line inking or coating apparatus 97 allows the application of yet another film of ink or a protective or decorative layer of coating material over any freshly printed or coated surface effects or special treatments, thereby producing a triple bump. The triple bump is achieved by applying a third film of ink or layer of coating material over the freshly printed or coated double bump simultaneously while the substrate is on the impression cylinder of the last printing unit.

When the in-line inking/coating apparatus 97 is installed, it is necessary to remove the SUPER BLUE® flexible covering from the delivery cylinder 42, and it is also necessary to modify or convert the delivery cylinder 42 for inking/coating service by mounting a plate or blanket B on the delivery cylinder 42, as shown in FIGURE 3 and FIGURE 4. Packing material is placed under the plate or blanket B, thereby packing the plate or blanket B at the correct packed-to-print radial clearance so that ink or coating material will be printed or coated onto the freshly

printed substrate S as it transfers through the nip between the plate or blanket B on the converted delivery cylinder 42 and the last impression cylinder 36. According to this arrangement, a freshly printed or coated substrate is overprinted or overcoated with a third film or layer of ink or coating material simultaneously while a second film or layer of ink or coating material is being over-printed or over-coated on the last impression cylinder 36.

The auxiliary inking/coating apparatus 97 and the converted or modified delivery cylinder 42 are mounted on the delivery drive shaft 43. The inking/coating apparatus 97 includes an applicator roller, preferably an anilox applicator roller 97A, for supplying ink or coating material to a plate or blanket B on the modified or converted delivery cylinder 42. The in-line inking/coating apparatus 97 and the modified or converted delivery cylinder 42 are preferably constructed as described in U.S. Patent 5,176,077 to Howard W. DeMoore (co-inventor and assignee), which is hereby incorporated by reference. The in-line inking/coating apparatus 97 is manufactured and sold by Printing Research, Inc. of Dallas, Texas, U.S.A., under its trademark SUPER BLUE EZ COATER™.

After the delivery cylinder 42 has been modified or converted for inking/coating service, and because of the reduced nip clearance imposed by the plate or blanket B, the modified delivery cylinder 42 can no longer perform its original function of guiding and transferring the freshly printed or coated substrate. Instead, the modified or converted delivery cylinder 42 functions as a part of the inking/coating apparatus 97 by printing or coating a third down film of ink or layer of coating material onto the freshly printed or coated substrate as it is simultaneously printed or coated on the last impression cylinder 36. Moreover, the mutual tack between the second down ink film or coating layer and the third down ink film or coating layer causes the overprinted or overcoated substrate to cling to the plate or

blanket, thus opposing or resisting separation of the substrate from the plate or blanket.

To remedy this problem, a vacuum-assisted transfer apparatus 99 is mounted adjacent the modified or converted delivery cylinder 42 as shown in FIGURE 3 and FIGURE 4. Another purpose of the vacuum-assisted transfer apparatus 99 is to separate the freshly overprinted or overcoated triple bump substrate from the plate or blanket B as the substrate transfers through the nip. The vacuum-assisted transfer apparatus 99 produces a pressure differential across the freshly overprinted or overcoated substrate as it transfers through the nip, thus producing a separation force onto the substrate and providing a clean separation from the plate or blanket B.

The vacuum-assisted transfer apparatus 99 is preferably constructed as described in U.S. Patent Nos. 5,113,255; 5,127,329; 5,205,217; 5,228,391; 5,243,909; and 5,419,254, all to Howard W. DeMoore, co-inventor, which are incorporated herein by reference. The vacuum-assisted transfer apparatus 99 is manufactured and sold by Printing Research, Inc. of Dallas, Texas, U.S.A. under its trademark BACVAC™.

Although the present invention and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the present invention as defined by the appended claims.

What is claimed is:

1. A rotary offset printing press of the type including first and second printing units, the first printing unit comprising:

a plate cylinder having a flexographic printing plate mounted thereon;

a blanket cylinder having a blanket disposed in ink or coating transfer engagement with the flexographic printing plate for receiving aqueous or flexographic printing ink or coating material from the flexographic printing plate;

an impression cylinder disposed adjacent the blanket cylinder thereby forming a nip between the blanket and the impression cylinder whereby the aqueous or flexographic printing ink or coating material can be transferred from the blanket to a substrate as the substrate is transferred through the nip;

inking/coating apparatus movably coupled to the printing unit for movement to an on-impression operative position and to an off-impression retracted position;

the inking/coating apparatus including container means for containing a volume of aqueous or flexographic ink or coating material, and at least one applicator roller coupled to the container means for applying aqueous or flexographic ink or coating material to the flexographic printing plate or to the blanket when the inking/coating apparatus is in the on-impression operative position;

the container means having a partition dam dividing the container means thereby defining a first container region and a second container region;

the at least one applicator roller having first and second transfer surfaces and means separating the first and second transfer surfaces; and,

the first and second transfer surfaces of the at least one applicator roller being disposed within the first and second container regions for rolling contact with aqueous or

flexographic printing ink or coating material contained within the first and second container regions, respectively.

2. A rotary offset printing press as defined in claim 1, wherein:

said separating means is an annular seal element disposed on the applicator roller; and,

the partition element is disposed in sealing engagement against the annular seal element of the applicator roller.

3. A rotary offset printing press as defined in claim 1, wherein:

said container means is an open fountain pan;

said separating means is an annular groove intersecting the applicator roller thereby separating the first and second transfer surfaces; and,

the partition element is a separator plate mounted on the fountain pan between the first and second reservoir regions and disposed in the annular groove.

4. A rotary offset printing press as defined in claim 1, including sheet feeding means coupled to the first printing unit for consecutively feeding substrates in sheet form into the first printing unit.

5. A rotary offset printing press as defined in claim 1, including web feeding means coupled to the first printing unit for continuously feeding a substrate in continuous web form into the first printing unit.

6. A rotary offset printing press as defined in claim 1, wherein:

said container means is a fountain pan having first and second pan sections for containing first and second aqueous or flexographic inks or coating materials, respectively;

said applicator roller having first and second transfer surfaces and an annular groove separating said first and second transfer surfaces; and,

a pan roller having first and second transfer surfaces mounted for rotation in the first and second pan sections, respectively, for separately transferring aqueous or flexographic ink or coating material from the first and second pan sections to the first and second transfer surfaces of the applicator roller.

7. A rotary offset printing press as set forth in claim 1, wherein:

said container means is a sealed doctor blade head having first and second reservoir chambers, said partition dam being mounted on the doctor blade head and separating the first and second reservoir chambers;

the at least one applicator roller comprising an anilox transfer roller having first and second fluid metering transfer surfaces disposed for rolling contact with the aqueous or flexographic ink or coating material in the first and second reservoir chambers, respectively;

the separating means being a seal band formed on the applicator roller between the first and second transfer surfaces; and,

the partition dam being disposed in sealing engagement with the seal band in the coupled position.

8. A rotary offset printing press as defined in claim 1, wherein the inking/coating apparatus comprises:

first cradle means for supporting a first applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

second cradle means for supporting a second applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

a first applicator roller mounted for rotation on the first cradle means, the first applicator roller having first and second transfer surfaces and a seal band separating the first and second transfer surfaces;

a second applicator roller mounted for rotation on the second cradle means, the second applicator roller having first and second transfer surfaces and means separating the first and second transfer surfaces;

first reservoir means for containing a volume of ink or coating material, the first reservoir means having first and second reservoir chambers and a partition element separating the first and second reservoir chambers of th4e first reservior means;

second reservoir means for containing a volume of ink or coating material, the second reservoir means having first and second reservoir chambers and a partition element separating the first and second reservoir chambers of the second reservoir means;

the first and second reservoir means being coupled to the first and second applicator rollers, respectively, the first and second transfer surfaces of the first applicator roller being disposed for rolling contact with ink or coating material in the first and second reservoir chambers, respectively, of the first reservoir means and the first partition seal element being disposed in sealing engagement against the separating means of the first applicator roller in the coupled position; and,

the first and second transfer surfaces of the second applicator roller being disposed for rolling contact with ink or coating material in the first and second reservoir chambers, respectively, of the second reservoir means and the partition element of the second reservoir means being disposed in

sealing engagement with the separating means of the second applicator roller in the coupled position.

9. A rotary offset printing press as defined in claim 1, wherein:

the at least one applicator roller is an anilox roller having first and second fluid metering transfer surfaces; and,

the volumetric capacity of the first transfer surface being different from the volumetric capacity of the second transfer surface.

10. A rotary offset printing press as defined in claim 1, wherein the inking/coating apparatus comprises:

cradle means;

the at least one applicator roller being mounted for rotation on the cradle means, the applicator roller having first and second transfer surfaces and means separating the first and second metering transfer surfaces;

reservoir means for containing a volume of ink or coating material, the reservoir means having first and second reservoir chambers and a partition element separating the first and second reservoir chambers;

the at least one applicator roller being coupled to the reservoir means with the first and second fluid metering transfer surfaces being disposed for rolling contact with the ink or coating material in the first and second reservoir chambers, respectively, and the partition element being disposed in sealing engagement with separating means of the applicator roller in the coupled position; and,

the volumetric capacity of the first transfer surface being different from the volumetric capacity of the second transfer surface.

11. A rotary offset printing press as set forth in claim 1, wherein the inking/coating apparatus comprises:

a fountain pan for containing a volume of liquid ink or coating material;

an applicator roller having a metering surface; and,

a pan roller mounted for rotation in the fountain pan and coupled to the applicator roller for transferring ink or coating material from the fountain pan to the applicator roller.

12. A rotary offset printing press as defined in claim 1, further including:

a transfer drum coupled in substrate transfer relation with the impression cylinder of the first printing unit and in substrate transfer relation with the second printing unit;

a first dryer mounted adjacent the impression cylinder of the first printing unit for discharging heated air onto a freshly printed or coated substrate while the substrate is in contact with the impression cylinder of the first printing unit;

a second dryer mounted adjacent the transfer drum for discharging heated air onto a freshly printed or coated substrate after it has been transferred from the impression cylinder of the first printing unit and while it is in contact with the transfer cylinder; and,

a third dryer disposed adjacent the second printing unit for discharging heated air onto a freshly printed or coated substrate after it has been transferred from the transfer drum and before it is printed or otherwise processed on the second printing unit.

13. A rotary offset printing press as defined in claim 1, wherein the means for applying ink or coating material comprises:

first cradle means;

a first reservoir or fountain means mounted on the first cradle means for containing ink or coating material;

a first applicator roller mounted for rotation on the first cradle means and disposed for rolling contact with ink or coating material in the first reservoir or fountain means, the first applicator roller being engagable with a printing plate on the plate cylinder;

second cradle means;

a second reservoir or fountain means mounted on the second cradle means for receiving ink or coating material; and,

a second applicator roller mounted for rotation on the second cradle means and disposed for rolling contact with ink or coating material in the second reservoir or fountain means, the second applicator roller being engagable with a plate or blanket mounted on the blanket cylinder in the operative position.

14. A rotary offset printing press as defined in claim 1, wherein the inking/coating apparatus is pivotally mounted on the printing unit in a position in which the nip contact point between said at least one applicator roller and a blanket or plate is offset with respect to a radius line projecting through the center of the plate cylinder or blanket cylinder to the axis of rotation of the printing/coating unit.

15. A rotary offset printing press as defined in claim 1, wherein:

said at least one applicator roller having first and second transfer surfaces and a seal band surface disposed between and separating the first and second transfer surfaces;

the reservoir means having a chamber and a partition member disposed within the chamber, the partition member dividing the chamber thereby defining a first reservoir chamber region and a second reservoir chamber region; and,

the partition member surface being disposed in sealing engagement against the seal band of the applicator roller.

16. A rotary offset printing press as defined in claim 1, wherein the inking/coating apparatus comprises:

first cradle means for supporting a first applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

second cradle means for supporting a second applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

a first applicator roller mounted for rotation on the first cradle means, the first applicator roller having first and second fluid metering transfer surfaces and a separation band separating the first and second fluid metering transfer surfaces;

a second applicator roller mounted for rotation on the second cradle means, the second applicator roller having first and second fluid metering transfer surfaces and a separation band separating the first and second metering transfer surfaces;

first reservoir means for containing a volume of ink or coating material, the first reservoir means having first and second reservoir chambers and a first partition element separating the first and second reservoir chambers;

second reservoir means for containing a volume of ink or coating material, the second reservoir means having first and second reservoir chambers and a second partition seal element separating the first and second reservoir chambers of the second reservoir means;

the first and second fluid metering transfer surfaces of the first applicator roller being disposed for rolling contact with ink or coating material in the first and second reservoir chambers, respectively, of the first reservoir means and the first partition element being disposed in sealing engagement against the separation band of the first applicator roller in the coupled position; and,

the first and second fluid metering transfer surfaces of the second applicator roller being disposed for rolling contact with ink or coating material in the first and

second reservoir chambers, respectively, of the second reservoir means and the second partition element of the second reservoir means being disposed in sealing engagement with the separation band of the second applicator roller in the coupled position.

17. A printing press as defined in claim 1, wherein the inking/coating apparatus comprises:

first cradle means for supporting a first applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

second cradle means for supporting a second applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

first reservoir means mounted on the first cradle means, said first reservoir means having a reservoir chamber for containing a volume of ink or coating material;

second reservoir means mounted on the second cradle means, said second reservoir means having a reservoir chamber for containing a volume of ink or coating material;

a first applicator roller mounted for rotation on the first cradle means, the first applicator roller having a fluid metering transfer surface;

a second applicator roller mounted for rotation on the second cradle means, the second applicator roller having a fluid metering transfer surface;

the first and second applicator rollers being coupled to the first and second reservoir means, respectively, the fluid metering transfer surfaces of the first and second applicator rollers being disposed for rolling contact with ink or coating material in the reservoir chambers of the first and second reservoir means, respectively; and,

the volumetric capacity of the fluid metering surface of the first applicator roller being different from the volumetric capacity of the fluid metering surface of the second applicator roller.

18. A printing press as defined in claim 1, wherein the means for applying ink or coating material comprises:

cradle means;

an applicator roller mounted for rotation on the cradle means, the applicator roller having first and second surfaces and a seal band separating the first and second transfer surfaces;

reservoir means for containing a volume of ink or coating material, the reservoir means having first and second reservoir chambers and a partition element separating the first and second reservoir chambers;

the applicator roller being coupled to the reservoir means with the first and second transfer surfaces being disposed for rolling contact with the ink or coating material in the first and second reservoir chambers, respectively, and the partition element being disposed in sealing engagement against the seal band of the applicator roller in the coupled position; and,

the volumetric capacity of the first fluid metering transfer surface being different from the volumetric capacity of the second fluid metering transfer surface.

19. A rotary offset printing press as defined in claim 1, further including:

a supply container for containing a volume of liquid ink or coating material;

circulation means coupled between the supply reservoir and the inking/coating apparatus for inducing the flow of liquid ink or coating material from said supply container to the inking/coating apparatus and for returning liquid ink or coating material from the inking/coating apparatus to the supply container; and,

heat exchanger means coupled to the circulation means for maintaining the temperature of the liquid ink or coating material within a predetermined temperature range.

20. A printing press as defined in claim 1, wherein the inking/coating apparatus is pivotally mounted on the first printing unit in a position in which the nip contact point between the applicator roller and a blanket or plate is offset with respect to a radius line projecting through the center of the plate cylinder or blanket cylinder to the axis of rotation of the printing/coating unit.

21. A printing press as defined in claim 1, including:

a dryer mounted on the first printing unit for discharging heated air onto a freshly printed or coated substrate before the freshly printed or coated substrate is subsequently printed, coated or otherwise processed on the second printing unit.

22. A printing press as defined in claim 21, wherein:

the dryer is mounted adjacent the impression cylinder of the first printing unit for discharging heated air onto a freshly printed or coated substrate while the substrate is in contact with said impression cylinder.

23. A printing press as defined in claim 1, further including:

a substrate transfer apparatus disposed in an interunit position on the press and coupled in substrate transfer relation with the impression cylinder of the first printing unit;

an interunit dryer disposed adjacent the substrate transfer apparatus for discharging heated air onto a freshly printed or coated substrate after it has been transferred from the first printing unit and while it is in contact with the substrate transfer apparatus.

24. A printing press as defined in claim 1, comprising:

a dryer mounted on the first printing unit for discharging heated air onto a freshly printed or coated substrate; and,

an extractor coupled to the dryer for extracting hot air and moisture vapors from an exposure zone between the dryer and the freshly printed or coated substrate.

"RETRACTABLE PRINTING/COATING UNIT OPERABLE ON THE PLATE AND BLANKET CYLINDERS SIMULTANEOUSLY FROM THE DAMPENER SIDE OF THE FIRST PRINTING UNIT OR ANY CONSECUTIVE PRINTING UNIT OF ANY ROTARY OFFSET PRINTING PRESS"

Abstract of the Disclosure

A retractable in-line inking/coating apparatus can apply either spot or overall inking/coating material to a plate and/or a blanket on the first printing unit or on any consecutive printing unit of any rotary offset printing press. The inking/coating apparatus is pivotally mounted within the conventional dampener space of any lithographic printing unit. The aqueous component of the flexographic printing ink or aqueous coating material is evaporated and dried by high velocity, hot air dryers and high performance heat and moisture extractors so that the aqueous or flexographic ink or coating material on a freshly printed or coated sheet is dry and can be dry-trapped on the next printing unit. The inking/coating apparatus includes dual cradles that support first and second applicator rollers so that the inking/coating apparatus can apply a double bump of aqueous/flexographic or UV-curable printing ink or coating material to a plate on the plate cylinder, while simultaneously applying aqueous, flexographic or UV-curable printing ink or coating material to a plate or a blanket on the blanket cylinder, and thereafter onto a sheet as the sheet is transferred through the nip between the blanket cylinder and the impression cylinder. A triple bump is printed or coated on the last printing unit with the aid of an impression cylinder inking/coating unit.

* * * * * * *

DTG\1975\0168DOCS\86038D.APP

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 1



FIG. 2

B6038

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD

2/10



FIG. 3

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 4

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 5

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 6



FIG. 7

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 8



FIG. 9

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 14

FIG. 15

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 10



FIG. 11



FIG. 12

FIG. 13

B6038

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 18

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 16



FIG. 17

UEXKÜLL & STOLBERG
PATENTANWÄLTE

BESELERSTRASSE 4
D - 22607 HAMBURG

EUROPEAN PATENT ATTORNEYS

DR. ULRICH GRAF STOLBERG
DIPL.-ING. JÜRGEN SUCHANTKE
DIPL.-ING. ARNULF HUBER
DR. ALLARD von KAMEKE
DIPL.-BIOL. INGEBORG VOELKER
DR. PETER FRANCK
DR. GEORG BOTH
DR. ULRICH-MARIA GROSS
DR. HELMUT von HEESCH
DIPL.-BIOL. JOACHIM STÜRKEN
DR. JOHANNES AHME
DR. HEINZ-PETER MUTH

TELEFON: (040) 899 6540
FAX: (040) 899 654 88
100763.733@COMPUSERVE.COM

18. 10. 1996
P 44214 -/lis

European Patent Office
Erhardtstraße 27

80331 München

EP0750960A1 96250220.9

Application No.: 96250220.9

Applicant : Howard W. DeMoore

Please find the following documents enclosed:

- Priority Document 08/538,274

1 X PRIO

R.T. Koerse 25. 10. 1996

A. Huber
(Association No. 1)



E UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office

October 10, 1996

IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE
RDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF
E PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT
THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER
111.

CATION NUMBER: *08/538,274*
G DATE: *October 2, 1995*

By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS

NORMA WOODSON
Certifying Officer

PATENT APPLICATION SERIAL NO. 08/538274

U.S. DEPARTMENT OF COMMERCE
PATENT AND TRADEMARK OFFICE
FEE RECORD SHEET

290 SB 11/06/95 08538274
1 201 386.00 CK 86038D

PTO-1554
(5/87)

386-20

08/538274

Attorney Docket
No. B6038D

SPECIFICATION

accompanying

Application for Grant of U.S. Letters Patent

JOINT
INVENTORS: Howard W. DeMoore
10954 Shady Trail
Dallas, Texas 75220

Ronald M. Rendleman
4331 Royal Ridge
Dallas, Texas 75229

John W. Bird
1514 Iroquois Circle
Carrollton, Texas 75007

TITLE: "RETRACTABLE PRINTING/COATING UNIT OPERABLE ON THE PLATE AND BLANKET CYLINDERS SIMULTANEOUSLY FROM THE DAMPENER SIDE OF THE FIRST PRINTING UNIT OR ANY CONSECUTIVE PRINTING UNIT OF ANY ROTARY OFFSET PRINTING PRESS"

Field of the Invention

This invention relates generally to sheet-fed or web-fed, rotary offset lithographic printing presses, and more particularly, to a new and improved inking/coating apparatus for the in-line application of aqueous or flexographic printing inks, primer or protective/decorative coatings applied simultaneously to the plate and blanket of the first or any consecutive printing unit of any lithographic printing press.

Background of the Invention

Conventional sheet-fed, rotary offset printing presses typically include one or more printing units through which individual sheets are fed and printed. After the last printing unit, freshly printed sheets are transferred by a delivery conveyor to the delivery end of the press where the freshly printed and/or coated sheets are collected and stacked uniformly. In a typical sheet-fed, rotary offset printing press such as the Heidelberg Speedmaster line of presses, the delivery conveyor includes a pair of endless chains carrying gripper bars with

gripper fingers which grip and pull freshly printed sheets from the last impression cylinder and convey the sheets to the sheet delivery stacker.

Since the inks used with sheet fed rotary offset printing presses are typically wet and tacky, special precautions must be taken to prevent marking and smearing of the freshly printed or coated sheets as the sheets are transferred from one printing unit to another. The printed ink on the surface of the sheet dries relatively slowly and is easily smeared during subsequent transfer between printing units. Marking, smearing and smudging can be prevented by a vacuum assisted sheet transfer apparatus as described in the following U.S. Patents: 5,113,255; 5,127,329; 5,205,217; 5,228,391; 5,243,909; and 5,419,254, all to Howard W. DeMoore, co-inventor, and manufactured and sold by Printing Research, Inc. of Dallas, Texas, U.S.A. under its trademark BACVAC™.

In some printing jobs, offsetting is prevented by applying a protective and/or decorative coating material over all or a portion of the freshly printed sheets. Some coatings are formed of a UV-curable or water-dispersed resin applied as a liquid solution over the freshly printed sheets to protect the ink from offsetting or set-off and improve the appearance of the freshly printed sheets. Such coatings are particularly desirable when decorative or protective finishes are applied in the printing of posters, record jackets, brochures, magazines, folding cartons and the like.

<u>Description of the Prior Art</u>

Various arrangements have been made for applying the coating as an in-line printing operation by using the last printing unit of the press as the coating application unit. For example, U.S. Patents 4,270,483; 4,685,414; and 4,779,557 disclose coating apparatus which can be moved into position to permit the blanket cylinder of the last printing unit of a printing press to be used to apply a coating material over the freshly printed

sheets. In U.S. Patent 4,841,903 (Bird) there are disclosed coating apparatus which can be selectively moved between the plate cylinder or the blanket cylinder of the last printing unit of the press so the last printing unit can only be used for coating purposes. However, when coating apparatus of these types are being used, the last printing unit cannot be used to print ink to the sheets, but rather can only be used for the coating operation. Thus, while coating with this type of in-line coating apparatus, the printing press loses the capability of printing on the last printing unit as it is converted to a coating unit.

The coater of U.S. Patent 5,107,790 (Sliker et al) is retractable along an inclined rail for extending and retracting a coater head into engagement with a blanket on the blanket cylinder. Because of its size, the rail-retractable coater can only be installed between the last printing unit of the press and the delivery sheet stacker, and cannot be used for interunit coating. The coater of U.S. Patent 4,615,293 (Jahn) provides two separate, independent coaters located on the dampener side of a converted printing unit for applying lacquer to a plate and to a rubber blanket. Consequently, although a plate and blanket are provided, the coating unit of Jahn's press is restricted to a dedicated coating operation only.

Proposals have been made for overcoming the loss of a printing unit when in-line coating is used, for example as set forth in U.S. Patent 5,176,077 to Howard W. DeMoore (co-inventor and assignee), which discloses a coating apparatus having an applicator roller positioned to apply the coating material to the freshly printed sheet while the sheet is still on the last impression cylinder of the press. This allows the last printing unit to print and coat simultaneously, so that no loss of printing unit capability results.

Some conventional coaters are rail-mounted and occupy a large amount of press space and reduce access to the press. Elaborate equipment is needed for retracting such coaters from the

operative coating position to the inoperative position, which reduces access to the printing unit.

Accordingly, there is a need for an in-line inking/coating apparatus which does not result in the loss of a printing unit, does not extend the length of the press, and which can print and coat aqueous and flexographic inks and coating materials simultaneously onto the plate and blanket on any lithographic printing unit of any lithographic printing press, including the first printing unit.

<u>Objects of the Invention</u>

Accordingly, a general object of the present invention is to provide improved inking/coating apparatus which is capable of selectively applying ink or coating material to a plate on a plate cylinder or ink or coating material to a plate or blanket on a blanket cylinder.

A specific object of the present invention is to provide improved inking/coating apparatus of the character described which is extendable into inking/coating engagement with either a plate on a plate cylinder or to a plate or blanket on a blanket cylinder.

A related object of the present invention is to provide improved inking/coating apparatus of the character described which is capable of being mounted on any lithographic printing unit of the press and does not interfere with operator access to the plate cylinder, blanket cylinder, or adjacent printing units.

Another object of the present invention is to provide improved inking/coating apparatus of the character described, which can be moved from an operative inking/coating engagement position adjacent to a plate cylinder or a blanket cylinder to a non-operative, retracted position.

Still another object of the present invention is to provide improved inking/coating apparatus of the character described, which can be used for applying aqueous, flexographic and ultra-violet curable inks and/or coatings in combination with

lithographic, flexographic and waterless printing processes on any rotary offset printing press.

A related object of the present invention is to provide improved inking/coating apparatus of the character described, which is capable of applying aqueous or flexographic ink or coating material on one printing unit, for example the first printing unit, and drying the ink or coating material before it is printed or coated on the next printing unit so that it can be overprinted or overcoated immediately on the next printing unit with waterless, aqueous, flexographic or lithographic inks or coating materials.

Yet another object of the present invention is to provide improved inking/coating apparatus for use on a multiple color rotary offset printing press that can apply ink or coating material separately and/or simultaneously to the plate and/or blanket of a printing unit of the press from a single operative position, and from a single inking/coating apparatus.

A related object of the present invention is to provide improved inking/coating apparatus of the character described, in which virtually no printing unit adjustment or alteration is required when the inking/coating apparatus is converted from plate to blanket printing or coating and vice versa.

Another object of the present invention is to provide improved inking/coating apparatus that can be operably mounted in the dampener space of any lithographic printing unit for inking/coating engagement with either a plate on a plate cylinder or a plate or blanket on a blanket cylinder, and which does not interfere with operator movement or activities in the interunit space between printing units.

Summary of the Invention

The foregoing objects are achieved by a retractable, inline inking/coating apparatus which is mounted on the dampener side of any printing unit of a rotary offset press for movement between an operative (on-impression) inking/coating position and

a retracted, disengaged (off-impression) position. The inking/coating apparatus includes an applicator roller which is movable into and out of engagement with a plate on a plate cylinder or a blanket on a blanket cylinder. The inking/coating applicator head is pivotally coupled to a printing unit by pivot pins which are mounted on the press side frames in the traditional dampener space of the printing unit in parallel alignment with the plate cylinder and the blanket cylinder. This dampener space mounting arrangement allows the inking/coating unit to be installed between any adjacent printing units on the press.

In the preferred embodiment, the applicator head includes vertically spaced pairs of cradle members with one cradle pair being adapted for supporting an inking/coating applicator roller in alignment with a plate cylinder, and the other cradle pair supporting an inking/coating applicator roller in alignment with the blanket cylinder, respectively, when the applicator head is in the operative position. Because of the pivotal support provided by the pivot pins, the applicator head can be extended and retracted within the limited space available in the traditional dampener space, without restricting operator access to the printing unit cylinders and without causing a printing unit to lose its printing capability.

When the inking/coating apparatus is used in combination with a flexographic printing plate and aqueous or flexographic ink or coating material, the water component of the aqueous or flexographic ink or coating material on the freshly printed or coated sheet is evaporated and dried by a high velocity, hot air interunit dryer and a high volume heat and moisture extractor assembly so that the freshly printed ink or coating material is dry before the sheet is printed or coated on the next printing unit. This quick drying process permits a base layer or film of ink, for example opaque white or metallic (gold, silver or other metallics) ink to be printed on the first printing unit, and then overprinted on the next printing unit witnout back-trapping or dot gain.

The construction and operation of the present invention will be understood from the following detailed description taken in conjunction with the accompanying drawings which disclose, by way of example, the principles and advantages of the present invention.

Brief Description of the Drawings

FIGURE 1 is a perspective view of a sheet fed, rotary offset printing press having inking/coating apparatus embodying the present invention;

FIGURE 2 is a simplified perspective view of the single head, dual cradle inking/coating apparatus of the present invention;

FIGURE 3 is a schematic side elevational view of the printing press of Figure 1 having single head, dual cradle inking/coating apparatus installed in the traditional dampener position of the first, second and last printing units;

FIGURE 4 is a simplified side elevational view showing the single head, dual cradle inking/coating apparatus in the operative inking/coating position for simultaneously printing on the printing plate and blanket on the fourth printing unit;

FIGURE 5 is a simplified side elevational view showing the single head, dual cradle inking/coating apparatus in the operative position for spot or overall inking or coating on the blanket of the first printing unit, and showing the dual cradle inking/coating apparatus in the operative position for spot or overall inking or coating on the printing plate of the second printing unit;

FIGURE 6 is a simplified side elevational view of the single head, dual cradle inking/coating apparatus of FIGURE 4 and FIGURE 5, partially broken away, showing the single head, dual cradle inking/coating apparatus in the operative coating position and having a sealed doctor blade reservoir assembly for spot or overall coating on the blanket;

FIGURE 7 is a schematic view showing a heat exchanger and pump assembly connected to the single head, dual cradle inking/coating apparatus for circulating temperature controlled ink or coating material to the inking/coating apparatus;

FIGURE 8 is a side elevational view, partially broken away, and similar to FIGURE 6 which illustrates an alternative coating head arrangement;

FIGURE 9 is a simplified elevational view of a printing unit which illustrates pivotal coupling of the inking/coating apparatus on the printing unit side frame members;

FIGURE 10 is a view similar to FIGURE 2 in which a pair of split applicator rollers are mounted in the upper cradle and lower cradle, respectively;

FIGURE 11 is a side elevational view of a split applicator roller;

FIGURE 12 is a perspective view of a doctor blade reservoir which is centrally partitioned by a seal element;

FIGURE 13 is a sectional view showing sealing engagement of the split applicator roller against the partition seal element of FIGURE 12;

FIGURE 14 is a view similar to FIGURE 8 which illustrates an alternative inking/coating embodiment;

FIGURE 15 is a simplified side elevational view of a substrate which has a bronzed-like finish which is applied by simultaneous operation of the dual applicator roller embodiment of FIGURE 14;

FIGURE 16 is a side elevational view, partly in section, of a pan roller having separate transfer surfaces mounted on a split fountain pan;

FIGURE 17 is a simplified side elevational view of the dual cradle inking/coating apparatus, partially broken away, which illustrates an alternative inking/coating head apparatus featuring a single doctor blade assembly, anilox applicator roller mounted on the lower cradle; and

FIGURE 18 is a side elevational view, partly in section, of a single doctor blade anilox applicator roller assembly having separate transfer surfaces, and a split fountain pan having separate fountain compartments, with the separate fountain compartments being supplied with different inks or coating materials from separate off-press sources.

Detailed Description of the Preferred Embodiments

As used herein, the term "processed" refers to printing and coating methods which can be applied to either side of a substrate, including the application of lithographic, waterless, UV-curable, aqueous and flexographic inks and/or coatings. The term "substrate" refers to sheet and web material. Also, as used herein, the term "waterless printing plate" refers to a printing plate having image areas and non-image areas which are oleophilic and oleophobic, respectively. "Waterless printing ink" refers to an oil-based ink which does not contain a significant aqueous component. "Flexographic plate" refers to a flexible printing plate having a relief surface which is wettable by flexographic ink or coating material. "Flexographic printing ink or coating material" refers to an ink or coating material having a base constituent of either water, solvent or UV-curable liquid. "UV-curable lithographic printing ink and coating material" refers to oil-based printing inks and coating materials that can be cured (dried) photomechanically by exposure to ultraviolet radiation, and that have a semi-paste or gel-like consistency. "Aqueous printing ink or coating material" refers to an ink or coating material that predominantly contains water as a solvent, diluent or vehicle. A "relief plate" refers to a printing plate having image areas which are raised relative to non-image areas which are recessed.

As shown in the exemplary drawings, the present invention is embodied in a new and improved in-line inking/coating apparatus, herein generally designated 10, for applying aqueous, flexographic or UV-curable inks or protective and/or decorative

coatings to sheets or webs printed in a sheet-fed or web-fed, rotary offset printing press, herein generally designated 12. In this instance, as shown in FIGURE 1, the inking/coating apparatus 10 is installed in a four unit rotary offset printing press 12, such as that manufactured by Heidelberger Druckmaschinen AG of Germany under its designation Heidelberg Speedmaster SM102 (40", 102cm).

The press 12 includes a press frame 14 coupled at one end, herein the right end, to a sheet feeder 16 from which sheets, herein designated S, are individually and sequentially fed into the press, and at the opposite end, with a sheet delivery stacker 20 in which the freshly printed sheets are collected and stacked. Interposed between the sheet feeder 16 and the sheet delivery stacker 20 are four substantially identical sheet printing units 22, 24, 26 and 28 which can print four different colors onto the sheets as they are transferred through the press 12. The printing units are housed within printing towers T1, T2, T3 and T4 formed by side frame members 14, 15. Each printing tower has a delivery side 25 and a dampener side 27. A dampener space 29 is partially enclosed by the side frames on the dampener side of the printing unit.

As illustrated, the printing units 22, 24, 26 and 28 are substantially identical and of conventional design. The first printing unit 22 includes an in-feed transfer cylinder 30, a plate cylinder 32, a blanket cylinder 34 and an impression cylinder 36, all supported for rotation in parallel alignment between the press side frames 14, 15 which define printing unit towers T1, T2, T3 and T4. Each of the first three printing units 22, 24 and 26 have a transfer cylinder 38 disposed to transfer the freshly printed sheets from the adjacent impression cylinder and transfer the freshly printed sheets to the next printing unit via an intermediate transfer drum 40.

The last printing unit 28 includes a delivery cylinder 42 mounted on a delivery shaft 43. The delivery cylinder 42 supports the freshly printed sheet 18 as it is transferred from

the last impression cylinder 36 to a delivery conveyor system, generally designated 44, which transfers the freshly printed sheet to the sheet delivery stacker 20. To prevent smearing during transfer, a flexible covering is mounted on the delivery cylinder 42, as described and claimed in U.S. Patent 4,402,267 to Howard W. DeMoore, which is incorporated herein by reference. The flexible covering is manufactured and sold by Printing Research, Inc. of Dallas, Texas, U.S.A., under its trademark SUPER BLUE®. Optionally, a vacuum-assisted sheet transfer assembly manufactured and sold by Printing Research, Inc. of Dallas, Texas, U.S.A., under its trademark BACVAC® can be substituted for the delivery transfer cylinder 42 and flexible covering.

The delivery conveyor system 44 as shown in FIGURE 2 is of conventional design and includes a pair of endless delivery gripper chains 46, only one of which is shown carrying at regular spaced locations along the chains, laterally disposed gripper bars having gripper fingers used to grip the leading edge of a freshly printed or coated sheet 18 after it leaves the nip between the impression cylinder 36 and delivery cylinder 42 of the last printing unit 28. As the leading edge is gripped by the gripper fingers, the delivery chains 46 pull the sheet away from the last impression cylinder 36 and convey the freshly printed or coated sheet to the sheet delivery stacker 20.

Prior to reaching the delivery sheet stacker, the freshly printed and/or coated sheets S pass under a delivery dryer 48 which includes a combination of infra-red thermal radiation, high velocity hot air flow and a high performance heat and moisture extractor for drying the ink and/or the protective/decorative coating. Preferably, the delivery dryer 48, including the high performance heat and moisture extractor is constructed as described in U.S. Application Serial Number 08/116,711, filed September 3, 1993, entitled "Infra-Red Forced Air Dryer and Extractor" by Howard C. Secor, Ronald M. Rendleman and Paul D. Copenhaver, commonly assigned to the assignee of the present invention, Howard W. DeMoore, and licensed to Printing

Research, Inc. of Dallas, Texas, U.S.A., which manufactures and markets the delivery dryer 48 under its trademark AIR BLANKET™.

In the exemplary embodiment shown in FIGURE 3, the first printing unit 22 has a flexographic printing plate PF mounted on the plate cylinder, and therefore neither an inking roller train nor a dampening system is required. A flexographic printing plate PF is also mounted on the plate cylinder of the second printing unit 24. The form rollers of the inking roller train 52 shown mounted on the second printing unit 24 are retracted and locked off to prevent plate contact. Flexographic ink is supplied to the flexographic plate PF of the second printing unit 24 by the inking/coating apparatus 10.

A suitable flexographic printing plate PF is offered by E.I. du Pont de Nemours of Wilmington, Delaware, U.S.A., under its trademark CYREL®. Another source is BASF Aktiengesellschaft of Ludwigshafen, Germany, which offers a suitable flexographic printing plate under its trademark NYLOFLEX®.

The third printing unit 26 as illustrated in FIGURE 3 and FIGURE 4 is equipped for lithographic printing and includes an inking apparatus 50 having an inking roller train 52 arranged to transfer ink Q from an ink fountain 54 to a lithographic plate P mounted on the plate cylinder 32. This is accomplished by a fountain roller 56 and a ductor roller 57. The fountain roller 56 projects into the ink fountain 54, whereupon its surface picks up ink. The lithographic printing ink Q is transferred from the fountain roller 56 to the inking roller train 52 by the ductor roller 57. The inking roller train 52 supplies ink Q to the image areas of the lithographic printing plate P.

The lithographic printing ink Q is transferred from the lithographic printing plate P to an ink receptive blanket B which is mounted on the blanket cylinder 34. The inked image carried on the blanket B is transferred to a substrate S as the substrate is transferred through the nip between the blanket cylinder 34 and the impression cylinder 36.

The inking roller arrangement 52 illustrated in FIGURE 3 and FIGURE 4 is exemplary for use in combination with lithographic ink printing plates P. It is understood that a dampening system 58 having a dampening fluid reservoir DF is coupled to the inking roller train 52 (FIGURE 4), but is not required for waterless or flexographic printing.

The plate cylinder 32 of printing unit 28 is equipped with a waterless printing plate PW. Waterless printing plates are also referred to as dry planographic printing plates and are disclosed in the following U.S. patents: 3,910,187; Re. 30,670; 4,086,093; and 4,853,313. Suitable waterless printing plates can be obtained from Toray Industries, Inc. of Tokyo, Japan. A dampening system is not used for waterless printing, and waterless (oil-based) printing ink is used. The waterless printing plate PW has image areas and non-image areas which are oleophilic/hydrophilic and oleophobic/hydrophobic, respectively. The waterless printing plate PW is engraved or etched, with the image areas being recessed with respect to the non-image areas. The image area of the waterless printing plate PW is rolled-up with the flexographic or aqueous printing ink which is transferred by the applicator roller 66. Both aqueous and oil-based inks and coatings are repelled from the non-image areas, and are retained in the image areas. The printing ink or coating is then transferred from the image areas to an ink or coating receptive blanket B and is printed or coated onto a substrate S.

For some printing jobs, a flexographic plate PF or a waterless printing plate PW is mounted over a resilient packing such as the blanket B on the blanket cylinder 34, for example as indicated by phantom lines in printing unit 22 of FIGURE 5. An advantage of this alternative embodiment is that the waterless plate PW or the flexographic plate PF are resiliently supported over the blanket cylinder by the underlying blanket B or other resilient packing. The radial deflection and give of the resilient blanket B provides uniform, positive engagement between

the applicator roller 66 and a flexographic plate or waterless plate.

In that arrangement, a plate is not mounted on the plate cylinder 32; instead, a waterless plate PW is mounted on the blanket cylinder, and the inked image on the waterless printing plate is not offset but is instead transferred directly from the waterless printing plate PW to the substrate S. The water component of flexographic ink on the freshly printed sheet is evaporated by high velocity, hot air dryers and high volume heat and moisture extractors so that the freshly printed aqueous or flexographic ink is dried before the substrate is printed on the next printing unit.

Referring now to FIGURE 2, FIGURE 3 and FIGURE 9, the inking/coating apparatus 10 is pivotally mounted on the side frames 14, 15 for rotation about an axis X. The inking/coating apparatus 10 includes a frame 60, a hydraulic motor 62, a lower gear train 64, an upper gear train 65, an applicator roller 66, a sealed doctor blade assembly 68 (FIGURE 6), and a drip pan DP, all mounted on the frame 60. The external peripheral surface of the applicator roller 66 is wetted by contact with liquid coating material or ink contained in a reservoir 70.

The hydraulic motor 62 drives the applicator roller 66 synchronously with the plate cylinder 32 and the blanket cylinder 34 in response to an RPM control signal from the press drive (not illustrated) and a feedback signal developed by a tachometer 72. While a hydraulic drive motor is preferred, other drive means such as an electric drive motor or an equivalent can be used.

When using waterless printing plate systems, the temperature of the waterless printing ink and of the waterless printing plate must be closely controlled for good image reproduction. For example, for waterless offset printing with TORAY waterless printing plates PW, it is absolutely necessary to control the waterless printing plate surface and waterless ink temperature to a very narrow range, for example 24°C (75°F) to 27°C (80°F).

Referring to FIGURE 7, the reservoir 70 is supplied with ink or coating which is temperature controlled by a heat exchanger 71. The temperature controlled ink or coating material is circulated by a positive displacement pump, for example a peristaltic pump, through the reservoir 70 and heat exchanger 71 from a source 73 through a supply conduit 75 and a return conduit 77. The heat exchanger 71 cools or heats the ink or coating material and maintains the ink or coating and the printing plate within the desired narrow temperature range.

According to one aspect of the present invention, aqueous/flexographic ink or coating material is supplied to the applicator roller 66, which transfers the aqueous/flexographic ink or coating material to the printing plate (FIGURE 7), which may be a waterless printing plate or a flexographic printing plate. When the inking/coating apparatus is used for applying aqueous/flexographic ink or coating material to a waterless printing plate PW, the inking roller train 52 is not required, and is retracted away from the printing plate. Because the viscosity of aqueous/flexographic printing ink or coating material varies with temperature, it is necessary to heat or cool the aqueous/flexographic printing ink or coating material to compensate for ambient temperature variations to maintain the ink viscosity in a preferred operating range.

For example, the temperature of the printing press can vary from around 60°F (15°C) in the morning, to around 85°F (29°C) or more in the afternoon. The viscosity of aqueous/flexographic printing ink or coating material can be marginally high when the ambient temperature of the press is near 60°F (15°C), and the viscosity can be marginally low when the ambient temperature of the press exceeds 85°F (29°C). Consequently, it is desirable to control the temperature of the aqueous/flexographic printing ink or coating material so that it will maintain the surface temperature of waterless printing plates within the specified temperature range. Moreover, the ink/coating material temperature should be controlled to maintain the tack of the aqueous/flexographic

printing ink or coating material within a desired range when the ink or coating material is being used in connection with flexographic printing processes.

The applicator roller 66 is preferably an anilox fluid metering roller which transfers measured amounts of printing ink or coating material to a plate or blanket. The surface of an anilox roller is engraved with an array of closely spaced, shallow depressions referred as "cells". Ink or coating from the reservoir 70 flows into the cells as the anilox roller turns through the reservoir. The transfer surface of the anilox roller is "doctored" (wiped or scraped) by dual doctor blades 68A, 68B to remove excess ink or coating material. The ink or coating metered by the anilox roller is that contained within the cells. The dual doctor blades 68A, 68B also seal the supply reservoir 70.

The anilox applicator roller 66 is cylindrical and may be constructed in various diameters and lengths, containing cells of various sizes and shapes. The volumetric capacity of an anilox roller is determined by cell size, shape and number of cells per unit area. Depending upon the intended application, the cell pattern may be fine (many small cells per unit area) or coarse (fewer large cells per unit area).

By supplying the ink or coating material through the inking/coating apparatus 10, more ink or coating material can be applied to the sheet S as compared with the inking roller train of a lithographic printing unit. Moreover, color intensity is stronger and more brilliant because the aqueous or flexographic ink or coating material is applied at a much heavier film thickness or weight than can be applied by the lithographic process, and the aqueous or flexographic colors are not diluted by dampening solution.

Preferably, the sealed doctor blade assembly 68 is constructed as described in U.S. Patent 5,176,077 to Howard W. DeMoore, co-inventor and assignee, which is incorporated herein by reference. An advantage of using a sealed reservoir is that fast drying ink or coating material can be used. Fast drying ink or

coating material can be used in an open fountain 53 (see FIGURE 8); however, open air exposure causes the water and solvents in the fast-drying ink or coating material to evaporate faster, thus causing the ink or coating material to dry prematurely and change viscosity. Moreover, an open fountain emits unwanted odors into the press room. When the sealed doctor blade assembly is utilized, the pump (FIGURE 7) which circulates ink or coating material to the doctor blade head is preferably a peristaltic pump, which does not inject air into the feeder lines which supply the ink or coating reservoir 70 and helps to prevent the formation of air bubbles and foam within the ink or coating material.

An inking/coating apparatus 10 having an alternative applicator roller arrangement is illustrated in FIGURES 10-13. In this arrangement, the engraved metering surface of the anilox applicator rollers 66, 67 are partitioned by smooth seal surfaces 66C which separates a first engraved peripheral surface portion 66A from a second engraved peripheral surface portion 66B. Likewise, smooth seal surfaces 66D, 66E are formed on the opposite end portions of the applicator roller 66 for engaging end seals 134, 136 (FIGURE 12) of the doctor blade reservoir. The upper applicator roller 67 has engraved anilox metering surfaces 67A and 67B which are separated by a smooth seal band 67C.

Referring now to FIGURE 12 and FIGURE 13, the reservoir 70 of the doctor blade head 68 is partitioned by a curved seal element 130 to form two separate chambers 70A, 70B. The seal element 130 is secured to the doctor blade head within an annular groove 132. The seal element 130 is preferably made of polyurethane foam or other durable, resilient foam material. The seal element 130 is engaged by the seal band 66, thus forming a rotary seal which blocks the leakage of ink or coating material from one reservoir chamber into the other reservoir chamber. Moreover, the seal band provides an unprinted or uncoated area which separates the printed or coated areas from each other, which is needed for work and turn printing jobs or other printing jobs which print two or more separate images onto the same substrate.

Another advantage of the split applicator roller embodiment is that it enables two or more flexographic inks or coating materials to be printed simultaneously within the same lithographic printing unit. That is, the reservoir chambers 70A, 70B of the upper doctor blade assembly can be supplied with gold ink and silver ink, for example, while the reservoir chambers 70A, 70B of the lower doctor blade assembly can be supplied with inks of two additional colors, for example opaque white ink and blue ink. This permits the opaque white ink to be overprinted with the gold ink, and the blue ink to be overprinted with the silver ink on the same printing unit on any lithographic press.

Moreover, a catalyst can be used in the upper doctor blade reservoir and a reactive ink or coating material can be used in the lower doctor blade reservoir. This can provide various effects, for example improved chemical resistance and higher gloss levels.

The split applicator roller sections 67A, 67B in the upper cradle position can be used for applying two separate inks or coating materials simultaneously, for example flexographic, aqueous and ultra-violet curable inks or coating materials, to separate surface areas of the plate, while the lower applicator roller sections 66A, 66B can apply an initiator layer and a micro-encapsulated layer simultaneously to separate blanket surface areas. Optionally, the metering surface portions 66A, 66B can be provided with different cell metering capacities for providing different printing effects which are being printed simultaneously. For example, the screen line count on one half-section of an anilox applicator roller is preferably in the range of 200-600 lines per inch (79-236 lines per cm) for half-tone images, and the screen line count of the other half-section is preferably in the range of 100-300 lines per inch (39-118 lines per cm) for overall coverage, high weight applications such as opaque white. This split arrangement in combination with dual applicator rollers is particularly advantageous when used in connection with "work and turn" printing jobs.

Referring again to FIGURE 8, instead of using the sealed doctor blade reservoir assembly 68 as shown in FIGURE 6, an open fountain assembly 69 is provided by the fountain pan 53 which contains a volume of liquid ink Q or coating material. The liquid ink or coating material is transferred to the applicator roller 66 by a pan roller 55 which turns in contact with ink Q or coating material in the fountain pan. If a split applicator roller is used, the pan roller 55 is also split, and the pan is divided into two pan sections 53A, 53B by a separator plate 53P, as shown in FIGURE 16.

In the alternative embodiment of FIGURE 16, the pan roller 55 is divided into two pan roller sections 55A, 55B by a centrally located, annular groove 59. The separator plate 53P is received within and centrally aligned with the groove 59, but does not touch the adjoining roller faces. By this arrangement, two or more inks or coating materials Q1, Q2 are contained within the open pan sections 55A, 55B for transfer by the split pan roller sections 53A, 53B, respectively. This permits two or more flexographic inks or coating materials to be transferred to two separate image areas on the plate or on the blanket of the same printing unit. This arrangement is particularly advantageous for work and turn printing jobs or other printing jobs which print two or more separate images onto the same substrate.

The frame 60 of the inking/coating apparatus 10 includes side support members 74, 76 which support the applicator roller 66, gear train 64, gear train 65, doctor blade assembly 68 and the drive motor 62. The applicator roller 66 is mounted on stub shafts 63A, 63B which are supported at opposite ends on a lower cradle assembly 100 formed by a pair of side support members 78, 80 which have sockets 79, 81 and retainer caps 101, 103. The stub shafts are received in roller bearings 105, 107 which permit free rotation of the applicator roller 66 about its longitudinal axis A1 (axis A2 in the upper cradle). The retainer caps 101, 103 hold the stub shafts 63A, 63B and bearings 105, 107 in the sockets 79,

81 and hold the applicator roller 66 in parallel alignment with the pivot axis X.

The side support members 74, 76 also have an upper cradle assembly 102 formed by a pair of side support members 82, 84 which are vertically spaced with respect to the lower side plates 78, 80. Each cradle 100, 102 has a pair of sockets 79, 81 and 83, 85, respectively, for holding an applicator roller 66, 67 for spot coating or inking engagement with the printing plate P on the plate cylinder 32 (FIGURE 4) or with a printing plate P or a blanket B on the blanket cylinder 34.

Preferably, the applicator roller 67 (FIGURE 8, FIGURE 9) the upper cradle (plate) position is an anilox roller having a resilient transfer surface. In the dual cradle arrangement as shown in FIGURE 2, the press operator can quickly change from blanket inking/coating to plate inking/coating within minutes, since it is only necessary to release, remove and reposition or replace the applicator roller 66.

The capability to simultaneously print in the flexographic mode, the aqueous mode, the waterless mode, or the lithographic mode on different printing units of the same lithographic press and to print or coat from either the plate position or the blanket position on any one of the printing units is referred to herein as the LITHOFLEX™ printing process or system. LITHOFLEX™ is a trademark of Printing Research, Inc. of Dallas, Texas, U.S.A., exclusive licensee of the present invention.

Referring now to FIGURE 14, an inking/coating apparatus 10 having an inking/coating assembly 109 of an alternative design is installed in the upper cradle position for applying ink and/or coating material to a plate P on the plate cylinder 32. According to this alternative embodiment, an applicator roller 67R having a resilient transfer surface is coupled to an anilox fluid metering roller which transfers measured amounts of printing ink or coating material to the plate P. The anilox roller 111 has a transfer surface constructed of metal, ceramic or composite material which is engraved with cells. The resilient applicator roller 67R is

interposed in transfer engagement with the plate P and the metering surface of the anilox roller 111. The resilient transfer surface of the applicator roller 67R provides uniform, positive engagement with the plate.

Referring now to FIGURE 17, an inking/coating apparatus 10 having an alternative inking/coating assembly 113 is installed in the lower cradle assembly 100 for applying flexographic or aqueous ink and/or coating material Q to a plate or blanket mounted on the blanket cylinder 34. Instead of using the sealed, dual doctor blade reservoir assembly 68 as shown in FIGURE 6, an open, single doctor blade anilox roller assembly 113 is supplied with liquid ink Q or coating material contained in an open fountain pan 117. The liquid ink or coating material Q is transferred to the engraved transfer surface of the anilox roller 66 as it turns in the fountain pan 117. Excess ink or coating material Q is removed from the engraved transfer surface by a single doctor blade 68B. The liquid ink or coating material Q is pumped from an off-press source, for example the drum 73 shown in FIGURE 17, through a supply conduit 119 into the fountain pan 117 by a pump 120.

For overall inking or coating jobs, the metering transfer surface of the anilox roller 66 extends over its entire peripheral surface. However, for certain printing jobs which print two or more separate images onto the same substrate, for example work and turn printing jobs, the metering transfer surface of the anilox applicator roller 66 is partitioned by a centrally located, annular undercut groove 66C which separates first and second metering transfer surfaces 66A, 66B as shown in FIGURE 11 and FIGURE 18.

The single doctor blade 68B has an edge 68E which wipes simultaneously against the split metering transfer surfaces 66A, 66B. In this single blade, split anilox roller embodiment 113, it is necessary to provide dual supply sources, for example drums 73A, 73B, dual supply lines 119A, 119B, and dual pumps 120A, 120B. Moreover, the fountain pan 117 is also split, and the pan 117 is

divided into two pan sections 117A, 117B by a separator plate 121, as shown in FIGURE 18. The separator plate 121 is centrally aligned with the undercut groove 66C, but does not touch the adjoining roller faces.

Although the single blade, split anilox applicator roller assembly 113 is shown mounted in the lower cradle position (FIGURE 17), it should be understood that the single blade, split anilox applicator roller assembly 113 can be mounted and used in the upper cradle position, as well.

According to another aspect of the present invention, the inking/coating apparatus 10 is pivotally coupled on horizontal pivot pins 88P, 90P which allows the single head, dual cradle inking/coating apparatus 10 to be mounted on any lithographic printing unit. Referring to FIGURE 9, the horizontal pivot pins 88P, 90P are mounted within the traditional dampener space 29 of the printing unit and are secured to the press side frames 14, 15, respectively. Preferably, the pivot support pins 88P, 90P are secured to the press side frames by a threaded fastener. The pivot support pins are received within circular openings 88, 90 which intersect the side support members 74, 76 of the inking/coating apparatus 10. The horizontal support pins 88P, 90P are disposed in parallel alignment with rotational axis X and with the plate cylinder and blanket cylinder, and are in longitudinal alignment with each other.

Preferably, the pivot pins 88P, 90P are located in the dampener space 29 so that the rotational axes A1, A2 of the applicator rollers 66, 67 are elevated with respect to the nip contact points N1, N2. By that arrangement, the transfer point between the applicator roller 66 and a blanket on the blanket cylinder 34 (as shown in FIGURE 8) and the transfer point between the applicator roller 66 and a plate on the plate cylinder 32 (as shown in FIGURE 5) are above the radius lines R1, R2 of the plate cylinder and the blanket cylinder, respectively. This permits the inking/coating apparatus 10 to move clockwise to retract the applicator roller 66 to an off-impression position relative to the

blanket cylinder in response to a single extension stroke of the power actuator arms 104A, 106A. Similarly, the applicator roller 66 is moved counterclockwise to the on-impression operative position as shown in FIGURES 4, 5, 6 and 8 by a single retraction stroke of the actuator arms 104A, 106A, respectively.

Preferably, the pivot pins are made of steel and the side support members are made of aluminum, with the steel pivot pins and the aluminum collar portion bordering the circular openings 88, 90 forming a low friction journal. By this arrangement, the inking/coating apparatus 10 is freely rotatable clockwise and counterclockwise with respect to the pivot pins 88P, 90P. Typically, the arc length of rotation is approximately 60 mils (about 1.5 mm). Consequently, the inking/coating apparatus 10 is almost totally enclosed within the dampener space 29 of the printing unit in the on-impression position and in the off-impression position.

The cradle assemblies 100 and 102 position the applicator roller 66 in inking/coating alignment with the plate cylinder or blanket cylinder, respectively, when the inking/coating apparatus 10 is extended to the operative (on-impression) position. Moreover, because the inking/coating apparatus 10 is installed within the dampener space 29, it is capable of freely rotating through a small arc while extending and retracting without being obstructed by the press side frames or other parts of the printing press. This makes it possible to install the inking/coating apparatus 10 on any lithographic printing unit. Moreover, because of its internal mounting position within the dampener space 29, the projection of the inking/coating apparatus 10 into the space between printing units is minimal. This assures unrestricted operator access to the printing unit when the applicator head is in the operative (on-impression) and retracted (off-impression) positions.

As shown in FIGURE 4 and FIGURE 5, movement of the inking/coating apparatus 10 is counterclockwise from the retracted

(off-impression) position to the operative (on-impression) position.

Although the dampener side installation is preferred, the inking/coating apparatus 10 can be adapted for operation on the delivery side of the printing unit, with the inking/coating apparatus being movable from a retracted (off-impression) position to an on-impression position for engagement of the applicator roller with either a plate on the plate cylinder or a blanket on the blanket cylinder on the delivery side 25 of the printing unit.

Movement of the inking/coating apparatus 10 to the operative (on-impression) position is produced by power actuators, preferably double acting pneumatic cylinders 104, 106 which have extendable/retractable power transfer arms 104A, 106A, respectively. The first pneumatic cylinder 104 is pivotally coupled to the press frame 14 by a pivot pin 108, and the second pneumatic cylinder 106 is pivotally coupled to the press frame 15 by a pivot pin 110. In response to selective actuation of the pneumatic cylinders 104, 106, the power transfer arms 104A, 106A are extended or retracted. The power transfer arm 104A is pivotally coupled to the side support member 74 by a pivot pin 112. Likewise, the power transfer arm 106A is pivotally coupled to the side support member 76 by a pivot pin 114.

As the power arms extend, the inking/coating apparatus 10 is rotated clockwise on the pivot pins 88P, 90P, thus moving the applicator roller 66 to the off-impression position. As the power arms retract, the inking/coater apparatus 60 is rotated counterclockwise on the pivot pins 88P, 90P, thus moving the applicator roller 66 to the on-impression position. The torque applied by the pneumatic actuators is transmitted to the inking/coating apparatus 10 through the pivot pin 112 and pivot pin 114.

Fine adjustment of the on-impression position of the applicator roller relative to the plate cylinder or the blanket cylinder, and of the pressure of roller engagement, is provided by an adjustable stop assembly 115. The adjustable stop assembly 115

has a threaded bolt 116 which is engagable with a bell crank 118. The bell crank 118 is pivotally coupled to the side support member 74 on a pin 120. One end of the bell crank 118 is engagable by the threaded bolt 116, and a cam roller 122 is mounted for rotation on its opposite end. The striking point of engagement is adjusted by rotation of the bolt 116 so that the applicator roller 66 is properly positioned for inking/coating engagement with the plate P or blanket B and provides the desired amount of inking/coating pressure when the inking/coating assembly 60 is moved to the operative position.

This arrangement permits the in-line inking/coating apparatus to operate effectively without encroaching in the interunit space between any adjacent printing units, and without blocking or obstructing access to the cylinders of the printing units when the inking/coating apparatus is in the extended (off-impression) position or retracted (on-impression) position. Moreover, when the in-line inking/coating apparatus is in the retracted position, the doctor blade reservoir and coating circulation lines can be drained and flushed automatically while the printing press is running as well as when the press has been stopped for change-over from one job to another or from one type of ink or coating to another.

Substrates which are printed or coated with aqueous flexographic printing inks require high velocity hot air for drying. When printing a flexographic ink such as opaque white or metallic gold, it is always necessary to dry the printed substrates between printing units before overprinting them. According to the present invention, the water component on the surface of the freshly printed or coated substrate S is evaporated and dried by high velocity, hot air interunit dryer and high volume heat and moisture extractor units 124, 126 and 128, as shown in FIGURE 2, FIGURE 4 and FIGURE 5. The dryer/extractor units 124, 126 and 128 are oriented to direct high velocity heated air onto the freshly printed/coated substrates as they are transferred by the impression cylinder 36 and the intermediate

transfer drum 40 of one printing unit and to another transfer cylinder 30 and to the impression cylinder 36 of the next printing unit. By that arrangement, the freshly printed flexographic ink or coating material is dried before the substrate S is overprinted by the next printing unit.

The high velocity, hot air dryer and high performance heat and moisture extractor units 124, 126 and 128 utilize high velocity air jets which scrub and break-up the moist air layer which clings to the surface of each freshly printed or coated sheet or web. Within each dryer, high velocity air is heated as it flows across a resistance heating element within an air delivery baffle tube. High velocity jets of hot air are discharged through multiple airflow apertures into an exposure zone Z (FIGURE 4 and FIGURE 5) and onto the freshly printed/coated sheet S as it is transferred by the impression cylinder 36 and transfer drum 40, respectively.

Each dryer assembly includes a pair of air delivery dryer heads 124D, 126D and 128D which are arranged in spaced, side-by-side relationship. The high velocity, hot air dryer and high performance heat and moisture extractor units 124, 126 and 128 are preferably constructed as disclosed in co-pending U.S. Patent Application Serial No. 08/132,584, filed October 6, 1993, entitled "High Velocity Hot Air Dryer", to Howard W. DeMoore, co-inventor and assignee of the present invention, and which is incorporated herein by reference, and which is marketed by Printing Research, Inc. of Dallas, Texas, U.S.A., under its trademark SUPER BLUE HV™.

The hot moisture-laden air displaced from the surface of each printed or coated sheet is extracted from the dryer exposure zone Z and exhausted from the printing unit by the high volume extractors 124, 126 and 128. Each extractor head includes an extractor manifold 124E, 126E and 128E coupled to the dryer heads 124D, 126D and 128D and draws the moisture, volatiles, odors and hot air through a longitudinal air gap G between the dryer heads. Best results are obtained when extraction is performed simulta-

neously with drying. Preferably, an extractor is closely coupled to the exposure zone Z at each dryer location as shown in FIGURE 4. Extractor heads 124E, 126E and 128E are mounted on the dryer heads 124D, 126D and 128D, respectively, with the longitudinal extractor air gap G facing directly into the exposure zone Z. According to this arrangement, each printed or coated sheet is dried before it is printed on the next printing unit.

The aqueous water-based inks used in flexographic printing evaporate at a relatively moderate temperature provided by the interunit high velocity hot air dryers/extractors 124, 126 and 128. Sharpness and print quality are substantially improved since the flexographic ink or coating material is dried before it is overprinted on the next printing unit. Since the freshly printed flexographic ink is dry, dot gain is substantially reduced and back-trapping on the blanket of the next printing unit is virtually eliminated. This interunit drying/extracting arrangement makes it possible to print flexographic inks such as metallic ink and opaque white ink on the first printing unit, and then dry-trap and overprint on the second and subsequent printing units.

Moreover, this arrangement permits the first printing unit 22 to be used as a coater in which a flexographic, aqueous or UV-curable coating material is applied to the lowest grade substrate such as recycled paper, cardboard, plastic and the like, to trap and seal-in lint, dust, spray powder and other debris and provide a smoother, more durable printing surface which can be overprinted on the next printing unit.

A first down (primer) aqueous coating layer seals-in the surface of a low grade, rough substrate, for example, re-cycled paper or plastic, and improves overprinted dot definition and provides better ink lay-down while preventing strike-through and show-through. A flexographic UV-curable coating material can then be applied downstream over the primer coating, thus producing higher coating gloss.

Preferably, the applicator roller 66 is constructed of composite carbon fiber material, metal or ceramic coated metal

when it is used for applying ink or coating material to the blanket B or other resilient material on the blanket cylinder 34. When the applicator roller 66 is applied to the plate, it is preferably constructed as an anilox roller having a resilient, compressible transfer surface. Suitable resilient roller surface materials include Buna N synthetic rubber and EPDM (terpolymer elastomer).

It has been demonstrated in prototype testing that the inking/coating apparatus 10 can apply a wide range of ink and coating types, including fluorescent (Day Glo), pearlescent, metallics (gold, silver and other metals), glitter, scratch and sniff (micro-encapsulated fragrance), scratch and reveal, luminous, pressure-sensitive adhesives and the like, as well as UV-curable and aqueous coatings.

With the dampener assembly removed from the printing unit, the inking/coating apparatus 10 can easily be installed in the dampener space for selectively applying flexographic inks and/or coatings to a flexographic or waterless printing plate or to the blanket. Moreover, overprinting of the flexographic inks and coatings can be performed on the next printing unit since the flexographic inks and/or coatings are dried by the high velocity, hot air interunit dryer and high volume heat and moisture extractor assembly of the present invention.

The flexographic inks and coatings as used in the present invention contain colored pigments and/or soluble dyes, binders which fix the pigments onto the surface of the substrate, waxes, defoamers, thickeners and solvents. Aqueous printing inks predominantly contain water as a diluent and/or vehicle. The thickeners which are preferred include algonates, starch, cellulose and its derivatives, for example cellulose esters or cellulose ethers and the like. Coloring agents including organic as well as inorganic pigments may be derived from dyes which are insoluble in water and solvents. Suitable binders include acrylates and/or polyvinylchloride.

When metallic inks are printed, the cells of the anilox roller must be appropriately sized to prevent the metal particles from getting stuck within the cells. For example, for metallic gold ink, the anilox roller should have a screen line count in the range of 175-300 lines per inch (68-118 lines per cm). Preferably, in order to keep the anilox roller cells clear, the doctor blade assembly 68 is equipped with a bristle brush BR (FIGURE 14) as set forth in U.S. Patent 5,425,809 to Steven M. Person, assigned to Howard W. DeMoore, and licensed to Printing Research, Inc. of Dallas, Texas, U.S.A., which is incorporated herein by reference.

The inking/coating apparatus 10 can also apply UV-curable inks and coatings. If UV-curable inks and coatings are utilized, ultra-violet dryers/extractors are installed adjacent to the high velocity hot air dryer/extractor units 124, 126 and 128, respectively.

It will be appreciated that the LITHOFLEX™ printing process described herein makes it possible to selectively operate a printing unit of a press in the lithographic printing mode while simultaneously operating another printing unit of the same press in either the flexographic printing mode or in the waterless printing mode, while also providing the capability to print or coat, separately or simultaneously, from either the plate position or the blanket position. The dual cradle support arrangement of the present invention makes it possible to quickly change over from inking/coating on the blanket cylinder position to inking/coating on the plate cylinder position with minimum press down-time, since it is only necessary to remove and reposition or replace the applicator roller 66 while the inking/coating apparatus 10 is in the retracted position. It is only necessary to remove four cap screws, lift the applicator roller 66 from the cradle, and reposition it in the other cradle. All of this can be accomplished in a few minutes, without removing the inking/coating apparatus 10 from the press.

It is possible to spot coat or overall coat from the plate position or from the blanket position with flexographic inks or coatings on one printing unit and then spot coat or overall coat with UV-curable inks or coatings from the plate position or from the blanket position on another printing unit during the same press run. Moreover, the press operator can spot or overall coat from the plate for one job, and then spot and/or overall coat from the blanket on the next job.

The positioning of the applicator roller relative to the plate or blanket is repeatable to a predetermined preset operative position. Consequently, only minor printing unit modifications or alterations may be required for the LITHOFLEX™ process. Although automatic extension and retraction have been described in connection with the exemplary embodiment, extension to the operative (on-impression) position and retraction to a non-operative (off-impression) position can be carried out manually, if desired. In the manual embodiment, it is necessary to latch the inking/coating apparatus 10 to the press side frames 14, 15 in the operative (on-impression) position, and to mechanically prop the inking/coating apparatus in the off-impression (retracted) position.

Referring again to FIGURE 8, an applicator roller 66 is mounted on the lower cradle assembly 100 by side support members 78, 80, and a second applicator roller 66 is mounted on the upper cradle assembly 102 by side support members 82, 84. According to this arrangement, the inking/coating apparatus 10 can apply printing ink and/or coating material to a plate on the plate cylinder, while simultaneously applying printing ink and/or coating material to a plate or a blanket on the blanket cylinder of the same printing unit. When the same color ink is used by the upper and lower applicator rollers from the plate position and from the blanket position simultaneously on the same printing unit, a "double bump" or double inking films or coating layers are applied to the substrate S during a single pass of the substrate through the printing unit. The tack of the two inks or coating

materials must be compatible for good transfer during the double bump. Moreover, the inking/coating apparatus 10 can be used for supplying ink or coating material to the blanket cylinder of a rotary offset web press, or to the blanket of a dedicated coating unit.

According to conventional bronzing techniques, a metallic (bronze) powder is applied off-line to previously printed substrate which produces a grainy, textured finish or appearance. The on-line application of bronze material by conventional flexographic or lithographic printing will only produce a smooth, continuous appearance. However, a grainy, textured finish is preferred for highest quality printing which, prior to the present invention, could only be produced by off-line methods.

Referring now to FIGURE 14 and FIGURE 15, metallic ink or coating material is applied on-line to the substrate S by simultaneous operation of the upper and lower applicator rollers 67R, 66 to produce an uneven surface finish having a bronze-like textured or grainy appearance. According to the simulated bronzing method of the present invention, the flexographic bronze ink is applied simultaneously to the plate and to the blanket by the dual cradle inking/coating apparatus 10 as shown in FIGURE 14. A resilient applicator roller 67R is mounted in the upper cradle 102, and an anilox applicator roller 66 is mounted on the lower cradle 100. The rollers are supplied from separate doctor blade reservoirs 70. The doctor blade reservoir 70 in the upper cradle position supplies bronze ink or coating material having relatively coarse, metallic particles 140 dispersed in aqueous or flexographic ink. The coarse particle ink or coating material is applied to the plate P by the resilient applicator roller 67R in the upper cradle position 102. At the same time, flexographic and/or bronze ink or coating material having relatively fine, metallic particles 142 is transferred to the blanket B by the anilox roller 66 which is mounted on the lower cradle 100.

The metering surfaces of the upper and lower applicator rollers have different cell sizes and volumetric capacities which

accommodate the coarse and fine metallic particles. For example, the anilox roller 111 mounted in the upper cradle position 102 which transfers the coarse metallic particles 140 preferably has a screen line count in the range of 100-300 lines per inch (39-118 lines per cm), and the metering surface of the anilox roller 66 mounted on the lower cradle 100 which transfers the relatively fine metallic particles 142 preferably has a screen line count in the range of 200-600 lines per inch (79-236 lines per cm).

After transfer from the plate to the blanket, the fine metallic particles 142 form a layer over the coarse metallic particles 140. As both bronze layers are offset onto the substrate S, the layer of fine metallic particles 142 is printed onto the substrate S with the top layer of coarse metallic particles 140 providing a textured, grainy appearance. The fine metallic particles 142 cover the substrate which would otherwise be visible in the gaps between the coarse metallic particles 140. The combination of the coarse particle layer over the fine particle layer thus provides a textured, bronzed-like finish and appearance.

Particulate materials other than metal can be used for producing a textured finish. For example, coarse and fine particles of metallized plastic (glitter), mica particles (pearlescent) and the like, can be substituted for the metallic particles for producing unlimited surface variations, appearances and effects. All of the particulate material, including the metallic particles, are preferably in solid, flat platelet form, and have a size dimension suitable for application by an anilox applicator roller. Other particulate or granular material, for example stone grit having irregular form and size, can be used to good advantage.

Solid metal particles in platelet form, which are good reflectors of light, are preferred for producing the bronzed-like appearance and effect. However, various textured finishes, which could have light-reflective properties, can be produced by using granular materials such as stone grit. Most commonly used metals

include copper, zinc and aluminum. Other ductile metals can be used, if desired. Moreover, the coarse and fine particles need not be made of the same particulate material. Various effects and textured appearances can be produced by utilizing diverse particulate materials for the coarse particles and the fine particles, respectively. Further, either fine or coarse particle ink or coating material can be printed from the upper cradle position, and either fine or coarse particle ink or coating material can be printed from the lower cradle position, depending on the special or surface finish that is desired.

It will be appreciated that the last printing unit 28 can be configured for additional inking/coating capabilities which include lithographic, waterless, aqueous and flexographic processes. Various substrate surface effects (for example double bump or triple bump inking/coating or bronzing) can be performed on the last printing unit. For triple bump inking/coating, the last printing unit 28 is equipped with an auxiliary in-line inking or coating apparatus 97 as shown in FIGURE 3 and FIGURE 4. The in-line inking or coating apparatus 97 allows the application of yet another film of ink or a protective or decorative layer of coating material over any freshly printed or coated surface effects or special treatments, thereby producing a triple bump. The triple bump is achieved by applying a third film of ink or layer of coating material over the freshly printed or coated double bump simultaneously while the substrate is on the impression cylinder of the last printing unit.

When the in-line inking/coating apparatus 97 is installed, it is necessary to remove the SUPER BLUE® flexible covering from the delivery cylinder 42, and it is also necessary to modify or convert the delivery cylinder 42 for inking/coating service by mounting a plate or blanket B on the delivery cylinder 42, as shown in FIGURE 3 and FIGURE 4. Packing material is placed under the plate or blanket B, thereby packing the plate or blanket B at the correct packed-to-print radial clearance so that ink or coating material will be printed or coated onto the freshly

printed substrate S as it transfers through the nip between the plate or blanket B on the converted delivery cylinder 42 and the last impression cylinder 36. According to this arrangement, a freshly printed or coated substrate is overprinted or overcoated with a third film or layer of ink or coating material simultaneously while a second film or layer of ink or coating material is being over-printed or over-coated on the last impression cylinder 36.

The auxiliary inking/coating apparatus 97 and the converted or modified delivery cylinder 42 are mounted on the delivery drive shaft 43. The inking/coating apparatus 97 includes an applicator roller, preferably an anilox applicator roller 97A, for supplying ink or coating material to a plate or blanket B on the modified or converted delivery cylinder 42. The in-line inking/coating apparatus 97 and the modified or converted delivery cylinder 42 are preferably constructed as described in U.S. Patent 5,176,077 to Howard W. DeMoore (co-inventor and assignee), which is hereby incorporated by reference. The in-line inking/coating apparatus 97 is manufactured and sold by Printing Research, Inc. of Dallas, Texas, U.S.A., under its trademark SUPER BLUE EZ COATER™.

After the delivery cylinder 42 has been modified or converted for inking/coating service, and because of the reduced nip clearance imposed by the plate or blanket B, the modified delivery cylinder 42 can no longer perform its original function of guiding and transferring the freshly printed or coated substrate. Instead, the modified or converted delivery cylinder 42 functions as a part of the inking/coating apparatus 97 by printing or coating a third down film of ink or layer of coating material onto the freshly printed or coated substrate as it is simultaneously printed or coated on the last impression cylinder 36. Moreover, the mutual tack between the second down ink film or coating layer and the third down ink film or coating layer causes the overprinted or overcoated substrate to cling to the plate or

blanket, thus opposing or resisting separation of the substrate from the plate or blanket.

To remedy this problem, a vacuum-assisted transfer apparatus 99 is mounted adjacent the modified or converted delivery cylinder 42 as shown in FIGURE 3 and FIGURE 4. Another purpose of the vacuum-assisted transfer apparatus 99 is to separate the freshly overprinted or overcoated triple bump substrate from the plate or blanket B as the substrate transfers through the nip. The vacuum-assisted transfer apparatus 99 produces a pressure differential across the freshly overprinted or overcoated substrate as it transfers through the nip, thus producing a separation force onto the substrate and providing a clean separation from the plate or blanket B.

The vacuum-assisted transfer apparatus 99 is preferably constructed as described in U.S. Patent Nos. 5,113,255; 5,127,329; 5,205,217; 5,228,391; 5,243,909; and 5,419,254, all to Howard W. DeMoore, co-inventor, which are incorporated herein by reference. The vacuum-assisted transfer apparatus 99 is manufactured and sold by Printing Research, Inc. of Dallas, Texas, U.S.A. under its trademark BACVAC™.

Although the present invention and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the present invention as defined by the appended claims.

What is claimed is:

1. A rotary offset printing press of the type including first and second printing units, the first printing unit comprising:

a plate cylinder having a flexographic printing plate mounted thereon;

a blanket cylinder having a blanket disposed in ink or coating transfer engagement with the flexographic printing plate for receiving aqueous or flexographic printing ink or coating material from the flexographic printing plate;

an impression cylinder disposed adjacent the blanket cylinder thereby forming a nip between the blanket and the impression cylinder whereby the aqueous or flexographic printing ink or coating material can be transferred from the blanket to a substrate as the substrate is transferred through the nip;

inking/coating apparatus movably coupled to the printing unit for movement to an on-impression operative position and to an off-impression retracted position;

the inking/coating apparatus including container means for containing a volume of aqueous or flexographic ink or coating material, and at least one applicator roller coupled to the container means for applying aqueous or flexographic ink or coating material to the flexographic printing plate or to the blanket when the inking/coating apparatus is in the on-impression operative position;

the container means having a partition dam dividing the container means thereby defining a first container region and a second container region;

the at least one applicator roller having first and second transfer surfaces and means separating the first and second transfer surfaces; and,

the first and second transfer surfaces of the at least one applicator roller being disposed within the first and second container regions for rolling contact with aqueous or

flexographic printing ink or coating material contained within the first and second container regions, respectively.

2. A rotary offset printing press as defined in claim 1, wherein:

said separating means is an annular seal element disposed on the applicator roller; and,

the partition element is disposed in sealing engagement against the annular seal element of the applicator roller.

3. A rotary offset printing press as defined in claim 1, wherein:

said container means is an open fountain pan;

said separating means is an annular groove intersecting the applicator roller thereby separating the first and second transfer surfaces; and,

the partition element is a separator plate mounted on the fountain pan between the first and second reservoir regions and disposed in the annular groove.

4. A rotary offset printing press as defined in claim 1, including sheet feeding means coupled to the first printing unit for consecutively feeding substrates in sheet form into the first printing unit.

5. A rotary offset printing press as defined in claim 1, including web feeding means coupled to the first printing unit for continuously feeding a substrate in continuous web form into the first printing unit.

6. A rotary offset printing press as defined in claim 1, wherein:

said container means is a fountain pan having first and second pan sections for containing first and second aqueous or flexographic inks or coating materials, respectively;

said applicator roller having first and second transfer surfaces and an annular groove separating said first and second transfer surfaces; and,

a pan roller having first and second transfer surfaces mounted for rotation in the first and second pan sections, respectively, for separately transferring aqueous or flexographic ink or coating material from the first and second pan sections to the first and second transfer surfaces of the applicator roller.

7. A rotary offset printing press as set forth in claim 1, wherein:

said container means is a sealed doctor blade head having first and second reservoir chambers, said partition dam being mounted on the doctor blade head and separating the first and second reservoir chambers;

the at least one applicator roller comprising an anilox transfer roller having first and second fluid metering transfer surfaces disposed for rolling contact with the aqueous or flexographic ink or coating material in the first and second reservoir chambers, respectively;

the separating means being a seal band formed on the applicator roller between the first and second transfer surfaces; and,

the partition dam being disposed in sealing engagement with the seal band in the coupled position.

8. A rotary offset printing press as defined in claim 1, wherein the inking/coating apparatus comprises:

first cradle means for supporting a first applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

second cradle means for supporting a second applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

a first applicator roller mounted for rotation on the first cradle means, the first applicator roller having first and second transfer surfaces and a seal band separating the first and second transfer surfaces;

a second applicator roller mounted for rotation on the second cradle means, the second applicator roller having first and second transfer surfaces and means separating the first and second transfer surfaces;

first reservoir means for containing a volume of ink or coating material, the first reservoir means having first and second reservoir chambers and a partition element separating the first and second reservoir chambers of th4e first reservior means;

second reservoir means for containing a volume of ink or coating material, the second reservoir means having first and second reservoir chambers and a partition element separating the first and second reservoir chambers of the second reservoir means;

the first and second reservoir means being coupled to the first and second applicator rollers, respectively, the first and second transfer surfaces of the first applicator roller being disposed for rolling contact with ink or coating material in the first and second reservoir chambers, respectively, of the first reservoir means and the first partition seal element being disposed in sealing engagement against the separating means of the first applicator roller in the coupled position; and,

the first and second transfer surfaces of the second applicator roller being disposed for rolling contact with ink or coating material in the first and second reservoir chambers, respectively, of the second reservoir means and the partition element of the second reservoir means being disposed in

sealing engagement with the separating means of the second applicator roller in the coupled position.

9. A rotary offset printing press as defined in claim 1, wherein:

the at least one applicator roller is an anilox roller having first and second fluid metering transfer surfaces; and,

the volumetric capacity of the first transfer surface being different from the volumetric capacity of the second transfer surface.

10. A rotary offset printing press as defined in claim 1, wherein the inking/coating apparatus comprises:

cradle means;

the at least one applicator roller being mounted for rotation on the cradle means, the applicator roller having first and second transfer surfaces and means separating the first and second metering transfer surfaces;

reservoir means for containing a volume of ink or coating material, the reservoir means having first and second reservoir chambers and a partition element separating the first and second reservoir chambers;

the at least one applicator roller being coupled to the reservoir means with the first and second fluid metering transfer surfaces being disposed for rolling contact with the ink or coating material in the first and second reservoir chambers, respectively, and the partition element being disposed in sealing engagement with separating means of the applicator roller in the coupled position; and,

the volumetric capacity of the first transfer surface being different from the volumetric capacity of the second transfer surface.

11. A rotary offset printing press as set forth in claim 1, wherein the inking/coating apparatus comprises:

a fountain pan for containing a volume of liquid ink or coating material;

an applicator roller having a metering surface; and,

a pan roller mounted for rotation in the fountain pan and coupled to the applicator roller for transferring ink or coating material from the fountain pan to the applicator roller.

12. A rotary offset printing press as defined in claim 1, further including:

a transfer drum coupled in substrate transfer relation with the impression cylinder of the first printing unit and in substrate transfer relation with the second printing unit;

a first dryer mounted adjacent the impression cylinder of the first printing unit for discharging heated air onto a freshly printed or coated substrate while the substrate is in contact with the impression cylinder of the first printing unit;

a second dryer mounted adjacent the transfer drum for discharging heated air onto a freshly printed or coated substrate after it has been transferred from the impression cylinder of the first printing unit and while it is in contact with the transfer cylinder; and,

a third dryer disposed adjacent the second printing unit for discharging heated air onto a freshly printed or coated substrate after it has been transferred from the transfer drum and before it is printed or otherwise processed on the second printing unit.

13. A rotary offset printing press as defined in claim 1, wherein the means for applying ink or coating material comprises:

first cradle means;

a first reservoir or fountain means mounted on the first cradle means for containing ink or coating material;

a first applicator roller mounted for rotation on the first cradle means and disposed for rolling contact with ink or coating material in the first reservoir or fountain means, the first applicator roller being engagable with a printing plate on the plate cylinder;

second cradle means;

a second reservoir or fountain means mounted on the second cradle means for receiving ink or coating material; and,

a second applicator roller mounted for rotation on the second cradle means and disposed for rolling contact with ink or coating material in the second reservoir or fountain means, the second applicator roller being engagable with a plate or blanket mounted on the blanket cylinder in the operative position.

14. A rotary offset printing press as defined in claim 1, wherein the inking/coating apparatus is pivotally mounted on the printing unit in a position in which the nip contact point between said at least one applicator roller and a blanket or plate is offset with respect to a radius line projecting through the center of the plate cylinder or blanket cylinder to the axis of rotation of the printing/coating unit.

15. A rotary offset printing press as defined in claim 1, wherein:

said at least one applicator roller having first and second transfer surfaces and a seal band surface disposed between and separating the first and second transfer surfaces;

the reservoir means having a chamber and a partition member disposed within the chamber, the partition member dividing the chamber thereby defining a first reservoir chamber region and a second reservoir chamber region; and,

the partition member surface being disposed in sealing engagement against the seal band of the applicator roller.

16. A rotary offset printing press as defined in claim 1, wherein the inking/coating apparatus comprises:

first cradle means for supporting a first applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

second cradle means for supporting a second applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

a first applicator roller mounted for rotation on the first cradle means, the first applicator roller having first and second fluid metering transfer surfaces and a separation band separating the first and second fluid metering transfer surfaces;

a second applicator roller mounted for rotation on the second cradle means, the second applicator roller having first and second fluid metering transfer surfaces and a separation band separating the first and second metering transfer surfaces;

first reservoir means for containing a volume of ink or coating material, the first reservoir means having first and second reservoir chambers and a first partition element separating the first and second reservoir chambers;

second reservoir means for containing a volume of ink or coating material, the second reservoir means having first and second reservoir chambers and a second partition seal element separating the first and second reservoir chambers of the second reservoir means;

the first and second fluid metering transfer surfaces of the first applicator roller being disposed for rolling contact with ink or coating material in the first and second reservoir chambers, respectively, of the first reservoir means and the first partition element being disposed in sealing engagement against the separation band of the first applicator roller in the coupled position; and,

the first and second fluid metering transfer surfaces of the second applicator roller being disposed for rolling contact with ink or coating material in the first and

second reservoir chambers, respectively, of the second reservoir means and the second partition element of the second reservoir means being disposed in sealing engagement with the separation band of the second applicator roller in the coupled position.

17. A printing press as defined in claim 1, wherein the inking/coating apparatus comprises:

first cradle means for supporting a first applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

second cradle means for supporting a second applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

first reservoir means mounted on the first cradle means, said first reservoir means having a reservoir chamber for containing a volume of ink or coating material;

second reservoir means mounted on the second cradle means, said second reservoir means having a reservoir chamber for containing a volume of ink or coating material;

a first applicator roller mounted for rotation on the first cradle means, the first applicator roller having a fluid metering transfer surface;

a second applicator roller mounted for rotation on the second cradle means, the second applicator roller having a fluid metering transfer surface;

the first and second applicator rollers being coupled to the first and second reservoir means, respectively, the fluid metering transfer surfaces of the first and second applicator rollers being disposed for rolling contact with ink or coating material in the reservoir chambers of the first and second reservoir means, respectively; and,

the volumetric capacity of the fluid metering surface of the first applicator roller being different from the volumetric capacity of the fluid metering surface of the second applicator roller.

18. A printing press as defined in claim 1, wherein the means for applying ink or coating material comprises:

cradle means;

an applicator roller mounted for rotation on the cradle means, the applicator roller having first and second surfaces and a seal band separating the first and second transfer surfaces;

reservoir means for containing a volume of ink or coating material, the reservoir means having first and second reservoir chambers and a partition element separating the first and second reservoir chambers;

the applicator roller being coupled to the reservoir means with the first and second transfer surfaces being disposed for rolling contact with the ink or coating material in the first and second reservoir chambers, respectively, and the partition element being disposed in sealing engagement against the seal band of the applicator roller in the coupled position; and,

the volumetric capacity of the first fluid metering transfer surface being different from the volumetric capacity of the second fluid metering transfer surface.

19. A rotary offset printing press as defined in claim 1, further including:

a supply container for containing a volume of liquid ink or coating material;

circulation means coupled between the supply reservoir and the inking/coating apparatus for inducing the flow of liquid ink or coating material from said supply container to the inking/coating apparatus and for returning liquid ink or coating material from the inking/coating apparatus to the supply container; and,

heat exchanger means coupled to the circulation means for maintaining the temperature of the liquid ink or coating material within a predetermined temperature range.

20. A printing press as defined in claim 1, wherein the inking/coating apparatus is pivotally mounted on the first printing unit in a position in which the nip contact point between the applicator roller and a blanket or plate is offset with respect to a radius line projecting through the center of the plate cylinder or blanket cylinder to the axis of rotation of the printing/coating unit.

21. A printing press as defined in claim 1, including:

a dryer mounted on the first printing unit for discharging heated air onto a freshly printed or coated substrate before the freshly printed or coated substrate is subsequently printed, coated or otherwise processed on the second printing unit.

22. A printing press as defined in claim 21, wherein:

the dryer is mounted adjacent the impression cylinder of the first printing unit for discharging heated air onto a freshly printed or coated substrate while the substrate is in contact with said impression cylinder.

23. A printing press as defined in claim 1, further including:

a substrate transfer apparatus disposed in an interunit position on the press and coupled in substrate transfer relation with the impression cylinder of the first printing unit;

an interunit dryer disposed adjacent the substrate transfer apparatus for discharging heated air onto a freshly printed or coated substrate after it has been transferred from the first printing unit and while it is in contact with the substrate transfer apparatus.

24. A printing press as defined in claim 1, comprising:

a dryer mounted on the first printing unit for discharging heated air onto a freshly printed or coated substrate; and,

an extractor coupled to the dryer for extracting hot air and moisture vapors from an exposure zone between the dryer and the freshly printed or coated substrate.

"RETRACTABLE PRINTING/COATING UNIT OPERABLE ON THE PLATE AND BLANKET CYLINDERS SIMULTANEOUSLY FROM THE DAMPENER SIDE OF THE FIRST PRINTING UNIT OR ANY CONSECUTIVE PRINTING UNIT OF ANY ROTARY OFFSET PRINTING PRESS"

Abstract of the Disclosure

A retractable in-line inking/coating apparatus can apply either spot or overall inking/coating material to a plate and/or a blanket on the first printing unit or on any consecutive printing unit of any rotary offset printing press. The inking/coating apparatus is pivotally mounted within the conventional dampener space of any lithographic printing unit. The aqueous component of the flexographic printing ink or aqueous coating material is evaporated and dried by high velocity, hot air dryers and high performance heat and moisture extractors so that the aqueous or flexographic ink or coating material on a freshly printed or coated sheet is dry and can be dry-trapped on the next printing unit. The inking/coating apparatus includes dual cradles that support first and second applicator rollers so that the inking/coating apparatus can apply a double bump of aqueous/flexographic or UV-curable printing ink or coating material to a plate on the plate cylinder, while simultaneously applying aqueous, flexographic or UV-curable printing ink or coating material to a plate or a blanket on the blanket cylinder, and thereafter onto a sheet as the sheet is transferred through the nip between the blanket cylinder and the impression cylinder. A triple bump is printed or coated on the last printing unit with the aid of an impression cylinder inking/coating unit.

* * * * * * *

Attorney Docket No.

B6038D

SMALL ENTITY
INDEPENDENT INVENTOR

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

DECLARATION CLAIMING SMALL ENTITY STATUS
(37 C.F.R. §1.9(f) and §1.27 (b)) - INDEPENDENT INVENTOR

I, HOWARD W. DEMOORE, hereby declare that I qualify as an independent inventor as defined in 37 C.F.R. §1.9(c) for the purposes of paying reduced fees under Section 41(a) and (b) of Title 35, United States Code, to the U.S. Patent and Trademark Office with regard to the invention entitled

"RETRACTABLE PRINTING/COATING UNIT OPERABLE ON THE PLATE AND BLANKET CYLINDERS SIMULTANEOUSLY FROM THE DAMPENER SIDE OF THE FIRST PRINTING UNIT OR ANY CONSECUTIVE PRINTING UNIT OF ANY ROTARY OFFSET PRINTING PRESS",

__X__ in the application filed herewith.

____ in U.S. application Serial No. _____ filed _____.

____ patent No. _____ __, issued _____.

I have not assigned, granted, conveyed or licensed, and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 C.F.R. §1.9(c) if that person had made the invention, or to any concern which would not qualify as a small busines concern under 37 C.F.R. §1.9(d) or a non-profit organization under 37 C.F.R. §1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under any obligation under contract or law to assign, grant, convey, or license any rights in the invention is identified below:

____ no such person, concern or organization exists.

X any such person, concern or organization is identified below, if applicable:

Full Name Printing Research, Inc.

Address 10954 Shady Trail

Dallas, Texas 75220

____ individual X small business concern

____ nonprofit organization

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate pursuant to 37 C.F.R. §1.28(b).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Printed Name of Inventor: Howard W. DeMoore

Date: 9/11/96 Howard W. DeMoore

Signature of Inventor

DTC 11976-0181DOCS:86048.SE3

Attorney Docket No.
B6038D

SMALL ENTITY
INDEPENDENT INVENTOR

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

DECLARATION CLAIMING SMALL ENTITY STATUS
(37 C.F.R. §1.9(f) and §1.27 (b)) - INDEPENDENT INVENTOR

I, RONALD M. RENDLEMAN, hereby declare that I qualify as an independent inventor as defined in 37 C.F.R. §1.9(c) for the purposes of paying reduced fees under Section 41(a) and (b) of Title 35, United States Code, to the U.S. Patent and Trademark Office with regard to the invention entitled

"RETRACTABLE PRINTING/COATING UNIT OPERABLE ON THE PLATE AND BLANKET CYLINDERS SIMULTANEOUSLY FROM THE DAMPENER SIDE OF THE FIRST PRINTING UNIT OR ANY CONSECUTIVE PRINTING UNIT OF ANY ROTARY OFFSET PRINTING PRESS",

_X_ in the application filed herewith.

____ in U.S. application Serial No. _____ filed _____.

____ patent No. _____, issued _____.

I have not assigned, granted, conveyed or licensed, and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 C.F.R. §1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 C.F.R. §1.9(d) or a non-profit organization under 37 C.F.R. §1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under any obligation under contract or law to assign, grant, convey, or license any rights in the invention is identified below:

____ no such person, concern or organization exists.

__X__ any such person, concern or organization is identified below, if applicable:

Full Name Howard W. DeMoore

Address 10954 Shady Trail

Dallas, Texas 75220

__X__ individual ____ small business concern

____ nonprofit organization

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate pursuant to 37 C.F.R. §1.28(b).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Printed Name of Inventor: Ronald M. Rendleman

Date: 9.11.95

Signature of Inventor

Attorney Docket No.
B6038D

SMALL ENTITY
INDEPENDENT INVENTOR

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

DECLARATION CLAIMING SMALL ENTITY STATUS
(37 C.F.R. §1.9(f) and §1.27 (b)) - INDEPENDENT INVENTOR

I, JOHN W. BIRD, hereby declare that I qualify as an independent inventor as defined in 37 C.F.R. §1.9(c) for the purposes of paying reduced fees under Section 41(a) and (b) of Title 35, United States Code, to the U.S. Patent and Trademark Office with regard to the invention entitled

"RETRACTABLE PRINTING/COATING UNIT OPERABLE ON THE PLATE AND BLANKET CYLINDERS SIMULTANEOUSLY FROM THE DAMPENER SIDE OF THE FIRST PRINTING UNIT OR ANY CONSECUTIVE PRINTING UNIT OF ANY ROTARY OFFSET PRINTING PRESS",

X in the application filed herewith.

____ in U.S. application Serial No. _____ filed _____.

____ Patent No. _____, issued _____.

I have not assigned, granted, conveyed or licensed, and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 C.F.R. §1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 C.F.R. §1.9(d) or a non-profit organization under 37 C.F.R. §1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under any obligation under contract or law to assign, grant, convey, or license any rights in the invention is identified below:

____ no such person, concern or organization exists.

X any such person, concern or organization is identified below, if applicable:

Full Name Howard W. DeMoore

Address 10954 Shady Trail

Dallas, Texas 75220

X individual ____ small business concern

____ nonprofit organization

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate pursuant to 37 C.F.R. §1.28(b).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Printed Name of Inventor: John W. Bird

Date: 9.12.95

Signature of Inventor

Attorney Docket No.
B6038D

SMALL ENTITY
SMALL BUSINESS CONCERN

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS (37 C.F.R. §1.9(f) and §1.27(c))-- SMALL BUSINESS CONCERN

I, HOWARD W. DEMOORE

hereby declare that I am

___ the owner of the small business concern identified below:

X an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF CONCERN Printing Research, Inc.

ADDRESS OF CONCERN 10954 Shady Trail

Dallas, Texas 75220

I hereby declare that the above-identified small business concern qualifies as a small business concern as defined in 13 C.F.R. §121.3-18, and reproduced in 37 C.F.R. §1.9(d), for purposes of paying reduced fees under Section 41(a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when, either directly or indirectly, one concern controls or has the power to control the other, or a third-party or parties controls or has the power to control both.

I hereby declare that rights under license, contract or law have been acquired by or conveyed to and remain with the small business concern identified above with regard to the invention entitled

"RETRACTABLE PRINTING/COATING UNIT OPERABLE ON THE PLATE AND BLANKET CYLINDERS SIMULTANEOUSLY FROM THE DAMPENER SIDE OF THE FIRST PRINTING UNIT OR ANY CONSECUTIVE PRINTING UNIT OF ANY ROTARY OFFSET PRINTING PRESS",

by inventors Howard W. DeMoore, Ronald M. Rendleman and John W. Bird

as described in

X the specification filed herewith.

___ the specification filed _____ under Serial No. _____.

___ Patent No. _____, issued _____.

If the rights held by the above-identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed below and no rights to the invention are held by any person, other than the inventor, who could not qualify as a small business concern under 37 C.F.R. §1.9(d) or by any concern which would not qualify as a small business concern under 37 C.F.R. §1.9(d) or a nonprofit organization under 37 C.F.R. §1.9(e).

X no such person, concern or organization exists

____ any such person, concern or organization is identified below, if applicable:

Full Name_____

Address_____

_____

____ individual ____ small business concern

____ nonprofit organization

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small business entity is no longer appropriate. (37 C.F.R. §1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these

statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

TYPED NAME OF PERSON SIGNING Howard W. DeMoore

TITLE OF PERSON OTHER THAN OWNER President and Chairman of the Board

Date: 9/11/95

Howard W DeMoore
Signature

DTC:11875:01:1:DOCS:86038.V5

PATENT

JOINT
UTILITY

Attorney Docket
No. B6038D

DECLARATION AND POWER OF ATTORNEY

We, HOWARD W. DEMOORE, RONALD M. RENDLEMAN and JOHN W. BIRD, joint inventors herein, hereby declare that.

Our residence, post office address and citizenship are as stated below next to our names.

We believe that we are the original, first and joint inventors of the subject matter which is claimed and for which a patent is sought on the invention entitled

"RETRACTABLE PRINTING/COATING UNIT OPERABLE ON THE PLATE AND BLANKET CYLINDERS SIMULTANEOUSLY FROM THE DAMPENER SIDE OF THE FIRST PRINTING UNIT OR ANY CONSECUTIVE PRINTING UNIT OF ANY ROTARY OFFSET PRINTING PRESS",

the specification of which is attached hereto.

We hereby state that we have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to in this declaration.

We each individually acknowledge the duty to disclose to the U.S. Patent Office all information known to me that is material to the patentability of any claim in accordance with Title 37, Code of Federal Regulations, §1.56, and which is material to the examination of this application, namely, information where there is a substantial likelihood that a reasonable examiner would consider it important in deciding whether to allow the application to issue as a patent.

We hereby claim foreign priority benefits under Title 35, United States Code §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Country	Application No.	Filing Date (day, month, year)
- NONE -		

We hereby claim the benefit under Title 35, United States Code §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code §112, we acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

U.S. Serial No.	U.S. Filing Date	Status
08/435,798	May 4, 1995	Pending

We hereby appoint DENNIS T. GRIGGS, Registration No. 27,790, of the firm of AKIN, GUMP, STRAUSS, HAUER & FELD, L.L.P., our attorney to prosecute this application and to transact all business in the U.S. Patent and Trademark Office connected therewith. We request that all correspondence be addressed to:

Dennis T. Griggs
Akin, Gump, Strauss, Hauer & Feld, L.L.P.
1700 Pacific Avenue, Suite 4100
Dallas, Texas 75201-4618

Phone: 214/969-2747

We hereby declare that all statements made herein of our own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of this application or any patent issued thereon.

Full name of first joint Inventor: Howard W. DeMoore

Residence: Dallas, Texas

Citizenship: U.S.

Post Office Address: 10954 Shady Trail
Dallas, Texas 75220

Date: 9/11/95

Howard W. DeMoore

Howard W. DeMoore

Full name of second joint Inventor: Ronald M. Rendleman

Residence: Dallas, Texas

Citizenship: U.S.

Post Office Address: 4331 Royal Ridge
Dallas, Texas 75229

Date: 7-11-95

Ronald M. Rendleman

Full name of third joint Inventor: John W. Bird

Residence: Carrollton, Texas

Citizenship: United Kingdom

Post Office Address: 1514 Iroquois Circle
Carrollton, Texas 75007

Date: 7 11 95

John W. Bird

Full name of
second joint Inventor: Ronald M. Rendleman

Residence: Dallas, Texas

Citizenship: U.S.

Post Office Address: 4331 Royal Ridge
Dallas, Texas 75229

Date: 7-11-95

Ronald M. Rendleman

Full name of
third joint Inventor: John W. Bird

Residence: Carrollton, Texas

Citizenship: United Kingdom

Post Office Address: 1514 Iroquois Circle
Carrollton, Texas 75007

Date: 7-11-95

John W. Bird

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 1



FIG. 2

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 3

B6038 08/538274

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 4

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 5

B6038

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 6



FIG. 7

B6038

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 8



FIG. 9

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 10



FIG. 11



FIG. 12



FIG. 13

B6038

[redacted] 08/538274

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 14



FIG. 15

B6038

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 16



FIG. 17

B6038

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 18

UEXKÜLL & STOLBERG
PATENTANWÄLTE

BESELERSTRASSE 4
D - 22607 HAMBURG

EUROPEAN PATENT ATTORNEYS

DR. ULRICH GRAF STOLBERG
DIPL.-ING. JÜRGEN SUCHANTKE
DIPL.-ING. ARNULF HUBER
DR. ALLARD von KAMEKE
DIPL.-BIOL. INGEBORG VOELKER
DR. PETER FRANCK
DR. GEORG BOTH
DR. ULRICH-MARIA GROSS
DR. HELMUT van HEESCH
DIPL.-BIOL. JOACHIM STÜRKEN
DR. JOHANNES AHME
DR. HEINZ-PETER MUTH

TELEFON: (040) 899 6540
FAX: (040) 899 654 88
100763.733@COMPUSERVE.COM

10.10.1996
P 44214 Hu

European Patent Office
Erhardtstraße 27

80331 München



Application No.: 96250220.9

Applicant : DeMoore, Howard W.

Please find the following documents enclosed:

- 3 copies of the specification, claims, abstract and drawings in EPO format.

Further, please note that applicant's family name is DeMoore, the given names being Howard W.

A. Huber
(Association No. 1)

1x DATINTEX
1x Search file
1x Main file

W BORIŃSKI 05. 11. 96

96250220.9

0031576 05110101

Field of the Invention

This invention relates generally to sheet-fed or web-fed, rotary offset lithographic printing presses, and more particularly, to a new and improved inking/coating apparatus for the in-line application of aqueous or flexographic printing inks, primer or protective/decorative coatings applied simultaneously to the plate and blanket of the first or any consecutive printing unit of any lithographic printing press.

Background of the Invention

Conventional sheet-fed, rotary offset printing presses typically include one or more printing units through which individual sheets are fed and printed. After the last printing unit, freshly printed sheets are transferred by a delivery conveyor to the delivery end of the press where the freshly printed and/or coated sheets are collected and stacked uniformly. In a typical sheet-fed, rotary offset printing press such as the Heidelberg Speedmaster line of presses, the delivery conveyor includes a pair of endless chains carrying gripper bars with

gripper fingers which grip and pull freshly printed sheets from the last impression cylinder and convey the sheets to the sheet delivery stacker.

Since the inks used with sheet fed rotary offset printing presses are typically wet and tacky, special precautions must be taken to prevent marking and smearing of the freshly printed or coated sheets as the sheets are transferred from one printing unit to another. The printed ink on the surface of the sheet dries relatively slowly and is easily smeared during subsequent transfer between printing units. Marking, smearing and smudging can be prevented by a vacuum assisted sheet transfer apparatus as described in the following U.S. Patents: 5,113,255; 5,127,329; 5,205,217; 5,228,391; 5,243,909; and 5,419,254, all to Howard W. DeMoore, co-inventor, and manufactured and sold by Printing Research, Inc. of Dallas, Texas, U.S.A. under its trademark BACVAC™.

In some printing jobs, offsetting is prevented by applying a protective and/or decorative coating material over all or a portion of the freshly printed sheets. Some coatings are formed of a UV-curable or water-dispersed resin applied as a liquid solution over the freshly printed sheets to protect the ink from offsetting or set-off and improve the appearance of the freshly printed sheets. Such coatings are particularly desirable when decorative or protective finishes are applied in the printing of posters, record jackets, brochures, magazines, folding cartons and the like.

Description of the Prior Art

Various arrangements have been made for applying the coating as an in-line printing operation by using the last printing unit of the press as the coating application unit. For example, U.S. Patents 4,270,483; 4,685,414; and 4,779,557 disclose coating apparatus which can be moved into position to permit the blanket cylinder of the last printing unit of a printing press to be used to apply a coating material over the freshly printed

sheets. In U.S. Patent 4,841,903 (Bird) there are disclosed coating apparatus which can be selectively moved between the plate cylinder or the blanket cylinder of the last printing unit of the press so the last printing unit can only be used for coating purposes. However, when coating apparatus of these types are being used, the last printing unit cannot be used to print ink to the sheets, but rather can only be used for the coating operation. Thus, while coating with this type of in-line coating apparatus, the printing press loses the capability of printing on the last printing unit as it is converted to a coating unit.

The coater of U.S. Patent 5,107,790 (Sliker et al) is retractable along an inclined rail for extending and retracting a coater head into engagement with a blanket on the blanket cylinder. Because of its size, the rail-retractable coater can only be installed between the last printing unit of the press and the delivery sheet stacker, and cannot be used for interunit coating. The coater of U.S. Patent 4,615,293 (Jahn) provides two separate, independent coaters located on the dampener side of a converted printing unit for applying lacquer to a plate and to a rubber blanket. Consequently, although a plate and blanket are provided, the coating unit of Jahn's press is restricted to a dedicated coating operation only.

Proposals have been made for overcoming the loss of a printing unit when in-line coating is used, for example as set forth in U.S. Patent 5,176,077 to Howard W. DeMoore (co-inventor and assignee), which discloses a coating apparatus having an applicator roller positioned to apply the coating material to the freshly printed sheet while the sheet is still on the last impression cylinder of the press. This allows the last printing unit to print and coat simultaneously, so that no loss of printing unit capability results.

Some conventional coaters are rail-mounted and occupy a large amount of press space and reduce access to the press. Elaborate equipment is needed for retracting such coaters from the

operative coating position to the inoperative position, which reduces access to the printing unit.

Accordingly, there is a need for an in-line inking/coating apparatus which does not result in the loss of a printing unit, does not extend the length of the press, and which can print and coat aqueous and flexographic inks and coating materials simultaneously onto the plate and blanket on any lithographic printing unit of any lithographic printing press, including the first printing unit.

Objects of the Invention

Accordingly, a general object of the present invention is to provide improved inking/coating apparatus which is capable of selectively applying ink or coating material to a plate on a plate cylinder or ink or coating material to a plate or blanket on a blanket cylinder.

A specific object of the present invention is to provide improved inking/coating apparatus of the character described which is extendable into inking/coating engagement with either a plate on a plate cylinder or to a plate or blanket on a blanket cylinder.

A related object of the present invention is to provide improved inking/coating apparatus of the character described which is capable of being mounted on any lithographic printing unit of the press and does not interfere with operator access to the plate cylinder, blanket cylinder, or adjacent printing units.

Another object of the present invention is to provide improved inking/coating apparatus of the character described, which can be moved from an operative inking/coating engagement position adjacent to a plate cylinder or a blanket cylinder to a non-operative, retracted position.

Still another object of the present invention is to provide improved inking/coating apparatus of the character described, which can be used for applying aqueous, flexographic and ultra-violet curable inks and/or coatings in combination with

lithographic, flexographic and waterless printing processes on any rotary offset printing press.

A related object of the present invention is to provide improved inking/coating apparatus of the character described, which is capable of applying aqueous or flexographic ink or coating material on one printing unit, for example the first printing unit, and drying the ink or coating material before it is printed or coated on the next printing unit so that it can be overprinted or overcoated immediately on the next printing unit with waterless, aqueous, flexographic or lithographic inks or coating materials.

Yet another object of the present invention is to provide improved inking/coating apparatus for use on a multiple color rotary offset printing press that can apply ink or coating material separately and/or simultaneously to the plate and/or blanket of a printing unit of the press from a single operative position, and from a single inking/coating apparatus.

A related object of the present invention is to provide improved inking/coating apparatus of the character described, in which virtually no printing unit adjustment or alteration is required when the inking/coating apparatus is converted from plate to blanket printing or coating and vice versa.

Another object of the present invention is to provide improved inking/coating apparatus that can be operably mounted in the dampener space of any lithographic printing unit for inking/coating engagement with either a plate on a plate cylinder or a plate or blanket on a blanket cylinder, and which does not interfere with operator movement or activities in the interunit space between printing units.

Summary of the Invention

The foregoing objects are achieved by a retractable, in-line inking/coating apparatus which is mounted on the dampener side of any printing unit of a rotary offset press for movement between an operative (on-impression) inking/coating position and

a retracted, disengaged (off-impression) position. The inking/coating apparatus includes an applicator roller which is movable into and out of engagement with a plate on a plate cylinder or a blanket on a blanket cylinder. The inking/coating applicator head is pivotally coupled to a printing unit by pivot pins which are mounted on the press side frames in the traditional dampener space of the printing unit in parallel alignment with the plate cylinder and the blanket cylinder. This dampener space mounting arrangement allows the inking/coating unit to be installed between any adjacent printing units on the press.

In the preferred embodiment, the applicator head includes vertically spaced pairs of cradle members with one cradle pair being adapted for supporting an inking/coating applicator roller in alignment with a plate cylinder, and the other cradle pair supporting an inking/coating applicator roller in alignment with the blanket cylinder, respectively, when the applicator head is in the operative position. Because of the pivotal support provided by the pivot pins, the applicator head can be extended and retracted within the limited space available in the traditional dampener space, without restricting operator access to the printing unit cylinders and without causing a printing unit to lose its printing capability.

When the inking/coating apparatus is used in combination with a flexographic printing plate and aqueous or flexographic ink or coating material, the water component of the aqueous or flexographic ink or coating material on the freshly printed or coated sheet is evaporated and dried by a high velocity, hot air interunit dryer and a high volume heat and moisture extractor assembly so that the freshly printed ink or coating material is dry before the sheet is printed or coated on the next printing unit. This quick drying process permits a base layer or film of ink, for example opaque white or metallic (gold, silver or other metallics) ink to be printed on the first printing unit, and then overprinted on the next printing unit without back-trapping or dot gain.

The construction and operation of the present invention will be understood from the following detailed description taken in conjunction with the accompanying drawings which disclose, by way of example, the principles and advantages of the present invention.

Brief Description of the Drawings

FIGURE 1 is a perspective view of a sheet fed, rotary offset printing press having inking/coating apparatus embodying the present invention;

FIGURE 2 is a simplified perspective view of the single head, dual cradle inking/coating apparatus of the present invention;

FIGURE 3 is a schematic side elevational view of the printing press of Figure 1 having single head, dual cradle inking/coating apparatus installed in the traditional dampener position of the first, second and last printing units;

FIGURE 4 is a simplified side elevational view showing the single head, dual cradle inking/coating apparatus in the operative inking/coating position for simultaneously printing on the printing plate and blanket on the fourth printing unit;

FIGURE 5 is a simplified side elevational view showing the single head, dual cradle inking/coating apparatus in the operative position for spot or overall inking or coating on the blanket of the first printing unit, and showing the dual cradle inking/coating apparatus in the operative position for spot or overall inking or coating on the printing plate of the second printing unit;

FIGURE 6 is a simplified side elevational view of the single head, dual cradle inking/coating apparatus of FIGURE 4 and FIGURE 5, partially broken away, showing the single head, dual cradle inking/coating apparatus in the operative coating position and having a sealed doctor blade reservoir assembly for spot or overall coating on the blanket;

FIGURE 7 is a schematic view showing a heat exchanger and pump assembly connected to the single head, dual cradle inking/coating apparatus for circulating temperature controlled ink or coating material to the inking/coating apparatus;

FIGURE 8 is a side elevational view, partially broken away, and similar to FIGURE 6 which illustrates an alternative coating head arrangement;

FIGURE 9 is a simplified elevational view of a printing unit which illustrates pivotal coupling of the inking/coating apparatus on the printing unit side frame members;

FIGURE 10 is a view similar to FIGURE 2 in which a pair of split applicator rollers are mounted in the upper cradle and lower cradle, respectively;

FIGURE 11 is a side elevational view of a split applicator roller;

FIGURE 12 is a perspective view of a doctor blade reservoir which is centrally partitioned by a seal element;

FIGURE 13 is a sectional view showing sealing engagement of the split applicator roller against the partition seal element of FIGURE 12;

FIGURE 14 is a view similar to FIGURE 8 which illustrates an alternative inking/coating embodiment;

FIGURE 15 is a simplified side elevational view of a substrate which has a bronzed-like finish which is applied by simultaneous operation of the dual applicator roller embodiment of FIGURE 14;

FIGURE 16 is a side elevational view, partly in section, of a pan roller having separate transfer surfaces mounted on a split fountain pan;

FIGURE 17 is a simplified side elevational view of the dual cradle inking/coating apparatus, partially broken away, which illustrates an alternative inking/coating head apparatus featuring a single doctor blade assembly, anilox applicator roller mounted on the lower cradle; and

FIGURE 18 is a side elevational view, partly in section, of a single doctor blade anilox applicator roller assembly having separate transfer surfaces, and a split fountain pan having separate fountain compartments, with the separate fountain compartments being supplied with different inks or coating materials from separate off-press sources.

Detailed Description of the Preferred Embodiments

As used herein, the term "processed" refers to printing and coating methods which can be applied to either side of a substrate, including the application of lithographic, waterless, UV-curable, aqueous and flexographic inks and/or coatings. The term "substrate" refers to sheet and web material. Also, as used herein, the term "waterless printing plate" refers to a printing plate having image areas and non-image areas which are oleophilic and oleophobic, respectively. "Waterless printing ink" refers to an oil-based ink which does not contain a significant aqueous component. "Flexographic plate" refers to a flexible printing plate having a relief surface which is wettable by flexographic ink or coating material. "Flexographic printing ink or coating material" refers to an ink or coating material having a base constituent of either water, solvent or UV-curable liquid. "UV-curable lithographic printing ink and coating material" refers to oil-based printing inks and coating materials that can be cured (dried) photomechanically by exposure to ultraviolet radiation, and that have a semi-paste or gel-like consistency. "Aqueous printing ink or coating material" refers to an ink or coating material that predominantly contains water as a solvent, diluent or vehicle. A "relief plate" refers to a printing plate having image areas which are raised relative to non-image areas which are recessed.

As shown in the exemplary drawings, the present invention is embodied in a new and improved in-line inking/coating apparatus, herein generally designated 10, for applying aqueous, flexographic or UV-curable inks or protective and/or decorative

coatings to sheets or webs printed in a sheet-fed or web-fed, rotary offset printing press, herein generally designated 12. In this instance, as shown in FIGURE 1, the inking/coating apparatus 10 is installed in a four unit rotary offset printing press 12, such as that manufactured by Heidelberger Druckmaschinen AG of Germany under its designation Heidelberg Speedmaster SM102 (40", 102cm).

The press 12 includes a press frame 14 coupled at one end, herein the right end, to a sheet feeder 16 from which sheets, herein designated S, are individually and sequentially fed into the press, and at the opposite end, with a sheet delivery stacker 20 in which the freshly printed sheets are collected and stacked. Interposed between the sheet feeder 16 and the sheet delivery stacker 20 are four substantially identical sheet printing units 22, 24, 26 and 28 which can print four different colors onto the sheets as they are transferred through the press 12. The printing units are housed within printing towers T1, T2, T3 and T4 formed by side frame members 14, 15. Each printing tower has a delivery side 25 and a dampener side 27. A dampener space 29 is partially enclosed by the side frames on the dampener side of the printing unit.

As illustrated, the printing units 22, 24, 26 and 28 are substantially identical and of conventional design. The first printing unit 22 includes an in-feed transfer cylinder 30, a plate cylinder 32, a blanket cylinder 34 and an impression cylinder 36, all supported for rotation in parallel alignment between the press side frames 14, 15 which define printing unit towers T1, T2, T3 and T4. Each of the first three printing units 22, 24 and 26 have a transfer cylinder 38 disposed to transfer the freshly printed sheets from the adjacent impression cylinder and transfer the freshly printed sheets to the next printing unit via an intermediate transfer drum 40.

The last printing unit 28 includes a delivery cylinder 42 mounted on a delivery shaft 43. The delivery cylinder 42 supports the freshly printed sheet 18 as it is transferred from

the last impression cylinder 36 to a delivery conveyor system, generally designated 44, which transfers the freshly printed sheet to the sheet delivery stacker 20. To prevent smearing during transfer, a flexible covering is mounted on the delivery cylinder 42, as described and claimed in U.S. Patent 4,402,267 to Howard W. DeMoore, which is incorporated herein by reference. The flexible covering is manufactured and sold by Printing Research, Inc. of Dallas, Texas, U.S.A., under its trademark SUPER BLUE®. Optionally, a vacuum-assisted sheet transfer assembly manufactured and sold by Printing Research, Inc. of Dallas, Texas, U.S.A., under its trademark BACVAC® can be substituted for the delivery transfer cylinder 42 and flexible covering.

The delivery conveyor system 44 as shown in FIGURE 2 is of conventional design and includes a pair of endless delivery gripper chains 46, only one of which is shown carrying at regular spaced locations along the chains, laterally disposed gripper bars having gripper fingers used to grip the leading edge of a freshly printed or coated sheet 18 after it leaves the nip between the impression cylinder 36 and delivery cylinder 42 of the last printing unit 28. As the leading edge is gripped by the gripper fingers, the delivery chains 46 pull the sheet away from the last impression cylinder 36 and convey the freshly printed or coated sheet to the sheet delivery stacker 20.

Prior to reaching the delivery sheet stacker, the freshly printed and/or coated sheets S pass under a delivery dryer 48 which includes a combination of infra-red thermal radiation, high velocity hot air flow and a high performance heat and moisture extractor for drying the ink and/or the protective/decorative coating. Preferably, the delivery dryer 48, including the high performance heat and moisture extractor is constructed as described in U.S. Application Serial Number 08/116,711, filed September 3, 1993, entitled "Infra-Red Forced Air Dryer and Extractor" by Howard C. Secor, Ronald M. Rendleman and Paul D. Copenhaver, commonly assigned to the assignee of the present invention, Howard W. DeMoore, and licensed to Printing

Research, Inc. of Dallas, Texas, U.S.A., which manufactures and markets the delivery dryer 48 under its trademark AIR BLANKET™.

In the exemplary embodiment shown in FIGURE 3, the first printing unit 22 has a flexographic printing plate PF mounted on the plate cylinder, and therefore neither an inking roller train nor a dampening system is required. A flexographic printing plate PF is also mounted on the plate cylinder of the second printing unit 24. The form rollers of the inking roller train 52 shown mounted on the second printing unit 24 are retracted and locked off to prevent plate contact. Flexographic ink is supplied to the flexographic plate PF of the second printing unit 24 by the inking/coating apparatus 10.

A suitable flexographic printing plate PF is offered by E.I. du Pont de Nemours of Wilmington, Delaware, U.S.A., under its trademark CYREL®. Another source is BASF Aktiengesellschaft of Ludwigshafen, Germany, which offers a suitable flexographic printing plate under its trademark NYLOFLEX®.

The third printing unit 26 as illustrated in FIGURE 3 and FIGURE 4 is equipped for lithographic printing and includes an inking apparatus 50 having an inking roller train 52 arranged to transfer ink Q from an ink fountain 54 to a lithographic plate P mounted on the plate cylinder 32. This is accomplished by a fountain roller 56 and a ductor roller 57. The fountain roller 56 projects into the ink fountain 54, whereupon its surface picks up ink. The lithographic printing ink Q is transferred from the fountain roller 56 to the inking roller train 52 by the ductor roller 57. The inking roller train 52 supplies ink Q to the image areas of the lithographic printing plate P.

The lithographic printing ink Q is transferred from the lithographic printing plate P to an ink receptive blanket B which is mounted on the blanket cylinder 34. The inked image carried on the blanket B is transferred to a substrate S as the substrate is transferred through the nip between the blanket cylinder 34 and the impression cylinder 36.

The inking roller arrangement 52 illustrated in FIGURE 3 and FIGURE 4 is exemplary for use in combination with lithographic ink printing plates P. It is understood that a dampening system 58 having a dampening fluid reservoir DF is coupled to the inking roller train 52 (FIGURE 4), but is not required for waterless or flexographic printing.

The plate cylinder 32 of printing unit 28 is equipped with a waterless printing plate PW. Waterless printing plates are also referred to as dry planographic printing plates and are disclosed in the following U.S. patents: 3,910,187; Re. 30,670; 4,086,093; and 4,853,313. Suitable waterless printing plates can be obtained from Toray Industries, Inc. of Tokyo, Japan. A dampening system is not used for waterless printing, and waterless (oil-based) printing ink is used. The waterless printing plate PW has image areas and non-image areas which are oleophilic/hydrophilic and oleophobic/hydrophobic, respectively. The waterless printing plate PW is engraved or etched, with the image areas being recessed with respect to the non-image areas. The image area of the waterless printing plate PW is rolled-up with the flexographic or aqueous printing ink which is transferred by the applicator roller 66. Both aqueous and oil-based inks and coatings are repelled from the non-image areas, and are retained in the image areas. The printing ink or coating is then transferred from the image areas to an ink or coating receptive blanket B and is printed or coated onto a substrate S.

For some printing jobs, a flexographic plate PF or a waterless printing plate PW is mounted over a resilient packing such as the blanket B on the blanket cylinder 34, for example as indicated by phantom lines in printing unit 22 of FIGURE 5. An advantage of this alternative embodiment is that the waterless plate PW or the flexographic plate PF are resiliently supported over the blanket cylinder by the underlying blanket B or other resilient packing. The radial deflection and give of the resilient blanket B provides uniform, positive engagement between

the applicator roller 66 and a flexographic plate or waterless plate.

In that arrangement, a plate is not mounted on the plate cylinder 32; instead, a waterless plate PW is mounted on the blanket cylinder, and the inked image on the waterless printing plate is not offset but is instead transferred directly from the waterless printing plate PW to the substrate S. The water component of flexographic ink on the freshly printed sheet is evaporated by high velocity, hot air dryers and high volume heat and moisture extractors so that the freshly printed aqueous or flexographic ink is dried before the substrate is printed on the next printing unit.

Referring now to FIGURE 2, FIGURE 3 and FIGURE 9, the inking/coating apparatus 10 is pivotally mounted on the side frames 14, 15 for rotation about an axis X. The inking/coating apparatus 10 includes a frame 60, a hydraulic motor 62, a lower gear train 64, an upper gear train 65, an applicator roller 66, a sealed doctor blade assembly 68 (FIGURE 6), and a drip pan DP, all mounted on the frame 60. The external peripheral surface of the applicator roller 66 is wetted by contact with liquid coating material or ink contained in a reservoir 70.

The hydraulic motor 62 drives the applicator roller 66 synchronously with the plate cylinder 32 and the blanket cylinder 34 in response to an RPM control signal from the press drive (not illustrated) and a feedback signal developed by a tachometer 72. While a hydraulic drive motor is preferred, other drive means such as an electric drive motor or an equivalent can be used.

When using waterless printing plate systems, the temperature of the waterless printing ink and of the waterless printing plate must be closely controlled for good image reproduction. For example, for waterless offset printing with TORAY waterless printing plates PW, it is absolutely necessary to control the waterless printing plate surface and waterless ink temperature to a very narrow range, for example 24°C (75°F) to 27°C (80°F).

Referring to FIGURE 7, the reservoir 70 is supplied with ink or coating which is temperature controlled by a heat exchanger 71. The temperature controlled ink or coating material is circulated by a positive displacement pump, for example a peristaltic pump, through the reservoir 70 and heat exchanger 71 from a source 73 through a supply conduit 75 and a return conduit 77. The heat exchanger 71 cools or heats the ink or coating material and maintains the ink or coating and the printing plate within the desired narrow temperature range.

According to one aspect of the present invention, aqueous/flexographic ink or coating material is supplied to the applicator roller 66, which transfers the aqueous/flexographic ink or coating material to the printing plate (FIGURE 7), which may be a waterless printing plate or a flexographic printing plate. When the inking/coating apparatus is used for applying aqueous/flexographic ink or coating material to a waterless printing plate PW, the inking roller train 52 is not required, and is retracted away from the printing plate. Because the viscosity of aqueous/flexographic printing ink or coating material varies with temperature, it is necessary to heat or cool the aqueous/flexographic printing ink or coating material to compensate for ambient temperature variations to maintain the ink viscosity in a preferred operating range.

For example, the temperature of the printing press can vary from around 60°F (15°C) in the morning, to around 85°F (29°C) or more in the afternoon. The viscosity of aqueous/flexographic printing ink or coating material can be marginally high when the ambient temperature of the press is near 60°F (15°C), and the viscosity can be marginally low when the ambient temperature of the press exceeds 85°F (29°C). Consequently, it is desirable to control the temperature of the aqueous/flexographic printing ink or coating material so that it will maintain the surface temperature of waterless printing plates within the specified temperature range. Moreover, the ink/coating material temperature should be controlled to maintain the tack of the aqueous/flexographic

printing ink or coating material within a desired range when the ink or coating material is being used in connection with flexographic printing processes.

The applicator roller 66 is preferably an anilox fluid metering roller which transfers measured amounts of printing ink or coating material to a plate or blanket. The surface of an anilox roller is engraved with an array of closely spaced, shallow depressions referred as "cells". Ink or coating from the reservoir 70 flows into the cells as the anilox roller turns through the reservoir. The transfer surface of the anilox roller is "doctored" (wiped or scraped) by dual doctor blades 68A, 68B to remove excess ink or coating material. The ink or coating metered by the anilox roller is that contained within the cells. The dual doctor blades 68A, 68B also seal the supply reservoir 70.

The anilox applicator roller 66 is cylindrical and may be constructed in various diameters and lengths, containing cells of various sizes and shapes. The volumetric capacity of an anilox roller is determined by cell size, shape and number of cells per unit area. Depending upon the intended application, the cell pattern may be fine (many small cells per unit area) or coarse (fewer large cells per unit area).

By supplying the ink or coating material through the inking/coating apparatus 10, more ink or coating material can be applied to the sheet S as compared with the inking roller train of a lithographic printing unit. Moreover, color intensity is stronger and more brilliant because the aqueous or flexographic ink or coating material is applied at a much heavier film thickness or weight than can be applied by the lithographic process, and the aqueous or flexographic colors are not diluted by dampening solution.

Preferably, the sealed doctor blade assembly 68 is constructed as described in U.S. Patent 5,176,077 to Howard W. DeMoore, co-inventor and assignee, which is incorporated herein by reference. An advantage of using a sealed reservoir is that fast drying ink or coating material can be used. Fast drying ink or

coating material can be used in an open fountain 53 (see FIGURE 8); however, open air exposure causes the water and solvents in the fast-drying ink or coating material to evaporate faster, thus causing the ink or coating material to dry prematurely and change viscosity. Moreover, an open fountain emits unwanted odors into the press room. When the sealed doctor blade assembly is utilized, the pump (FIGURE 7) which circulates ink or coating material to the doctor blade head is preferably a peristaltic pump, which does not inject air into the feeder lines which supply the ink or coating reservoir 70 and helps to prevent the formation of air bubbles and foam within the ink or coating material.

An inking/coating apparatus 10 having an alternative applicator roller arrangement is illustrated in FIGURES 10-13. In this arrangement, the engraved metering surface of the anilox applicator rollers 66, 67 are partitioned by smooth seal surfaces 66C which separates a first engraved peripheral surface portion 66A from a second engraved peripheral surface portion 66B. Likewise, smooth seal surfaces 66D, 66E are formed on the opposite end portions of the applicator roller 66 for engaging end seals 134, 136 (FIGURE 12) of the doctor blade reservoir. The upper applicator roller 67 has engraved anilox metering surfaces 67A and 67B which are separated by a smooth seal band 67C.

Referring now to FIGURE 12 and FIGURE 13, the reservoir 70 of the doctor blade head 68 is partitioned by a curved seal element 130 to form two separate chambers 70A, 70B. The seal element 130 is secured to the doctor blade head within an annular groove 132. The seal element 130 is preferably made of polyurethane foam or other durable, resilient foam material. The seal element 130 is engaged by the seal band 66, thus forming a rotary seal which blocks the leakage of ink or coating material from one reservoir chamber into the other reservoir chamber. Moreover, the seal band provides an unprinted or uncoated area which separates the printed or coated areas from each other, which is needed for work and turn printing jobs or other printing jobs which print two or more separate images onto the same substrate.

Another advantage of the split applicator roller embodiment is that it enables two or more flexographic inks or coating materials to be printed simultaneously within the same lithographic printing unit. That is, the reservoir chambers 70A, 70B of the upper doctor blade assembly can be supplied with gold ink and silver ink, for example, while the reservoir chambers 70A, 70B of the lower doctor blade assembly can be supplied with inks of two additional colors, for example opaque white ink and blue ink. This permits the opaque white ink to be overprinted with the gold ink, and the blue ink to be overprinted with the silver ink on the same printing unit on any lithographic press.

Moreover, a catalyst can be used in the upper doctor blade reservoir and a reactive ink or coating material can be used in the lower doctor blade reservoir. This can provide various effects, for example improved chemical resistance and higher gloss levels.

The split applicator roller sections 67A, 67B in the upper cradle position can be used for applying two separate inks or coating materials simultaneously, for example flexographic, aqueous and ultra-violet curable inks or coating materials, to separate surface areas of the plate, while the lower applicator roller sections 66A, 66B can apply an initiator layer and a micro-encapsulated layer simultaneously to separate blanket surface areas. Optionally, the metering surface portions 66A, 66B can be provided with different cell metering capacities for providing different printing effects which are being printed simultaneously. For example, the screen line count on one half-section of an anilox applicator roller is preferably in the range of 200-600 lines per inch (79-236 lines per cm) for half-tone images, and the screen line count of the other half-section is preferably in the range of 100-300 lines per inch (39-118 lines per cm) for overall coverage, high weight applications such as opaque white. This split arrangement in combination with dual applicator rollers is particularly advantageous when used in connection with "work and turn" printing jobs.

Referring again to FIGURE 8, instead of using the sealed doctor blade reservoir assembly 68 as shown in FIGURE 6, an open fountain assembly 69 is provided by the fountain pan 53 which contains a volume of liquid ink Q or coating material. The liquid ink or coating material is transferred to the applicator roller 66 by a pan roller 55 which turns in contact with ink Q or coating material in the fountain pan. If a split applicator roller is used, the pan roller 55 is also split, and the pan is divided into two pan sections 53A, 53B by a separator plate 53P, as shown in FIGURE 16.

In the alternative embodiment of FIGURE 16, the pan roller 55 is divided into two pan roller sections 55A, 55B by a centrally located, annular groove 59. The separator plate 53P is received within and centrally aligned with the groove 59, but does not touch the adjoining roller faces. By this arrangement, two or more inks or coating materials Q1, Q2 are contained within the open pan sections 55A, 55B for transfer by the split pan roller sections 53A, 53B, respectively. This permits two or more flexographic inks or coating materials to be transferred to two separate image areas on the plate or on the blanket of the same printing unit. This arrangement is particularly advantageous for work and turn printing jobs or other printing jobs which print two or more separate images onto the same substrate.

The frame 60 of the inking/coating apparatus 10 includes side support members 74, 76 which support the applicator roller 66, gear train 64, gear train 65, doctor blade assembly 68 and the drive motor 62. The applicator roller 66 is mounted on stub shafts 63A, 63B which are supported at opposite ends on a lower cradle assembly 100 formed by a pair of side support members 78, 80 which have sockets 79, 81 and retainer caps 101, 103. The stub shafts are received in roller bearings 105, 107 which permit free rotation of the applicator roller 66 about its longitudinal axis A1 (axis A2 in the upper cradle). The retainer caps 101, 103 hold the stub shafts 63A, 63B and bearings 105, 107 in the sockets 79,

81 and hold the applicator roller 66 in parallel alignment with the pivot axis X.

The side support members 74, 76 also have an upper cradle assembly 102 formed by a pair of side support members 82, 84 which are vertically spaced with respect to the lower side plates 78, 80. Each cradle 100, 102 has a pair of sockets 79, 81 and 83, 85, respectively, for holding an applicator roller 66, 67 for spot coating or inking engagement with the printing plate P on the plate cylinder 32 (FIGURE 4) or with a printing plate P or a blanket B on the blanket cylinder 34.

Preferably, the applicator roller 67 (FIGURE 8, FIGURE 9) the upper cradle (plate) position is an anilox roller having a resilient transfer surface. In the dual cradle arrangement as shown in FIGURE 2, the press operator can quickly change from blanket inking/coating to plate inking/coating within minutes, since it is only necessary to release, remove and reposition or replace the applicator roller 66.

The capability to simultaneously print in the flexographic mode, the aqueous mode, the waterless mode, or the lithographic mode on different printing units of the same lithographic press and to print or coat from either the plate position or the blanket position on any one of the printing units is referred to herein as the LITHOFLEX™ printing process or system. LITHOFLEX™ is a trademark of Printing Research, Inc. of Dallas, Texas, U.S.A., exclusive licensee of the present invention.

Referring now to FIGURE 14, an inking/coating apparatus 10 having an inking/coating assembly 109 of an alternative design is installed in the upper cradle position for applying ink and/or coating material to a plate P on the plate cylinder 32. According to this alternative embodiment, an applicator roller 67R having a resilient transfer surface is coupled to an anilox fluid metering roller which transfers measured amounts of printing ink or coating material to the plate P. The anilox roller 111 has a transfer surface constructed of metal, ceramic or composite material which is engraved with cells. The resilient applicator roller 67R is

interposed in transfer engagement with the plate P and the metering surface of the anilox roller 111. The resilient transfer surface of the applicator roller 67R provides uniform, positive engagement with the plate.

Referring now to FIGURE 17, an inking/coating apparatus 10 having an alternative inking/coating assembly 113 is installed in the lower cradle assembly 100 for applying flexographic or aqueous ink and/or coating material Q to a plate or blanket mounted on the blanket cylinder 34. Instead of using the sealed, dual doctor blade reservoir assembly 68 as shown in FIGURE 6, an open, single doctor blade anilox roller assembly 113 is supplied with liquid ink Q or coating material contained in an open fountain pan 117. The liquid ink or coating material Q is transferred to the engraved transfer surface of the anilox roller 66 as it turns in the fountain pan 117. Excess ink or coating material Q is removed from the engraved transfer surface by a single doctor blade 68B. The liquid ink or coating material Q is pumped from an off-press source, for example the drum 73 shown in FIGURE 17, through a supply conduit 119 into the fountain pan 117 by a pump 120.

For overall inking or coating jobs, the metering transfer surface of the anilox roller 66 extends over its entire peripheral surface. However, for certain printing jobs which print two or more separate images onto the same substrate, for example work and turn printing jobs, the metering transfer surface of the anilox applicator roller 66 is partitioned by a centrally located, annular undercut groove 66C which separates first and second metering transfer surfaces 66A, 66B as shown in FIGURE 11 and FIGURE 18.

The single doctor blade 68B has an edge 68E which wipes simultaneously against the split metering transfer surfaces 66A, 66B. In this single blade, split anilox roller embodiment 113, it is necessary to provide dual supply sources, for example drums 73A, 73B, dual supply lines 119A, 119B, and dual pumps 120A, 120B. Moreover, the fountain pan 117 is also split, and the pan 117 is

divided into two pan sections 117A, 117B by a separator plate 121, as shown in FIGURE 18. The separator plate 121 is centrally aligned with the undercut groove 66C, but does not touch the adjoining roller faces.

Although the single blade, split anilox applicator roller assembly 113 is shown mounted in the lower cradle position (FIGURE 17), it should be understood that the single blade, split anilox applicator roller assembly 113 can be mounted and used in the upper cradle position, as well.

According to another aspect of the present invention, the inking/coating apparatus 10 is pivotally coupled on horizontal pivot pins 88P, 90P which allows the single head, dual cradle inking/coating apparatus 10 to be mounted on any lithographic printing unit. Referring to FIGURE 9, the horizontal pivot pins 88P, 90P are mounted within the traditional dampener space 29 of the printing unit and are secured to the press side frames 14, 15, respectively. Preferably, the pivot support pins 88P, 90P are secured to the press side frames by a threaded fastener. The pivot support pins are received within circular openings 88, 90 which intersect the side support members 74, 76 of the inking/coating apparatus 10. The horizontal support pins 88P, 90P are disposed in parallel alignment with rotational axis X and with the plate cylinder and blanket cylinder, and are in longitudinal alignment with each other.

Preferably, the pivot pins 88P, 90P are located in the dampener space 29 so that the rotational axes A1, A2 of the applicator rollers 66, 67 are elevated with respect to the nip contact points N1, N2. By that arrangement, the transfer point between the applicator roller 66 and a blanket on the blanket cylinder 34 (as shown in FIGURE 8) and the transfer point between the applicator roller 66 and a plate on the plate cylinder 32 (as shown in FIGURE 5) are above the radius lines R1, R2 of the plate cylinder and the blanket cylinder, respectively. This permits the inking/coating apparatus 10 to move clockwise to retract the applicator roller 66 to an off-impression position relative to the

blanket cylinder in response to a single extension stroke of the power actuator arms 104A, 106A. Similarly, the applicator roller 66 is moved counterclockwise to the on-impression operative position as shown in FIGURES 4, 5, 6 and 8 by a single retraction stroke of the actuator arms 104A, 106A, respectively.

Preferably, the pivot pins are made of steel and the side support members are made of aluminum, with the steel pivot pins and the aluminum collar portion bordering the circular openings 88, 90 forming a low friction journal. By this arrangement, the inking/coating apparatus 10 is freely rotatable clockwise and counterclockwise with respect to the pivot pins 88P, 90P. Typically, the arc length of rotation is approximately 60 mils (about 1.5 mm). Consequently, the inking/coating apparatus 10 is almost totally enclosed within the dampener space 29 of the printing unit in the on-impression position and in the off-impression position.

The cradle assemblies 100 and 102 position the applicator roller 66 in inking/coating alignment with the plate cylinder or blanket cylinder, respectively, when the inking/coating apparatus 10 is extended to the operative (on-impression) position. Moreover, because the inking/coating apparatus 10 is installed within the dampener space 29, it is capable of freely rotating through a small arc while extending and retracting without being obstructed by the press side frames or other parts of the printing press. This makes it possible to install the inking/coating apparatus 10 on any lithographic printing unit. Moreover, because of its internal mounting position within the dampener space 29, the projection of the inking/coating apparatus 10 into the space between printing units is minimal. This assures unrestricted operator access to the printing unit when the applicator head is in the operative (on-impression) and retracted (off-impression) positions.

As shown in FIGURE 4 and FIGURE 5, movement of the inking/coating apparatus 10 is counterclockwise from the retracted

(off-impression) position to the operative (on-impression) position.

Although the dampener side installation is preferred, the inking/coating apparatus 10 can be adapted for operation on the delivery side of the printing unit, with the inking/coating apparatus being movable from a retracted (off-impression) position to an on-impression position for engagement of the applicator roller with either a plate on the plate cylinder or a blanket on the blanket cylinder on the delivery side 25 of the printing unit.

Movement of the inking/coating apparatus 10 to the operative (on-impression) position is produced by power actuators, preferably double acting pneumatic cylinders 104, 106 which have extendable/retractable power transfer arms 104A, 106A, respectively. The first pneumatic cylinder 104 is pivotally coupled to the press frame 14 by a pivot pin 108, and the second pneumatic cylinder 106 is pivotally coupled to the press frame 15 by a pivot pin 110. In response to selective actuation of the pneumatic cylinders 104, 106, the power transfer arms 104A, 106A are extended or retracted. The power transfer arm 104A is pivotally coupled to the side support member 74 by a pivot pin 112. Likewise, the power transfer arm 106A is pivotally coupled to the side support member 76 by a pivot pin 114.

As the power arms extend, the inking/coating apparatus 10 is rotated clockwise on the pivot pins 88P, 90P, thus moving the applicator roller 66 to the off-impression position. As the power arms retract, the inking/coater apparatus 60 is rotated counterclockwise on the pivot pins 88P, 90P, thus moving the applicator roller 66 to the on-impression position. The torque applied by the pneumatic actuators is transmitted to the inking/coating apparatus 10 through the pivot pin 112 and pivot pin 114.

Fine adjustment of the on-impression position of the applicator roller relative to the plate cylinder or the blanket cylinder, and of the pressure of roller engagement, is provided by an adjustable stop assembly 115. The adjustable stop assembly 115

has a threaded bolt 116 which is engagable with a bell crank 118. The bell crank 118 is pivotally coupled to the side support member 74 on a pin 120. One end of the bell crank 118 is engagable by the threaded bolt 116, and a cam roller 122 is mounted for rotation on its opposite end. The striking point of engagement is adjusted by rotation of the bolt 116 so that the applicator roller 66 is properly positioned for inking/coating engagement with the plate P or blanket B and provides the desired amount of inking/coating pressure when the inking/coating assembly 60 is moved to the operative position.

This arrangement permits the in-line inking/coating apparatus to operate effectively without encroaching in the interunit space between any adjacent printing units, and without blocking or obstructing access to the cylinders of the printing units when the inking/coating apparatus is in the extended (off-impression) position or retracted (on-impression) position. Moreover, when the in-line inking/coating apparatus is in the retracted position, the doctor blade reservoir and coating circulation lines can be drained and flushed automatically while the printing press is running as well as when the press has been stopped for change-over from one job to another or from one type of ink or coating to another.

Substrates which are printed or coated with aqueous flexographic printing inks require high velocity hot air for drying. When printing a flexographic ink such as opaque white or metallic gold, it is always necessary to dry the printed substrates between printing units before overprinting them. According to the present invention, the water component on the surface of the freshly printed or coated substrate S is evaporated and dried by high velocity, hot air interunit dryer and high volume heat and moisture extractor units 124, 126 and 128, as shown in FIGURE 2, FIGURE 4 and FIGURE 5. The dryer/extractor units 124, 126 and 128 are oriented to direct high velocity heated air onto the freshly printed/coated substrates as they are transferred by the impression cylinder 36 and the intermediate

transfer drum 40 of one printing unit and to another transfer cylinder 30 and to the impression cylinder 36 of the next printing unit. By that arrangement, the freshly printed flexographic ink or coating material is dried before the substrate S is overprinted by the next printing unit.

The high velocity, hot air dryer and high performance heat and moisture extractor units 124, 126 and 128 utilize high velocity air jets which scrub and break-up the moist air layer which clings to the surface of each freshly printed or coated sheet or web. Within each dryer, high velocity air is heated as it flows across a resistance heating element within an air delivery baffle tube. High velocity jets of hot air are discharged through multiple airflow apertures into an exposure zone Z (FIGURE 4 and FIGURE 5) and onto the freshly printed/coated sheet S as it is transferred by the impression cylinder 36 and transfer drum 40, respectively.

Each dryer assembly includes a pair of air delivery dryer heads 124D, 126D and 128D which are arranged in spaced, side-by-side relationship. The high velocity, hot air dryer and high performance heat and moisture extractor units 124, 126 and 128 are preferably constructed as disclosed in co-pending U.S. Patent Application Serial No. 08/132,584, filed October 6, 1993, entitled "High Velocity Hot Air Dryer", to Howard W. DeMoore, co-inventor and assignee of the present invention, and which is incorporated herein by reference, and which is marketed by Printing Research, Inc. of Dallas, Texas, U.S.A., under its trademark SUPER BLUE HV™.

The hot moisture-laden air displaced from the surface of each printed or coated sheet is extracted from the dryer exposure zone Z and exhausted from the printing unit by the high volume extractors 124, 126 and 128. Each extractor head includes an extractor manifold 124E, 126E and 128E coupled to the dryer heads 124D, 126D and 128D and draws the moisture, volatiles, odors and hot air through a longitudinal air gap G between the dryer heads. Best results are obtained when extraction is performed simulta-

neously with drying. Preferably, an extractor is closely coupled to the exposure zone Z at each dryer location as shown in FIGURE 4. Extractor heads 124E, 126E and 128E are mounted on the dryer heads 124D, 126D and 128D, respectively, with the longitudinal extractor air gap G facing directly into the exposure zone Z. According to this arrangement, each printed or coated sheet is dried before it is printed on the next printing unit.

The aqueous water-based inks used in flexographic printing evaporate at a relatively moderate temperature provided by the interunit high velocity hot air dryers/extractors 124, 126 and 128. Sharpness and print quality are substantially improved since the flexographic ink or coating material is dried before it is overprinted on the next printing unit. Since the freshly printed flexographic ink is dry, dot gain is substantially reduced and back-trapping on the blanket of the next printing unit is virtually eliminated. This interunit drying/extracting arrangement makes it possible to print flexographic inks such as metallic ink and opaque white ink on the first printing unit, and then dry-trap and overprint on the second and subsequent printing units.

Moreover, this arrangement permits the first printing unit 22 to be used as a coater in which a flexographic, aqueous or UV-curable coating material is applied to the lowest grade substrate such as recycled paper, cardboard, plastic and the like, to trap and seal-in lint, dust, spray powder and other debris and provide a smoother, more durable printing surface which can be overprinted on the next printing unit.

A first down (primer) aqueous coating layer seals-in the surface of a low grade, rough substrate, for example, re-cycled paper or plastic, and improves overprinted dot definition and provides better ink lay-down while preventing strike-through and show-through. A flexographic UV-curable coating material can then be applied downstream over the primer coating, thus producing higher coating gloss.

Preferably, the applicator roller 66 is constructed of composite carbon fiber material, metal or ceramic coated metal

when it is u[illegible] for applying ink or coating [illegible]ral to the blanket B or other resilient material on the blanket cylinder 34. When the applicator roller 66 is applied to the plate, it is preferably constructed as an anilox roller having a resilient, compressible transfer surface. Suitable resilient roller surface materials include Buna N synthetic rubber and EPDM (terpolymer elastomer).

It has been demonstrated in prototype testing that the inking/coating apparatus 10 can apply a wide range of ink and coating types, including fluorescent (Day Glo), pearlescent, metallics (gold, silver and other metals), glitter, scratch and sniff (micro-encapsulated fragrance), scratch and reveal, luminous, pressure-sensitive adhesives and the like, as well as UV-curable and aqueous coatings.

With the dampener assembly removed from the printing unit, the inking/coating apparatus 10 can easily be installed in the dampener space for selectively applying flexographic inks and/or coatings to a flexographic or waterless printing plate or to the blanket. Moreover, overprinting of the flexographic inks and coatings can be performed on the next printing unit since the flexographic inks and/or coatings are dried by the high velocity, hot air interunit dryer and high volume heat and moisture extractor assembly of the present invention.

The flexographic inks and coatings as used in the present invention contain colored pigments and/or soluble dyes, binders which fix the pigments onto the surface of the substrate, waxes, defoamers, thickeners and solvents. Aqueous printing inks predominantly contain water as a diluent and/or vehicle. The thickeners which are preferred include algonates, starch, cellulose and its derivatives, for example cellulose esters or cellulose ethers and the like. Coloring agents including organic as well as inorganic pigments may be derived from dyes which are insoluble in water and solvents. Suitable binders include acrylates and/or polyvinylchloride.

When metallic inks are printed, the cells of the anilox roller must be appropriately sized to prevent the metal particles from getting stuck within the cells. For example, for metallic gold ink, the anilox roller should have a screen line count in the range of 175-300 lines per inch (68-118 lines per cm). Preferably, in order to keep the anilox roller cells clear, the doctor blade assembly 68 is equipped with a bristle brush BR (FIGURE 14) as set forth in U.S. Patent 5,425,809 to Steven M. Person, assigned to Howard W. DeMoore, and licensed to Printing Research, Inc. of Dallas, Texas, U.S.A., which is incorporated herein by reference.

The inking/coating apparatus 10 can also apply UV-curable inks and coatings. If UV-curable inks and coatings are utilized, ultra-violet dryers/extractors are installed adjacent to the high velocity hot air dryer/extractor units 124, 126 and 128, respectively.

It will be appreciated that the LITHOFLEX™ printing process described herein makes it possible to selectively operate a printing unit of a press in the lithographic printing mode while simultaneously operating another printing unit of the same press in either the flexographic printing mode or in the waterless printing mode, while also providing the capability to print or coat, separately or simultaneously, from either the plate position or the blanket position. The dual cradle support arrangement of the present invention makes it possible to quickly change over from inking/coating on the blanket cylinder position to inking/coating on the plate cylinder position with minimum press down-time, since it is only necessary to remove and reposition or replace the applicator roller 66 while the inking/coating apparatus 10 is in the retracted position. It is only necessary to remove four cap screws, lift the applicator roller 66 from the cradle, and reposition it in the other cradle. All of this can be accomplished in a few minutes, without removing the inking/coating apparatus 10 from the press.

It is possible to spot coat or overall coat from the plate position or from the blanket position with flexographic inks or coatings on one printing unit and then spot coat or overall coat with UV-curable inks or coatings from the plate position or from the blanket position on another printing unit during the same press run. Moreover, the press operator can spot or overall coat from the plate for one job, and then spot and/or overall coat from the blanket on the next job.

The positioning of the applicator roller relative to the plate or blanket is repeatable to a predetermined preset operative position. Consequently, only minor printing unit modifications or alterations may be required for the LITHOFLEX™ process. Although automatic extension and retraction have been described in connection with the exemplary embodiment, extension to the operative (on-impression) position and retraction to a non-operative (off-impression) position can be carried out manually, if desired. In the manual embodiment, it is necessary to latch the inking/coating apparatus 10 to the press side frames 14, 15 in the operative (on-impression) position, and to mechanically prop the inking/coating apparatus in the off-impression (retracted) position.

Referring again to FIGURE 8, an applicator roller 66 is mounted on the lower cradle assembly 100 by side support members 78, 80, and a second applicator roller 66 is mounted on the upper cradle assembly 102 by side support members 82, 84. According to this arrangement, the inking/coating apparatus 10 can apply printing ink and/or coating material to a plate on the plate cylinder, while simultaneously applying printing ink and/or coating material to a plate or a blanket on the blanket cylinder of the same printing unit. When the same color ink is used by the upper and lower applicator rollers from the plate position and from the blanket position simultaneously on the same printing unit, a "double bump" or double inking films or coating layers are applied to the substrate S during a single pass of the substrate through the printing unit. The tack of the two inks or coating

materials must be compatible for good transfer during the double bump. Moreover, the inking/coating apparatus 10 can be used for supplying ink or coating material to the blanket cylinder of a rotary offset web press, or to the blanket of a dedicated coating unit.

According to conventional bronzing techniques, a metallic (bronze) powder is applied off-line to previously printed substrate which produces a grainy, textured finish or appearance. The on-line application of bronze material by conventional flexographic or lithographic printing will only produce a smooth, continuous appearance. However, a grainy, textured finish is preferred for highest quality printing which, prior to the present invention, could only be produced by off-line methods.

Referring now to FIGURE 14 and FIGURE 15, metallic ink or coating material is applied on-line to the substrate S by simultaneous operation of the upper and lower applicator rollers 67R, 66 to produce an uneven surface finish having a bronze-like textured or grainy appearance. According to the simulated bronzing method of the present invention, the flexographic bronze ink is applied simultaneously to the plate and to the blanket by the dual cradle inking/coating apparatus 10 as shown in FIGURE 14. A resilient applicator roller 67R is mounted in the upper cradle 102, and an anilox applicator roller 66 is mounted on the lower cradle 100. The rollers are supplied from separate doctor blade reservoirs 70. The doctor blade reservoir 70 in the upper cradle position supplies bronze ink or coating material having relatively coarse, metallic particles 140 dispersed in aqueous or flexographic ink. The coarse particle ink or coating material is applied to the plate P by the resilient applicator roller 67R in the upper cradle position 102. At the same time, flexographic and/or bronze ink or coating material having relatively fine, metallic particles 142 is transferred to the blanket B by the anilox roller 66 which is mounted on the lower cradle 100.

The metering surfaces of the upper and lower applicator rollers have different cell sizes and volumetric capacities which

accommodate the coarse and fine metallic particles. For example, the anilox roller 111 mounted in the upper cradle position 102 which transfers the coarse metallic particles 140 preferably has a screen line count in the range of 100-300 lines per inch (39-118 lines per cm), and the metering surface of the anilox roller 66 mounted on the lower cradle 100 which transfers the relatively fine metallic particles 142 preferably has a screen line count in the range of 200-600 lines per inch (79-236 lines per cm).

After transfer from the plate to the blanket, the fine metallic particles 142 form a layer over the coarse metallic particles 140. As both bronze layers are offset onto the substrate S, the layer of fine metallic particles 142 is printed onto the substrate S with the top layer of coarse metallic particles 140 providing a textured, grainy appearance. The fine metallic particles 142 cover the substrate which would otherwise be visible in the gaps between the coarse metallic particles 140. The combination of the coarse particle layer over the fine particle layer thus provides a textured, bronzed-like finish and appearance.

Particulate materials other than metal can be used for producing a textured finish. For example, coarse and fine particles of metallized plastic (glitter), mica particles (pearlescent) and the like, can be substituted for the metallic particles for producing unlimited surface variations, appearances and effects. All of the particulate material, including the metallic particles, are preferably in solid, flat platelet form, and have a size dimension suitable for application by an anilox applicator roller. Other particulate or granular material, for example stone grit having irregular form and size, can be used to good advantage.

Solid metal particles in platelet form, which are good reflectors of light, are preferred for producing the bronzed-like appearance and effect. However, various textured finishes, which could have light-reflective properties, can be produced by using granular materials such as stone grit. Most commonly used metals

include copper, zinc and aluminum. Other ductile metals can be used, if desired. Moreover, the coarse and fine particles need not be made of the same particulate material. Various effects and textured appearances can be produced by utilizing diverse particulate materials for the coarse particles and the fine particles, respectively. Further, either fine or coarse particle ink or coating material can be printed from the upper cradle position, and either fine or coarse particle ink or coating material can be printed from the lower cradle position, depending on the special or surface finish that is desired.

It will be appreciated that the last printing unit 28 can be configured for additional inking/coating capabilities which include lithographic, waterless, aqueous and flexographic processes. Various substrate surface effects (for example double bump or triple bump inking/coating or bronzing) can be performed on the last printing unit. For triple bump inking/coating, the last printing unit 28 is equipped with an auxiliary in-line inking or coating apparatus 97 as shown in FIGURE 3 and FIGURE 4. The in-line inking or coating apparatus 97 allows the application of yet another film of ink or a protective or decorative layer of coating material over any freshly printed or coated surface effects or special treatments, thereby producing a triple bump. The triple bump is achieved by applying a third film of ink or layer of coating material over the freshly printed or coated double bump simultaneously while the substrate is on the impression cylinder of the last printing unit.

When the in-line inking/coating apparatus 97 is installed, it is necessary to remove the SUPER BLUE® flexible covering from the delivery cylinder 42, and it is also necessary to modify or convert the delivery cylinder 42 for inking/coating service by mounting a plate or blanket B on the delivery cylinder 42, as shown in FIGURE 3 and FIGURE 4. Packing material is placed under the plate or blanket B, thereby packing the plate or blanket B at the correct packed-to-print radial clearance so that ink or coating material will be printed or coated onto the freshly

printed substrate S as it transfers through the nip between the plate or blanket B on the converted delivery cylinder 42 and the last impression cylinder 36. According to this arrangement, a freshly printed or coated substrate is overprinted or overcoated with a third film or layer of ink or coating material simultaneously while a second film or layer of ink or coating material is being over-printed or over-coated on the last impression cylinder 36.

The auxiliary inking/coating apparatus 97 and the converted or modified delivery cylinder 42 are mounted on the delivery drive shaft 43. The inking/coating apparatus 97 includes an applicator roller, preferably an anilox applicator roller 97A, for supplying ink or coating material to a plate or blanket B on the modified or converted delivery cylinder 42. The in-line inking/coating apparatus 97 and the modified or converted delivery cylinder 42 are preferably constructed as described in U.S. Patent 5,176,077 to Howard W. DeMoore (co-inventor and assignee), which is hereby incorporated by reference. The in-line inking/coating apparatus 97 is manufactured and sold by Printing Research, Inc. of Dallas, Texas, U.S.A., under its trademark SUPER BLUE EZ COATER™.

After the delivery cylinder 42 has been modified or converted for inking/coating service, and because of the reduced nip clearance imposed by the plate or blanket B, the modified delivery cylinder 42 can no longer perform its original function of guiding and transferring the freshly printed or coated substrate. Instead, the modified or converted delivery cylinder 42 functions as a part of the inking/coating apparatus 97 by printing or coating a third down film of ink or layer of coating material onto the freshly printed or coated substrate as it is simultaneously printed or coated on the last impression cylinder 36. Moreover, the mutual tack between the second down ink film or coating layer and the third down ink film or coating layer causes the overprinted or overcoated substrate to cling to the plate or

blanket, thus opposing or resisting separation of the substrate from the plate or blanket.

To remedy this problem, a vacuum-assisted transfer apparatus 99 is mounted adjacent the modified or converted delivery cylinder 42 as shown in FIGURE 3 and FIGURE 4. Another purpose of the vacuum-assisted transfer apparatus 99 is to separate the freshly overprinted or overcoated triple bump substrate from the plate or blanket B as the substrate transfers through the nip. The vacuum-assisted transfer apparatus 99 produces a pressure differential across the freshly overprinted or overcoated substrate as it transfers through the nip, thus producing a separation force onto the substrate and providing a clean separation from the plate or blanket B.

The vacuum-assisted transfer apparatus 99 is preferably constructed as described in U.S. Patent Nos. 5,113,255; 5,127,329; 5,205,217; 5,228,391; 5,243,909; and 5,419,254, all to Howard W. DeMoore, co-inventor, which are incorporated herein by reference. The vacuum-assisted transfer apparatus 99 is manufactured and sold by Printing Research, Inc. of Dallas, Texas, U.S.A. under its trademark BACVAC™.

Although the present invention and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the present invention as defined by the appended claims.

What is claimed is:

1. A rotary offset printing press of the type including first and second printing units, the first printing unit comprising:

a plate cylinder having a flexographic printing plate mounted thereon;

a blanket cylinder having a blanket disposed in ink or coating transfer engagement with the flexographic printing plate for receiving aqueous or flexographic printing ink or coating material from the flexographic printing plate;

an impression cylinder disposed adjacent the blanket cylinder thereby forming a nip between the blanket and the impression cylinder whereby the aqueous or flexographic printing ink or coating material can be transferred from the blanket to a substrate as the substrate is transferred through the nip;

inking/coating apparatus movably coupled to the printing unit for movement to an on-impression operative position and to an off-impression retracted position;

the inking/coating apparatus including container means for containing a volume of aqueous or flexographic ink or coating material, and at least one applicator roller coupled to the container means for applying aqueous or flexographic ink or coating material to the flexographic printing plate or to the blanket when the inking/coating apparatus is in the on-impression operative position;

the container means having a partition dam dividing the container means thereby defining a first container region and a second container region;

the at least one applicator roller having first and second transfer surfaces and means separating the first and second transfer surfaces; and,

the first and second transfer surfaces of the at least one applicator roller being disposed within the first and second container regions for rolling contact with aqueous or

flexographic printing ink or coating material contained within the first and second container regions, respectively.

2. A rotary offset printing press as defined in claim 1, wherein:

said separating means is an annular seal element disposed on the applicator roller; and,

the partition element is disposed in sealing engagement against the annular seal element of the applicator roller.

3. A rotary offset printing press as defined in claim 1, wherein:

said container means is an open fountain pan;

said separating means is an annular groove intersecting the applicator roller thereby separating the first and second transfer surfaces; and,

the partition element is a separator plate mounted on the fountain pan between the first and second reservoir regions and disposed in the annular groove.

4. A rotary offset printing press as defined in claim 1, including sheet feeding means coupled to the first printing unit for consecutively feeding substrates in sheet form into the first printing unit.

5. A rotary offset printing press as defined in claim 1, including web feeding means coupled to the first printing unit for continuously feeding a substrate in continuous web form into the first printing unit.

6. A rotary offset printing press as defined in claim 1, wherein:

said container means is a fountain pan having first and second pan sections for containing first and second aqueous or flexographic inks or coating materials, respectively;

said applicator roller having first and second transfer surfaces and an annular groove separating said first and second transfer surfaces; and,

a pan roller having first and second transfer surfaces mounted for rotation in the first and second pan sections, respectively, for separately transferring aqueous or flexographic ink or coating material from the first and second pan sections to the first and second transfer surfaces of the applicator roller.

7. A rotary offset printing press as set forth in claim 1, wherein:

said container means is a sealed doctor blade head having first and second reservoir chambers, said partition dam being mounted on the doctor blade head and separating the first and second reservoir chambers;

the at least one applicator roller comprising an anilox transfer roller having first and second fluid metering transfer surfaces disposed for rolling contact with the aqueous or flexographic ink or coating material in the first and second reservoir chambers, respectively;

the separating means being a seal band formed on the applicator roller between the first and second transfer surfaces; and,

the partition dam being disposed in sealing engagement with the seal band in the coupled position.

8. A rotary offset printing press as defined in claim 1, wherein the inking/coating apparatus comprises:

first cradle means for supporting a first applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

second cradle means for supporting a second applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

a first applicator roller mounted for rotation on the first cradle means, the first applicator roller having first and second transfer surfaces and a seal band separating the first and second transfer surfaces;

a second applicator roller mounted for rotation on the second cradle means, the second applicator roller having first and second transfer surfaces and means separating the first and second transfer surfaces;

first reservoir means for containing a volume of ink or coating material, the first reservoir means having first and second reservoir chambers and a partition element separating the first and second reservoir chambers of th4e first reservior means;

second reservoir means for containing a volume of ink or coating material, the second reservoir means having first and second reservoir chambers and a partition element separating the first and second reservoir chambers of the second reservoir means;

the first and second reservoir means being coupled to the first and second applicator rollers, respectively, the first and second transfer surfaces of the first applicator roller being disposed for rolling contact with ink or coating material in the first and second reservoir chambers, respectively, of the first reservoir means and the first partition seal element being disposed in sealing engagement against the separating means of the first applicator roller in the coupled position; and,

the first and second transfer surfaces of the second applicator roller being disposed for rolling contact with ink or coating material in the first and second reservoir chambers, respectively, of the second reservoir means and the partition element of the second reservoir means being disposed in

sealing engagement with the separating means of the second applicator roller in the coupled position.

9. A rotary offset printing press as defined in claim 1, wherein:

the at least one applicator roller is an anilox roller having first and second fluid metering transfer surfaces; and,

the volumetric capacity of the first transfer surface being different from the volumetric capacity of the second transfer surface.

10. A rotary offset printing press as defined in claim 1, wherein the inking/coating apparatus comprises:

cradle means;

the at least one applicator roller being mounted for rotation on the cradle means, the applicator roller having first and second transfer surfaces and means separating the first and second metering transfer surfaces;

reservoir means for containing a volume of ink or coating material, the reservoir means having first and second reservoir chambers and a partition element separating the first and second reservoir chambers;

the at least one applicator roller being coupled to the reservoir means with the first and second fluid metering transfer surfaces being disposed for rolling contact with the ink or coating material in the first and second reservoir chambers, respectively, and the partition element being disposed in sealing engagement with separating means of the applicator roller in the coupled position; and,

the volumetric capacity of the first transfer surface being different from the volumetric capacity of the second transfer surface.

11. A rotary offset printing press as set forth in claim 1, wherein the inking/coating apparatus comprises:

a fountain pan for containing a volume of liquid ink or coating material;

an applicator roller having a metering surface; and,

a pan roller mounted for rotation in the fountain pan and coupled to the applicator roller for transferring ink or coating material from the fountain pan to the applicator roller.

12. A rotary offset printing press as defined in claim 1, further including:

a transfer drum coupled in substrate transfer relation with the impression cylinder of the first printing unit and in substrate transfer relation with the second printing unit;

a first dryer mounted adjacent the impression cylinder of the first printing unit for discharging heated air onto a freshly printed or coated substrate while the substrate is in contact with the impression cylinder of the first printing unit;

a second dryer mounted adjacent the transfer drum for discharging heated air onto a freshly printed or coated substrate after it has been transferred from the impression cylinder of the first printing unit and while it is in contact with the transfer cylinder; and,

a third dryer disposed adjacent the second printing unit for discharging heated air onto a freshly printed or coated substrate after it has been transferred from the transfer drum and before it is printed or otherwise processed on the second printing unit.

13. A rotary offset printing press as defined in claim 1, wherein the means for applying ink or coating material comprises:

first cradle means;

a first reservoir or fountain means mounted on the first cradle means for containing ink or coating material;

a first applicator roller mounted for rotation on the first cradle means and disposed for rolling contact with ink or coating material in the first reservoir or fountain means, the first applicator roller being engagable with a printing plate on the plate cylinder;

second cradle means;

a second reservoir or fountain means mounted on the second cradle means for receiving ink or coating material; and,

a second applicator roller mounted for rotation on the second cradle means and disposed for rolling contact with ink or coating material in the second reservoir or fountain means, the second applicator roller being engagable with a plate or blanket mounted on the blanket cylinder in the operative position.

14. A rotary offset printing press as defined in claim 1, wherein the inking/coating apparatus is pivotally mounted on the printing unit in a position in which the nip contact point between said at least one applicator roller and a blanket or plate is offset with respect to a radius line projecting through the center of the plate cylinder or blanket cylinder to the axis of rotation of the printing/coating unit.

15. A rotary offset printing press as defined in claim 1, wherein:

said at least one applicator roller having first and second transfer surfaces and a seal band surface disposed between and separating the first and second transfer surfaces;

the reservoir means having a chamber and a partition member disposed within the chamber, the partition member dividing the chamber thereby defining a first reservoir chamber region and a second reservoir chamber region; and,

the partition member surface being disposed in sealing engagement against the seal band of the applicator roller.

16. A rotary offset printing press as defined in claim 1, wherein the inking/coating apparatus comprises:

first cradle means for supporting a first applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

second cradle means for supporting a second applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

a first applicator roller mounted for rotation on the first cradle means, the first applicator roller having first and second fluid metering transfer surfaces and a separation band separating the first and second fluid metering transfer surfaces;

a second applicator roller mounted for rotation on the second cradle means, the second applicator roller having first and second fluid metering transfer surfaces and a separation band separating the first and second metering transfer surfaces;

first reservoir means for containing a volume of ink or coating material, the first reservoir means having first and second reservoir chambers and a first partition element separating the first and second reservoir chambers;

second reservoir means for containing a volume of ink or coating material, the second reservoir means having first and second reservoir chambers and a second partition seal element separating the first and second reservoir chambers of the second reservoir means;

the first and second fluid metering transfer surfaces of the first applicator roller being disposed for rolling contact with ink or coating material in the first and second reservoir chambers, respectively, of the first reservoir means and the first partition element being disposed in sealing engagement against the separation band of the first applicator roller in the coupled position; and,

the first and second fluid metering transfer surfaces of the second applicator roller being disposed for rolling contact with ink or coating material in the first and

second reservoir chambers, respectively, of the second reservoir means and the second partition element of the second reservoir means being disposed in sealing engagement with the separation band of the second applicator roller in the coupled position.

17. A printing press as defined in claim 1, wherein the inking/coating apparatus comprises:

first cradle means for supporting a first applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

second cradle means for supporting a second applicator roller for engagement with a plate or blanket when the inking/coating apparatus is in the operative position;

first reservoir means mounted on the first cradle means, said first reservoir means having a reservoir chamber for containing a volume of ink or coating material;

second reservoir means mounted on the second cradle means, said second reservoir means having a reservoir chamber for containing a volume of ink or coating material;

a first applicator roller mounted for rotation on the first cradle means, the first applicator roller having a fluid metering transfer surface;

a second applicator roller mounted for rotation on the second cradle means, the second applicator roller having a fluid metering transfer surface;

the first and second applicator rollers being coupled to the first and second reservoir means, respectively, the fluid metering transfer surfaces of the first and second applicator rollers being disposed for rolling contact with ink or coating material in the reservoir chambers of the first and second reservoir means, respectively; and,

the volumetric capacity of the fluid metering surface of the first applicator roller being different from the volumetric capacity of the fluid metering surface of the second applicator roller.

18. A printing press as defined in claim 1, wherein the means for applying ink or coating material comprises:

cradle means;

an applicator roller mounted for rotation on the cradle means, the applicator roller having first and second surfaces and a seal band separating the first and second transfer surfaces;

reservoir means for containing a volume of ink or coating material, the reservoir means having first and second reservoir chambers and a partition element separating the first and second reservoir chambers;

the applicator roller being coupled to the reservoir means with the first and second transfer surfaces being disposed for rolling contact with the ink or coating material in the first and second reservoir chambers, respectively, and the partition element being disposed in sealing engagement against the seal band of the applicator roller in the coupled position; and,

the volumetric capacity of the first fluid metering transfer surface being different from the volumetric capacity of the second fluid metering transfer surface.

19. A rotary offset printing press as defined in claim 1, further including:

a supply container for containing a volume of liquid ink or coating material;

circulation means coupled between the supply reservoir and the inking/coating apparatus for inducing the flow of liquid ink or coating material from said supply container to the inking/coating apparatus and for returning liquid ink or coating material from the inking/coating apparatus to the supply container; and,

heat exchanger means coupled to the circulation means for maintaining the temperature of the liquid ink or coating material within a predetermined temperature range.

20. A printing press as defined in claim 1, wherein the inking/coating apparatus is pivotally mounted on the first printing unit in a position in which the nip contact point between the applicator roller and a blanket or plate is offset with respect to a radius line projecting through the center of the plate cylinder or blanket cylinder to the axis of rotation of the printing/coating unit.

21. A printing press as defined in claim 1, including:

a dryer mounted on the first printing unit for discharging heated air onto a freshly printed or coated substrate before the freshly printed or coated substrate is subsequently printed, coated or otherwise processed on the second printing unit.

22. A printing press as defined in claim 21, wherein:

the dryer is mounted adjacent the impression cylinder of the first printing unit for discharging heated air onto a freshly printed or coated substrate while the substrate is in contact with said impression cylinder.

23. A printing press as defined in claim 1, further including:

a substrate transfer apparatus disposed in an interunit position on the press and coupled in substrate transfer relation with the impression cylinder of the first printing unit;

an interunit dryer disposed adjacent the substrate transfer apparatus for discharging heated air onto a freshly printed or coated substrate after it has been transferred from the first printing unit and while it is in contact with the substrate transfer apparatus.

24. A printing press as defined in claim 1, comprising:

a dryer mounted on the first printing unit for discharging heated air onto a freshly printed or coated substrate; and,

an extractor coupled to the dryer for extracting hot air and moisture vapors from an exposure zone between the dryer and the freshly printed or coated substrate.

Abstract of the Disclosure

A retractable in-line inking/coating apparatus can apply either spot or overall inking/coating material to a plate and/or a blanket on the first printing unit or on any consecutive printing unit of any rotary offset printing press. The inking/coating apparatus is pivotally mounted within the conventional dampener space of any lithographic printing unit. The aqueous component of the flexographic printing ink or aqueous coating material is evaporated and dried by high velocity, hot air dryers and high performance heat and moisture extractors so that the aqueous or flexographic ink or coating material on a freshly printed or coated sheet is dry and can be dry-trapped on the next printing unit. The inking/coating apparatus includes dual cradles that support first and second applicator rollers so that the inking/coating apparatus can apply a double bump of aqueous/flexographic or UV-curable printing ink or coating material to a plate on the plate cylinder, while simultaneously applying aqueous, flexographic or UV-curable printing ink or coating material to a plate or a blanket on the blanket cylinder, and thereafter onto a sheet as the sheet is transferred through the nip between the blanket cylinder and the impression cylinder. A triple bump is printed or coated on the last printing unit with the aid of an impression cylinder inking/coating unit.

* * * * * * *

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD

96250220.9



FIG. 1



FIG. 2

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 3

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 4

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 5

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 6



FIG. 7

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 8



FIG. 9

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 10



FIG. 11



FIG. 12



FIG. 13

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 14

FIG. 15

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 16



FIG. 17

HOWARD W. DEMOORE
RONALD M. RENDLEMAN
JOHN W. BIRD



FIG. 18

(5006793) RECEIVING SECTION
(PGP790) ZAHLUNGSBELEG - PAYMENT - PAIEMENT 30/10/96

FINANZ GENERATED CODING

DOSSIER NR: 96250220.9 DFIL: 02.10.96

NR: 96250220.9 2 962502209

P 44214 /

28000327 UEXKÜLL & STOLBERG
BESELERSTRASSE 4
D-22607 HAMBURG DEUTSCHLAND

001	DEM	600,00	FFEE11	231096!
002	DEM	1900,00	SFEE11	231096!
005	DEM	5950,00	DEST13AT	231096!
			DEST13BE	231096!
			DEST13CH	231096!
			DEST13DE	231096!
			DEST13DK	231096!
			DEST13ES	231096!
			DEST13FI	231096!
			DEST13FR	231096!
			DEST13GB	231096!
			DEST13GR	231096!
			DEST13IE	231096!
			DEST13IT	231096!
			DEST13LU	231096!
			DEST13MC	231096!
			DEST13NL	231096!
			DEST13PT	231096!
			DEST13SE	231096!
015	DEM	1120,00	CLMS12	231096!

101150.96/571360

BELEG-NR : 00669898
REFERENCE-NR: 009

(5006793) RECEIVING SECTION
(PGP790) ZAHLUNGSBELEG - PAYMENT - PAIEMENT 30/10/96

FINANZ GENERATED CODING

DOSSIER NR: 96250220.9 DFIL: 02.10.96

NR: 96250220.9 2 962502209

P 44214

28000327 UEXKÜLL & STOLBERG
BESELERSTRASSE 4
D-22607 HAMBURG DEUTSCHLAND

055 DEM 40,00 (X 1) ASOC13 231096!

09315796-051101

W BORIWSKI 05. 11. 96

BELEG-NR : 00669898
REFERENCE-NR: 009

P.B. 5818 - Patentlaan 2
2280 HV Rijswijk (ZH)
(070) 3 40 20 40
TX 31651 epo nl
FAX (070) 3 40 30 16

Europäisches Patentamt
Zweigstelle in Den Haag Recherchenabteilung

European Patent Office
Branch at The Hague Search division

Office européen des brevets
Département à La Haye Division de la recherche

UEXKÜLL & STOLBERG
Patentanwälte
Beselerstrasse 4
22607 Hamburg
ALLEMAGNE

Datum/Date
23.04.98

Zeichen/Ref./Ref.	Anmeldung Nr./Application No./Demande n°./Patent Nr./Patent No./Brevet n°.
P 44214	96250220.9-2304-

Anmelder/Applicant/Demandeur/Patentinhaber/Proprietor/Titulaire
DeMoore, Howard W.

EP 0 756 360 A1

COMMUNICATION

The European Patent Office herewith transmits as an enclosure the European search report for the above-mentioned European patent application.

If applicable, copies of the documents cited in the European search report are attached.

☒ Additional set(s) of copies of the documents cited in the European search report is (are) enclosed as well.

The following specifications given by the applicant have been approved by the Search Division:

☐ abstract ☒ title

☒ The abstract was modified by the Search Division and the definitive text is attached to this communication,

The following figure will be published together with the abstract: 1

EUROPÄISCHES PATENTAMT · DEN HAAG · EUROPEAN PATENT OFFICE · THE HAGUE · OFFICE EUROPÉEN DES BREVETS · LA HAYE

REFUND OF THE SEARCH FEE

If applicable under Article 10 Rules relating to fees, a separate communication from the Receiving Section on the refund of the search fee will be sent later.

European Patent Office

EUROPEAN SEARCH REPORT

Application Number
EP 96 25 0220

DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
D,Y	US 4 615 293 A (HEIDELBERGER DRUCKMASCHINEN AG) * the whole document *	1,2,4,6, 7,15,18	B41F31/18
Y	EP 0 293 586 A (M.A.N.-ROLAND DRUCKMASCHINEN AKTIENGESELLSCHAFT) Abstract; fig.1	1,2,4,7, 15,18	
Y	GB 2 263 438 A (THE LANGSTON CORPORATION) Abstract;fig.1-3	1,2,4,7, 15,18	
Y	CH 319 962 A (MASCHINENFABRIK WINKLER, FALLERT & CO.) * the whole document *	6	

TECHNICAL FIELDS SEARCHED (Int.Cl.6)

B41F

The present search report has been drawn up for all claims

Place of search	Date of completion of the search	Examiner
THE HAGUE	11 March 1998	Loncke, J

CATEGORY OF CITED DOCUMENTS

X : particularly relevant if taken alone
Y : particularly relevant if combined with another document of the same category
A : technological background
O : non-written disclosure
P : intermediate document

T : theory or principle underlying the invention
E : earlier patent document, but published on, or after the filing date
D : document cited in the application
L : document cited for other reasons

& : member of the same patent family, corresponding document

EPO FORM 1503 03.82 (P04C01)

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO. EP 96 25 0220

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

11-03-1998

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4615293 A	07-10-86	DE 3327993 A	21-02-85
		FR 2550130 A	08-02-85
		GB 2144372 A,B	06-03-85
		JP 1749250 C	08-04-93
		JP 4039428 B	29-06-92
		JP 60054850 A	29-03-85
EP 293586 A	07-12-88	US 4796528 A	10-01-89
		CA 1299915 A	05-05-92
		DE 3876293 A	14-01-93
		JP 63312149 A	20-12-88
GB 2263438 A	28-07-93	US 5243907 A	14-09-93
		DE 4301427 A	29-07-93
		FR 2687096 A	13-08-93
		US RE35471 E	11-03-97
CH 319962 A		NONE	

ABSTRACT / ZUSAMMENFASSUNG / ABREGE

96250220.9

A retractable in-line inking/coating apparatus can apply either spot or overall inking/coating material to a plate and/or a blanket on the first printing unit or on any consecutive printing unit of any rotary offset printing press. The inking/coating apparatus is pivotally mounted within the conventional dampener space of any lithographic printing unit. The aqueous component of the flexographic printing ink or aqueous coating material is evaporated and dried by high velocity, hot air dryers and high performance heat and moisture extractors so that the aqueous or flexographic ink or coating material on a freshly printed or coated sheet is dry and can be dry-trapped on the next printing unit. The inking/coating apparatus includes dual cradles that support first and second applicator rollers (66/67) so that the inking/coating apparatus can apply a double bump of aqueous/flexographic or UV-curable printing ink or coating material to a plate on the plate cylinder (32), while simultaneously applying aqueous, flexographic or UV-curable printing ink or coating material to a plate or a blanket on the blanket cylinder (34), and thereafter onto a sheet as the sheet is transferred through the nip between the blanket cylinder (34) and the impression cylinder (36). A triple bump is printed or coated on the last printing unit with the aid of an impression cylinder inking/coating unit.